

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
29 November 2001 (29.11.2001)

PCT

(10) International Publication Number  
**WO 01/90883 A2**

(51) International Patent Classification<sup>7</sup>: **G06F 9/00**

**Mohamed, M.**; 78 Cabot Ave., Santa Clara, CA 95051 (US).

(21) International Application Number: PCT/US01/15120

(22) International Filing Date: 9 May 2001 (09.05.2001)

(74) Agent: **KOWERT, Robert, C.**; Conley, Rose & Tayon, P.C., P.O. Box 398, Austin, TX 78767-0398 (US).

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/202,975	9 May 2000 (09.05.2000)	US
60/208,011	26 May 2000 (26.05.2000)	US
60/209,430	2 June 2000 (02.06.2000)	US
60/209,140	2 June 2000 (02.06.2000)	US
60/209,525	5 June 2000 (05.06.2000)	US
09/672,200	27 September 2000 (27.09.2000)	US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

(71) Applicant: **SUN MICROSYSTEMS, INC.** [US/US]; 901 San Antonio Road, Palo Alto, CA 94303 (US).

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).


(72) Inventors: **SLAUGHTER, Gregory, L.**; 3326 Emerson St., Palo Alto, CA 94306 (US). **SAULPAUGH, Thomas, E.**; 6938 Bret Harte Dr., San Jose, CA 95120 (US). **TRAVERSAT, Bernard, A.**; 2055 California St., Apartment 402, San Francisco, CA 94109 (US). **ABDELAZIZ,**

**Published:**

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: REMOTE FUNCTION INVOCATION WITH MESSAGING IN A DISTRIBUTED COMPUTING ENVIRONMENT



(57) Abstract: An interface between clients and services in a distributed computing environment is described. Method gates may provide an interface to remotely invoke functions of a service. A method gate may be generated from an advertisement that may include definitions for one or more messages for remotely invoking functions of the service. A client may generate messages containing representations of method calls. The service may invoke functions that correspond to the set of messages. A method gate on the service may unmarshal the message and invoke the function. The client may receive the results of the function directly. Alternatively, the results may be stored, an advertisement to the results may be provided, and a gate may be generated to access the results. Message gates may perform the sending and receiving of the messages between the client and service. In one embodiment, functions of the service may be computer programming language (e.g. Java) methods. In one embodiment, a message including a representation of a method call may be generated when no actual method call was made. In one embodiment, a method call may be transformed into messages that may be sent to the service; the service may not know that the messages were generated from a method call. In one embodiment, a service may transform messages requesting functions into method calls; the client may not know that the service is invoking methods to perform the functions.



---

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**TITLE: REMOTE FUNCTION INVOCATION WITH MESSAGING IN A DISTRIBUTED  
COMPUTING ENVIRONMENT**

**BACKGROUND OF THE INVENTION**

5

1. Field of the Invention

This invention relates to distributed computing environments including Web-centric and Internet-centric distributed computing environments, and more particularly to a heterogeneous distributed computing environment including a remote function invocation mechanism based upon a message passing model for connecting network  
10 clients and services.

2. Description of the Related Art

Intelligent devices are becoming increasingly common. Such devices range from smart appliances, personal digital assistants (PDAs), cell phones, lap top computers, desktop computers, workstations, mainframes;  
15 even, super computers. Networks are also becoming an increasingly common way to interconnect intelligent devices so that they may communicate with one another. However, there may be large differences in the computing power and storage capabilities of various intelligent devices. Devices with more limited capabilities may be referred to as small footprint devices or "thin" devices. Thin devices may not be able to participate in networks interconnecting more capable devices. However, it may still be desirable to interconnect a wide variety  
20 of different types of intelligent devices.

The desire to improve networking capabilities is ever increasing. Business networks are expanding to include direct interaction with suppliers and customers. Cellular phones, personal digital assistants and Internet-enabled computers are commonplace in both business and the home. Home networks are available for interconnecting audio/visual equipment such as televisions and stereo equipment to home computers, and other  
25 devices to control intelligent systems such as security systems and temperature control thermostats. High bandwidth mediums such as cable and ADSL enable improved services such as Internet access video on demand, e-commerce, etc. Network systems are becoming pervasive. Even without a formal network, it is still desirable for intelligent devices to be able to communicate with each other and share resources.

Currently, traditional networks are complex to set up, expand and manage. For example, adding  
30 hardware or software to a network often requires a network administrator to load drivers and configure systems. Making small changes to a network configuration may require that the entire network be brought down for a period. In addition, certain intelligent devices may not support the necessary interfaces to communicate on a given network.

What is needed is a simple way to connect various types of intelligent devices to allow for  
35 communication and sharing of resources while avoiding the interoperability and complex configuration problems existing in conventional networks. Various technologies exist for improving the addition of devices to a network. For example, many modern I/O buses, such as the Universal Serial Bus, 1394 and PCI, support plug and play or dynamic discovery protocols to simplify the addition of a new device on the bus. However, these solutions are limited to specific peripheral buses and are not suitable for general networks.

A more recent technology, Jini from Sun Microsystems, Inc., seeks to simplify the connection and sharing of devices such as printers and disk drives on a network. A device that incorporates Jini may announce itself to the network, may provide some details about its capabilities, and may immediately become accessible to other devices on the network. Jini allows for distributed computing where the capabilities of the various devices are shared on a network. The Jini technology seeks to enable users to share services and resources over a network. Another goal of the Jini technology is to provide users with easy access to resources anywhere on the network while allowing the network location of the user to change. Jini also seeks to simplify the task of building, maintaining and altering a network of devices, software and users.

Jini requires that each Jini enabled device have a certain amount of memory and processing power. Typically, a Jini enabled device is equipped with a Java Virtual Machine (JVM). Thus, Jini systems are Java technology centered. Java is a high level object oriented programming language developed by Sun Microsystems, Inc. Java source code may be compiled into a format called bytecode, which may then be executed by a Java Virtual Machine.

Bytecode is computer source code that is processed by a virtual machine, rather than the "real" computer machine, the hardware processor. The virtual machine converts generalized machine instruction (the bytecode) into specific machine instructions (instructions that the computer's processor will understand). Using a language that comes with a virtual machine for each platform, the source language statements may be compiled only once and may then run on any platform that supports the virtual machine. The Java programming language is an example of such a language, and the Java Virtual Machine (JVM) is an example of a virtual machine platform that supports programs written in the Java programming language.

Since Java Virtual Machines may be provided for most computing platforms, Java and thus Jini provide for a certain amount of platform independence. The Jini architecture leverages off the assumption that the Java programming language is the implementation language for the components of the Jini system. The ability to dynamically download and run Java code is central to many features of the Jini architecture.

The purpose of the Jini architecture is to federate groups of devices and software components into a single dynamic distributed system. A key concept within the Jini architecture is that of a service. A service is an entity that can be used by a person, a program, or another service. Two examples of services are printing a document and translating from one word processor format to another. Jini allows the members of a Jini system to share access to services. Services in a Jini system communicate with each other by using a service protocol, which is a set of interfaces written in the Java programming language. Services are found and resolved in a Jini system by a look-up service. A look-up service maps interfaces indicating the functionality provided by a service to sets of objects that implement the service.

Descriptive entries may also be associated with a service. Devices and applications use a process known as discovery to register with the Jini network. Once registered, the device or application places itself in the look-up service. The look-up service may store not only pointers to these services on the network, but also may store the code for accessing these services. For example, when a printer registers with the look-up service, it loads its printer driver and/or an interface to the driver into the look-up service. When a client wants to use the printer, the driver and driver interface are downloaded from the look-up service to the client. This code mobility means that clients can take advantage of services from the network without pre-installing or loading drivers or other software.



Communication between services in a Jini system is accomplished using the Java Remote Method Invocation (RMI). RMI is a Java programming language enabled extension to traditional remote procedure call mechanisms. RMI allows not only data to be passed from object to object around the Jini network, but full objects including code as well. Jini systems depend upon this ability to move code around the network in a form that is encapsulated as a Java object.

Access to services in a Jini system is lease based. A lease is a grant of guaranteed access over a time. Each lease is negotiated between the user of the service and the provider of the service as part of the service protocol. A service may be requested for some period and access may be granted for some period presumably considering the request period. Leases must be renewed for a service to remain part of the Jini system.

Figure 1 illustrates the basic Jini technology stack. The Jini technology defines a distributed programming model (supported by JavaSpaces, leases, and object templates). Object communication in Jini is based on an RMI layer over a TCP/IP capable networking layer.

Jini is a promising technology for simplifying distributed computing. However, for certain types of devices, Jini may not be appropriate. The computing landscape is moving toward a distributed, Web-centric service and content model where the composition of client services and content changes rapidly. The client of the future may be a companion type device that users take with them wherever they go. Such a device may be a combination of a cell phone and a PDA for example. It would be desirable for such devices to be able to communicate and share resources with devices that are more powerful, as well as with thinner or less powerful devices.

In addition, with the advent of the Internet and resulting explosion of devices connected to the net, a distributed programming model designed to leverage this phenomenon is needed. An enabling technology is needed that facilitates clients connecting to services in a reliable and secure fashion. Various clients from thick to thin and services need to be connected over the Internet, corporate Internets, or even within single computers. It is desirable to abstract the distance, latency and implementation from both clients and services.

The key challenge for distributed computing technology is to be scalable from powerful thick clients down to very thin clients such as embedded mobile devices. Current distributed computing technologies, such as Jini, may not be scalable enough for the needs of all types of clients. Some devices, such as small footprint devices or embedded devices, may lack sufficient memory resources and/or lack sufficient networking bandwidth to participate satisfactorily in current distributed computing technologies. The low end of the client spectrum, including embedded mobile devices, often have limited or fixed code execution environments. These devices also may have minimal or no persistent storage capabilities. Most small, embedded mobile devices do not support a Java Virtual Machine. Most code-capable small clients run native code only. In addition, most small devices have little more than flash memory or battery backed RAM as their sole persistent storage media. The size of the storage is often very small and sometimes read-only in nature. Furthermore, the access time of this type of storage media is often an order of magnitude greater than hard disk access time in clients that are more powerful.

Existing connection technologies, such as Jini, may not be as scalable as desired because they are too big. For example, Jini requires that all participants support Java; however, many small clients may not have the resources for a Java Virtual Machine. Furthermore, due to its use of RMI, Jini requires that clients be able to download code and content. Jini may augment the existing client platform by downloading new classes, which

may pose security and size concerns for small devices such as embedded devices. Jini works by clients and resources communicating by passing code and data. When a client activates a Jini service, the service may return its results to the client, which may include a large amount of code or content. In Jini, a client may call a method and a large object may be returned, and thus downloaded. The client may not have the resource to accept the returned object. In addition, RMI and Java itself require a lot of memory. Many small foot print devices may not have the resources to participate effectively or at all in current distributed computing technologies.

Another concern with existing distributed computing technologies is that they often require certain levels of connection capability and protocols. For example, Jini assumes the existence of a network of reasonable speed for connecting computers and devices. Jini also requires devices to support TCP/IP network transport protocol. However, many smaller devices may have limited connection capabilities. Small devices may have high latency or low speed network connections and may not support TCP/IP.

As mentioned above, Jini requires devices to support Java and thus include a Java Virtual Machine, which requires a certain amount of processing and storage capabilities that might not be present for many small devices. This also restricts the flexibility of Jini in that non-Java devices may not directly participate in a Jini system. Since Jini requires Java, it may be deemed a homogenous environment. However, it is desirable to have a distributed computing facility for heterogeneous distributed computing that scales from extremely small embedded devices through PDA's and cell phones to laptops and beyond even to the most powerful computers.

Other heterogeneous solutions exist, such as the Common Object Request Broker Architecture (CORBA). CORBA is an architecture that enables program objects to communicate with one another regardless of the programming language they were written in or what operating system they're running on. However, CORBA does not address all of the connection issues that are addressed by Jini. In addition, CORBA suffers from similar scalability problems as Jini.

Technology such as Jini and CORBA use a code-centric programming model to define the interface between remote components. A code-centric programming model defines programmatic interfaces or API's for communication between remote clients or components. The API's may be defined in a particular programming language. The API's must be agreed to by all software components to ensure proper interoperability. Since all access to components is through these standards API's, the code that implements these API's must be present in the client platform. The code may be statically linked into the platform or dynamically downloaded when needed. Many embedded or mobile devices simply cannot accept code dynamically from a network due to the quality control issues involved as well as the reliance on a single language and program execution environment. Data-centric models, such as networking protocols, may avoid the dependence on moving code; however, such protocols are not rich enough to easily provide for distributed computing and they also lack the ease of programming with code and other programming features, such as type safety.

Conventional distributed computing systems rely on the ability of a program executing on a first device to be able to remotely call a program on a second device and have the results returned to the first device. The Remote Procedure Call (RPC) is a basic mechanism for remotely calling a program or procedure. CORBA and Jini are both based on the ability to remotely invoke program methods. However, communicating by passing code or objects, such as in Jini or CORBA, may be somewhat complex. For example, as mentioned above, Jini uses the Java Remote Method Invocation (RMI) to communicate between services. In order for a client to move Java

objects to and from remote locations, some means of serialization/deserialization is needed. Such current facilities in the Java Development Kit (JDK) rely upon the reflection API to determine the content of a Java object, and ultimately that code must consult the Virtual Machine. This code is quite large and inefficient.

The fundamental problems with the current method for doing serialization/deserialization include its size, speed, and object traversal model. Code outside the JVM does not know the structure or graph of a Java object and thus must traverse the object graph, pulling it apart, and ultimately must call upon the JVM. Traditional serialization and reflection mechanisms for storing and moving Java objects are just not practical for all types of devices, especially thinner devices. Some of the difficulties with Java reflection and serialization are that an object's graph (an object's transitive closure) reflection is difficult to do outside the JVM. Serialization is too large, requiring a large amount of code. In addition, serialization is a Java specific object interchange format and thus may not be used with non-Java devices.

The Jini distributed computing model requires the movement of Java objects between Java devices. Thus, the serialization mechanism itself is not platform independent since it may not be used by non-Java platforms to send and receive objects. Serialization is a homogenous object format – it only works on Java platforms. Serialization uses the reflection API and may be limited by security concerns, which often must be addressed using native JVM dependent methods. The reflection API may provide a graph of objects, but is inefficient due to the number of calls between the JVM and the code calling the reflection methods.

The use of Java reflection to serialize an object requires an application to ping pong in and out of the JVM to pick apart an object one field at a time as the transitive closure of the object is dynamically analyzed. Deserializing an object using Java deserialization requires the application to work closely with the JVM to reconstitute the object one field at a time as the transitive closure of the object is dynamically analyzed. Thus, Java serialization/deserialization is slow and cumbersome while also requiring large amounts of application and JVM code as well as persistent storage space.

Even for thin clients that do support Java, the Jini RMI may not be practical for thin clients with minimal memory footprints and minimal bandwidth. The serialization associated with the Jini RMI is slow, big, requires the JVM reflection API, and is a Java specific object representation. Java deserialization is also slow, big and requires a serialized-object parser. Even Java based thin clients may not be able to accept huge Java objects (along with needed classes) being returned (necessarily) across the network to the client as required in Jini. A more scalable distributed computing mechanism is needed. It may be desirable for a more scalable distributed computing mechanism to address security concerns and be expandable to allow for the passing of objects, such as Java objects, and even to allow for process migration from one network mode to another.

Object based distributed computing systems need persistent storage. However, as discussed above, attempts at object storage are often language and operating system specific. In addition, these object storage systems are too complicated to be used with many small, embedded systems. For example, the Jini technology uses JavaSpaces as persistent object containers. However, a JavaSpace can only store Java objects and cannot be implemented in small devices. Each object in a JavaSpace is serialized and pays the above-described penalties associated with Java serialization. It may be desirable to have a heterogeneous object repository for distributed computing that may scale from small to large devices.

JavaSpaces from Sun Microsystems, Inc., draws from the parallel processing work of David Gelernter, a computer science professor at Yale University. Gelernter's set of functions named "Linda" create a shared memory space called a TupleSpace, in which results of a computer's processes or the processes themselves may be stored for access by multiple CPUs. Linda therefore provides a global shared memory for multiple processors.

5 Another technology which extends Linda is TSpaces from IBM Corporation. TSpaces extends the basic Linda TupleSpace framework with real data management and the ability to download new data types and new semantic functionality. TSpaces provides a set of network communication buffers and a set of APIs for accessing those buffers. Like many of the solutions discussed above, TSpaces therefore uses a code-centric programming model and shares the drawbacks of such a model. Additionally, TSpaces is implemented in the Java programming language and therefore requires a Java Virtual Machine or other means of executing Java bytecode, such as a Java-capable microprocessor. Therefore, TSpaces may be inappropriate for small-footprint devices which cannot devote sufficient resources for executing Java bytecode.

10 It is desirable in object oriented distributed systems to be able to locate object repositories and find particular objects within those repositories. As mentioned above, the Jini look-up server may not be practical for small devices with small memory footprints. A more efficient mechanism for locating object stores may be desirable.

15 It may be desirable in a distributed network computing model for clients to have the ability to locate services. Current network protocols either provide only a single standard service access interface that provides no security when accessing a network service or provides "all or nothing" access to the full range of the service's capabilities, which may include administrator or privileged functions. Also, current network protocols to locate services do not provide a flexible mechanism for finding services. Current protocols either do not provide any selective search capability at all (e.g. UPnP) or only provide a primitive keyword and attribute grammar mechanism (e.g. SLP). Thus, current service discovery mechanism may be too inflexible in their security and search criteria mechanisms.

20 Also, current service discovery models have a symmetric model for service location. However, it may be a waste of resources for certain service devices, such as devices whose functionality is available on a proximity basis, to support the discovery model. This is because such devices are already located by proximity (e.g. one device physically pointing to another one). Thus, an alternate light-weight discovery mechanism may also be desirable for such devices.

25 Distributed object access also desires a fair and efficient sharing mechanism. As described above Jini currently uses a leasing mechanism to share objects. However, Jini leases are time based which may result in a number of problems. For example, the current object holder might have no idea how long to lease an object and may hold it too long. In addition, the use of time-based leases may require that time be synchronized between multiple machines. Moreover time based leasing may require operating system support. In addition, Jini leases are established and released via RMI. Thus, the Jini leasing mechanism suffers from the above-noted problems with using RMI. In addition, the Jini leasing mechanism does not provide a security mechanism for establishing, renewing and canceling of leases. Other leasing mechanisms may be desirable.

30 Generally speaking, it is desirable for small memory foot print mobile client devices to be able to run a variety of services, both legacy and new, in a distributed environment. The types of small clients may include cell

phones and PDA's with a variety of different networking interfaces, typically low bandwidth. Often these devices have very small displays with limited graphics, but they could include laptops and notebook computers, which may have a larger display and more sophisticated graphics capabilities. The services may be a wide range of applications as well as control programs for devices such as printers. It is desirable for a mobile client to be able to use these services wherever they may be.

A mobile client will often be at a temporary dynamic network address, so networking messages it sends cannot be routed beyond that networking interface (otherwise there may be collisions when two different clients on different networks have the same dynamic address). Mobile clients often do not have the capability for a full function browser or other sophisticated software. The displays may limit the client from running certain applications. Traditional application models are based on predetermined user interface or data characteristics. Any change to the application requires recompilation of the application.

It may be desirable for such clients to have a mechanism for finding and invoking distributed applications or services. The client may need to run even large legacy applications which could not possibly fit in the client's memory footprint. As discussed above, current technology, such as Jini, may not be practical for small footprint devices. The pervasiveness of mobile thin clients may also raise additional needs. For example, it may be desirable to locate services based on the physical location of the user and his mobile client. For example, information about the services in a local vicinity may be very helpful, such as local restaurants, weather, traffic maps and movie information. Similarly, information about computing resources, such as printers in a particular location, may be helpful. Current technologies do not provide an automatic mechanism for locating services based on physical location of the client. Another need raised by thin mobile clients is that of addressing the human factor. Thin mobile clients typically do not contain ergonomic keyboards and monitors. The provision of such human factor services and/or the ability to locate such services in a distributed computing environment may be desirable.

A distributed computing model should provide clients with a way to find transient documents and services. It may be desirable to have a mechanism for finding general-purpose documents (including services and/or service advertisements), where the documents are expressed in a platform-independent and language-independent typing such as that provided by eXtensible Markup Language (XML). Current approaches, including lookup mechanisms for Jini, Universal Plug and Play (UPnP), and the Service Location Protocol (SLP), do not support such a general-purpose document lookup mechanism. For example, the Jini lookup mechanism is limited to Java Language typing and is therefore not language-independent. UPnP and SLP support a discovery protocol only for services, not for general-purpose documents.

## SUMMARY OF THE INVENTION

Embodiments of method gates are described that provide a method interface between clients and services in a distributed computing environment. A method gate may be bi-directional, allowing remote method invocations from client to service and from service to client. A method gate may be generated from schema information (e.g. from a service advertisement in a space). The schema information may include definitions for one or more method interfaces. From this information, code may be generated as part of the gate for interfacing to one or more methods. Each method invocation (e.g. from a client application) in the generated code may cause a

message to be sent to the service containing the marshaled method parameters. The message syntax and parameters to be included may be specified in the schema. Thus, the method gate provides a message interface to remotely invoke a service method. The method gate may be generated on the client or proxied on a server, such as the space server where the service method was advertised or a special gateway server.

5 A service may have a corresponding method gate that implements or is linked to a set of object methods that correspond to the set of method messages defined in the service's data representation language schema. There may be a one to one correspondence between the object methods implemented by or linked to the service's method gate and the method messages defined by the service's schema. Once a service's corresponding method receives a message from a client to invoke one of the service's methods, the service's method gate may unmarshal or unpack  
10 the parameters of the message invocation and then invoke the method indicated by the received message and pass the unmarshaled parameters.

The method gate may provide a synchronous request-response message interface in which clients remotely call methods causing services to return results. The underlying message passing mechanics may be completely hidden from the client. This form of remote method invocation may deal with method results as  
15 follows. Instead of downloading result objects (and associated classes) into the client, only a result reference or references may be returned in data representation language messages, in one embodiment. An object reference may be a generated results gate representing the real object result. In other embodiments, the client may choose to receive the actual result object. In addition, once a client has received a result object reference, the client may use this reference to receive or manipulate the actual result object. In one embodiment, the result reference includes  
20 one or more URIs to the real result.

The real result object(s) may be stored in a service results space. This temporary results space may act as a query results cache. Results returned from each method invocation may be advertised in the results space. A result itself may be or may include a method that could then be remotely instantiated by a client, thus generating its own method gate. Therefore, the distributed computing environment may support recursive remote method  
25 invocation.

When a client uses a method gate to remotely invoke a service method, a reference to the method results may be returned from the service method gate instead of the actual results. From this reference, a results gate may be generated to access the actual result. Thus, the client or client method gate may receive a result URI and perhaps a result schema and/or authentication credential for constructing a gate to access the remote method  
30 results.

A service method gate may return a results gate to the client gate as the result of the method. The client may then use the results gate to access the actual results. In one embodiment, the client receiving the results gate cannot distinguish between the results gate and the result itself in which case the results gate may be an object proxy for the actual result object. The results gate may also be a method gate that supports remote method  
35 invocation to result objects. In this manner, a chain of parent and child method/results gates may be created.

Client and service message gates may perform the actual sending and receiving of the method invocation and results messages from the client to the service, using a protocol specified in a service advertisement.

In one embodiment, the remote methods may be Java methods. In this embodiment, method results may be correctly typed according to the Java typing system. When a Java method is remotely invoked as described

above, the results gate may be cast into the Java type that matches the result type. In this embodiment, method gates may be used in the distributed computing environment to allow remote Java objects to behave as local Java objects. The method invocation and results may appear the same to the client Java software program whether the real object is local or remote.

5 In one embodiment, a message including a representation of a method call may be generated on a client when no actual method call was made. In this embodiment, a process on the client may invoke computer programming language methods on a service without the client actually generating computer programming language method calls.

10 In one embodiment, a client may transform a method call into one or more messages that may be sent to the service, wherein the messages do not include information that may be unmarshaled into a method call, but instead include information that may be used by the service to perform a function on behalf of the client. In this embodiment, the service may not know that the messages were originally generated from a method call. These messages may still be considered a "representation" of the method call, but may not be in a form that the service recognizes as a marshaled method call that may be unmarshaled to regenerate a method call.

15 In one embodiment, a service may transform one or more messages requesting the service to perform one or more functions into a method call. In this embodiment, no method call may have been made on the client to generate the messages. Thus, the client may not know that the service is invoking a method to perform the requested function(s).

## 20 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is an illustration of a conventional distributed computing technology stack;

Figure 2 is an illustration of a distributed computing environment programming model according to one embodiment;

25 Figure 3 is an illustration of messaging and networking layers for a distributed computing environment according to one embodiment;

Figure 4 is an illustration of a discovery service for finding spaces advertising objects or services in a distributed computing environment according to one embodiment;

Figure 5 illustrates client profiles supporting static and formatted messages for a distributed computing environment according to one embodiment;

30 Figure 6 is an illustration of a distributed computing model employing XML messaging according to one embodiment;

Figure 7 illustrates a platform independent distributing computing environment according to one embodiment;

35 Figure 8 is an illustration of a distributed computing model in which services are advertised in spaces according to one embodiment;

Figure 9 is an illustration of a distributed computing model in which results are stored in spaces according to one embodiment;

Figure 10a is an illustration of client and service gates as messaging endpoints in a distributed computing model according to one embodiment;

Figure 10b is an illustration a message endpoint generation according to a schema for accessing a service according to one embodiment.

Figure 11a illustrates gate creation in a distributed computing environment according to one embodiment;

Figure 11b illustrates gate creation and gate pairs in a distributed computing environment according to one embodiment;

Figure 12 is an illustration of possible gate components in a distributed computing environment according to one embodiment;

Figure 13 is an illustration of proxy client for a conventional browser to participate in the distributed computing environment according to one embodiment;

Figure 14 illustrates the use of a method gate to provide a remote method invocation interface to a service in a distributed computing environment according to one embodiment;

Figure 15 is an illustration of the use of a space in a distributed computing environment according to one embodiment;

Figure 16 illustrates advertisement structure according to one embodiment;

Figure 17 illustrates one example of advertisement state transitions that an advertisement may undergo during its lifetime according to one embodiment;

Figure 18 is an illustration various space location mechanisms in a distributed computing environment according to one embodiment;

Figure 19 is an illustration of space federations in a distributed computing environment according to one embodiment;

Figure 20 is a flow diagram illustrating client formation of a session with a space service in a distributed computing environment according to one embodiment;

Figure 21 is an illustration of a space event type hierarchy for one embodiment;

Figure 22 is a flow diagram illustrating service instantiation in a distributed computing environment according to one embodiment;

Figure 23 is an illustration of a default space in a distributed computing environment according to one embodiment;

Figure 24 illustrates an example of a device bridging proximity-based devices onto another transport mechanism to allow the services provided by the proximity-based devices to be accessed by devices outside the proximity range of the devices, according to one embodiment;

Figure 25 is an illustration of the use of lease renewal messages in a distributed computing environment according to one embodiment;

Figure 26a is a flow diagram illustrating an authentication service providing an authentication credential to a client according to one embodiment;

Figure 26b is a flow diagram expanding on step 1002 of Figure 26a and illustrating an authentication service generating an authentication credential according to one embodiment;

Figure 27 illustrates one embodiment of a bridging mechanism;

Figure 28 illustrates an example of a space discovery protocol mapped to an external discovery service according to one embodiment;



Figure 29 illustrates bridging a client external to the distributed computing environment to a space in the distributed computing environment according to one embodiment;

Figure 30 is an illustration of a proxy mechanism according to one embodiment;

Figure 31 illustrates one embodiment of a client with an associated display and display service according to one embodiment;

Figures 32A and 32B illustrate examples of using schemas of dynamic display objects according to one embodiment;

Figure 33A illustrates a typical string representation in the C programming language;

Figure 33B illustrates an example of a conventional string function;

Figure 33C illustrates an efficient method for representing and managing strings in general, and in small footprint systems such as embedded systems in particular according to one embodiment;

Figure 34 illustrates a process of moving objects between a client and a service according to one embodiment;

Figures 35a and 35b are data flow diagrams illustrating embodiments where a virtual machine (e.g. JVM) includes extensions for compiling objects (e.g. Java Objects) into XML representations of the objects, and for decompiling XML representations of (Java) objects into (Java) objects;

Figure 36 illustrates a client and a service accessing store mechanisms in the distributed computing environment, according to one embodiment;

Figure 37 illustrates process migration using an XML representation of the state of a process, according to one embodiment;

Figure 38 illustrates a mobile client device accessing spaces in a local distributed computing network, according to one embodiment;

Figure 39a illustrates a user of a mobile device discovering the location of docking stations, according to one embodiment;

Figure 39b illustrates a mobile client device connecting to a docking station, according to one embodiment;

Figure 40a illustrates an embodiment of embedded devices controlled by a control system and accessible within the distributed computing environment, according to one embodiment;

Figure 40b illustrates a device control system connected via a network (e.g. the Internet) to embedded devices accessible within the distributed computing environment, according to one embodiment;

Figure 41 is a flow diagram illustrating creating a gate according to one embodiment;

Figure 42a is a flow diagram illustrating a client sending a message to a service according to one embodiment;

Figure 42b is a flow diagram illustrating a service receiving a message from a client and using an authentication service to authenticate the message according to one embodiment;

Figure 42c is a flow diagram illustrating the general process of a client and service exchanging messages with embedded authentication credential according to one embodiment;

Figure 43 is a flow diagram illustrating a mechanism for checking the integrity of messages according to one embodiment;

Figure 44 is a flow diagram illustrating a mechanism for leasing resources according to one embodiment;

Figures 45a-45e are flow diagrams illustrating various embodiments of a mechanism for communicating between clients and services using method gates;

Figure 46 is a flow diagram illustrating a mechanism for sending objects from services to clients using XML representations of the objects;

Figure 47 is a flow diagram illustrating a mechanism for secure object decompilation on a client device; and

Figure 48 is a flow diagram illustrating a mechanism for migrating processes using data representation language representations of the processes in a distributed computing environment.

While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and will herein be described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention.

## DETAILED DESCRIPTION OF EMBODIMENTS OF THE INVENTION

### Overview of Embodiments for Distributed Computing

Turning now to Figure 2, a distributed computing environment programming model is illustrated. The model includes API layer 102 for facilitating distributed computing. The API layer 102 provides an interface that facilitates clients connecting to services. The API layer 102 is concerned with the discovery of and the connecting of clients and services. The API layer 102 provides send message and receive message capabilities. This messaging API may provide an interface for simple messages in a representation data or meta-data format, such as in the eXtensible Mark-up Language (XML). Note that while embodiments are described herein employing XML, other meta-data type languages or formats may be used in alternate embodiments. In some embodiments, the API layer may also provide an interface for messages to communicate between objects or pass objects, such as Java objects. APIs may be provided to discover an object repository or "space", find a particular object, claim and release an object, and write or take an object to or from the object repository. Objects accessible through API layer 102 may be represented by a representation data format, such as XML. Thus, an XML representation of an object may be manipulated, as opposed to the object itself.

API layer 102 sits on top of a messaging layer 104. The messaging layer 104 is based on a representation data format, such as XML. In one embodiment, XML messages are generated by messaging layer 104 according to calls to the API layer 102. The messaging layer 104 may provide defined static messages that may be sent between clients and services. Messaging layer 104 may also provide for dynamically generated messages. In one embodiment, an object, such as a Java object, may be dynamically converted into an XML representation. The messaging layer 104 may then send the XML object representation as a message. Conversely, the messaging layer 104 may receive an XML representation of an object. The object may then be reconstituted from that message.

In one embodiment, messages sent by messaging layer 104 may include several basic elements, such as an address, authentication credentials, security tokens, and a message body. The message system transmission and receive mechanisms may be completely stateless. Any notion of state may be embedded in the message stream

between sender and receiver. Thus, message transmission may be done asynchronously. In a preferred embodiment, no connection model is imposed. Thus, transports such as TCP are not required. Also, error conditions may be limited to non-delivery or security exceptions.

Messaging layer 104 sits on top of a message capable networking layer 106. In a preferred embodiment, messaging layer 104 does not require that a particular networking protocol be used. TCP/IP and UDP/IP are examples of message capable protocols that may be used for message capable networking layer 106. However, other more specialized protocols such as the Wireless Application Protocol (WAP) may also be used. Other possible message protocols are IrDA and Bluetooth network drivers beneath the transport layer. Networking layer 106 is not limited to a single reliable connection protocol, such as TCP/IP. Therefore, connection to a larger variety of devices is possible.

In one embodiment, message capable network layer 106 may be implemented from the networking classes provided by the Java2 Micro Edition (J2ME) platform. The Java2 Micro Edition platform may be suitable for smaller footprint devices that do not have the resources for a full Java platform or in which it would not be efficient to run a full Java platform. Since J2ME already provides a message capable family of networking protocols (to support sockets), it follows that for the small footprint cost of adding messaging layer 104, distributing computing facilities may be provided for small devices that already include J2ME.

Message capable networking layer 106 may also be provided by the Java Development Kit's (JDK) java.net networking classes. Alternatively, any message capable networking facilities may be used for message capable networking layer 106. In a preferred embodiment, a reliable transport is not required, thus embedded devices supporting an unreliable data gram transport such as UDP/IP may still support the messaging layer.

Thus, thin clients may participate in a distributed computing environment by simply adding a thin messaging layer 104 above a basic networking protocol stack. As shown in Figure 3, a basic system includes messaging layer 104 on top of a networking layer 106. The networking layer may provide for reliable messages, e.g. TCP, or unreliable messages, e.g. UDP. The Internet Protocol (IP) is shown in Figure 3 as an example of protocol that may be used in networking layer 106. However, the distributed computing environment does not require IP. Other protocols may be used in the distributed computing environment besides IP. A network driver such as for Ethernet, Token Ring, Bluetooth, etc. may also be part of the networking layer. Many small clients already provide a network driver and transport protocol such as UDP/IP. Thus, with the addition of the thin XML based messaging layer, the device may participate in the distributed computing environment.

Thus, the foundation for the distributed computing environment is a simple message passing layer implemented on top of reliable connection and/or unreliable data grams. The messaging technology is very different from communications technologies employed in other distribution computing systems, such as Jini which employs the Java remote method invocation (RMI). The message passing layer 104 supports an asynchronous, stateless style of distributed programming, instead of the synchronous, state-full style predicated by RMI. Moreover, message passing layer 104 is based on a data representation language such as XML and thus copies data, but not code, from source to destination, unlike RMI. By using a representation data language, such as XML, messaging layer 104 may interoperate with non-Java and non-Jini platforms in a seamless fashion because Java code is not assumed on the sending or receiving end of a message. Moreover, unlike RMI, messaging layer 104 does not require a reliable transport mechanism such as TCP/IP.

The message passing layer may provide simple send() and receive() methods to send a message specified as an array or string of bytes, for example. The send() method may return immediately, performing the data transfer asynchronously. For flow control purposes a callback method may be supplied which is invoked in the event that the send() method throws an exception indicating it cannot handle the send() request. The receive() method may be synchronous and may return the next available message.

The message passing layer may also provide methods for storing XML representations of objects, services and content in "spaces". A space is named and accessed on the network using an URI (Uniform Resource Identifier). The URI may be a URL (Uniform Resource Locator) or a simpler version of a URL. In some embodiments, the URL class may be too large. For such embodiments a simpler resource locator may be used that specifies the protocol for moving the messages between client and server, protocol dependent host ID, protocol dependent port ID, and a space name.

An XML representation of an object may be added to a space using a write() method provided by the messaging layer. In one embodiment, the object and the client-specified name may be supplied as parameters. In one embodiment, the write method may translate the object into its XML representation. A take() method may be provided to return the object and remove it from the space. A find() method may be provided to return a specified object from its XML representation in a space. The find() method may also be used to return an array of matching objects in a space given a class. Each of these space methods is implemented using the message-passing layer. A lease mechanism may also be provided, as described in more detail below.

A discovery service may be provided for clients as a general search facility that may be used by a client to locate a particular space. Rather than attempt to define a complicated search protocol which may not be feasible for a thin client to implement, the discovery service may offload the actual search to XML-based search facilities, leaving the discovery service simply to provide interface functionality to the client. The approach is illustrated in Figure 4. In one embodiment, the discovery service receives a string specifying something to locate, and it sends an XML message to a known discovery front-end (perhaps found in a default space), which then parses the string and makes a corresponding XML query to a search facility (which may be an internet search facility). The discovery front-end may parse what it obtains from the search facility and repackage it as an array of strings (each string may be a URI for each found space) which it may send in an XML message to the client. It should be noted that the discovery service does not require that the messaging be atop a connection-oriented transport. Thus, even very thin clients that do not have TCP could use such a discovery service. The discovery front-end makes it possible for the client to discover spaces without a browser or search facility on the client. The client only needs a simple facility that sends a string that specifies keywords to the front-end, which interfaces with a search facility.

A client may be any platform that can send a message using at least a subset of the API and messaging layers. In one embodiment the API layer may provide for both static (or raw) and formatted (or cooked) messages. A server may be any platform capable of receiving and fulfilling message requests. An explicit raw message send may be provided that moves a series of bytes from a client to a server or to another client. The message type may be specified as reliable (e.g. TCP) or unreliable (e.g. UDP). The smallest of devices may use raw unreliable message passing as their sole means of participation in the distributed computing environment. The

device may use these messages to announce its presence and its status. Such small devices may also receive raw messages to implement certain functions, such as turning a feature on or off.

Message-based services such as spaces may send and receive reliable formatted messages. A space message may be formatted with a well-defined header and with XML. In one embodiment, a formatted message  
5 send may occur when a client uses a space method to claim, write, or take objects from a space. The message contents may be dynamically formatted in XML and contain well-defined headers. Figure 5 illustrates client profiles supporting formatted and static messages. By using static messages, small devices may use a smaller profile of code to participate in the distributed computing environment. For example, a small device could just send basic pre-defined messages. Depending on the client, the static pre-defined messages may consume a small  
10 amount of memory (e.g. <200 bytes). Static messages may also be an option even for larger devices. On the other hand, the dynamic XML messages may be useful when object values are not known at compile time.

Turning now to Figure 6, a distributed computing model is illustrated that combines a messaging system with XML messages and XML object representation. The platform independence of XML may be leveraged so that the system may provide for a heterogeneous distributed computing environment. Thus, client 110 may be  
15 implemented on almost any platform instead of a particular platform like Java. The messaging system may be implemented on any network capable messaging layer, such as Internet protocols (e.g. TCP/IP or UDP/IP). Thus, the computing environment may be distributed over the Internet. In one embodiment, the messaging system may also use shared memory as a quick interprocess message passing mechanism when the client and/or space server and/or service are on the same computer system. The distributed computing model of Figure 6 may also be very  
20 scalable because almost any size client can be configured to send and/or receive XML messages.

As shown in Figure 6, two kinds of software programs may run in the distributed computing model: services 112 and clients 110. Services 112 may advertise their capabilities to clients wishing to use the service. The services 112 may advertise their capabilities in spaces 114. As illustrated in Figure 7, clients 110 and services 112 may or may not reside within the same network device. For example, devices 120 and 124 each support one  
25 client, whereas service 112a and client 110b are implemented in the same device 122. Also, as illustrated in Figure 7, no particular platform is required for the devices to support the clients and services. For example, device 120 is Java based, whereas device 124 provides a native code runtime environment.

A device may be a networking transport addressable unit. Example devices include, but by no means are limited to: PDAs, cellular/mobile phones, notebook computers, laptops, desktop computers, more powerful  
30 computer systems, even supercomputers. Both clients and services may be URI-addressable instances of software (or firmware) that run on devices. Using the distributed computing environment architecture, a client may run a service. A space is a service that manages a repository of XML documents. Even though it is redundant, the term, space service, may be used herein for readability. A software component may be both a client and service at different times. For example, when a service uses a space (e.g. to advertise itself), that service is a client of the  
35 space.

Figure 8 illustrates the basic model of the distributed computing environment in one embodiment. The distributed computing environment may connect clients 110 to services 112 throughout a network. The network may be a wide area network such as the Internet. The network may also be a combination of networks such as a local area network (LAN) connected to a wireless network over the Internet. As shown in Figure 8, a service 112

publishes an advertisement 132 for itself (represented in XML) in a space 114. The advertisement 132 specifies the service's XML schema and URI address. Then, a client 110 may look up the advertisement 132. The client 110 may use the advertisement 132 to instantiate a gate 130. The gate 130 allows the client 110 to run the service 112, by sending (and receiving) XML messages to (and from) the service 112.

5           Some results of running a service may be returned to the client in an XML message. However, since other results may be too large for a small client to receive and consume at once, a service 112 may put those results or an XML representation of the results 134 in a space 114, as shown in Figure 9, and return them by reference (in an XML message) to the client 110, rather than by value. Examples of methods of returning a reference to results include, but are not limited to: returning in the message a URI referencing the results in a  
10   space, and: returning in the message an XML document including the URI of the results. Later, the client 110 may access the results, or pass them by reference to another service. The space in which results may be stored may be different from the space in which the service is advertised.

          In one embodiment, the distributed computing environment uses XML for content definition, advertisement and description. New content for the distributed computing environment (messages and  
15   advertisements for example) are defined in XML. Existing content types (e.g. developed for other environments) may also be described using XML as a level of indirection (meta-data). XML provides a powerful means of representing data throughout a distributed system because, similar to the way that Java provides universal code, XML provides universal data. XML is language agnostic and is self-describing. The XML content may be strongly typed and validated using schemas. Using a provided XML schema, the system may ensure that only  
20   valid XML content is passed in a message. XML content may also be translated, into other content types such as HTML and WML. Thus, clients that do not understand XML may still use the distributed computing environment services.

          In one embodiment, the distributed computing environment messages may define the protocol used to connect clients with services, and to address content in spaces and stores. The use of messages to define a  
25   protocol allows many different kinds of devices to participate in the protocol. Each device may be free to implement the protocol in a manner best suited to its abilities and role. For example, not all devices are capable of supporting a Java runtime environment. The distributed computing environment protocol definition does not require nor imply the use of Java on a device. Nor does it preclude it.

          A service's capabilities may be expressed in terms of the messages the service accepts. A service's  
30   message set may be defined using an XML schema. An XML message schema defines each message format using XML typed tags. The tag usage rules may also be defined in the schema. The message schema may be a component of an XML advertisement along with the service's message endpoint used to receive messages. The distributed computing environment may allow clients to use all or some subset of a service's capabilities. Security policies may be employed to enforce the set of capabilities given to a client. For example, once a set of  
35   capabilities has been given to a client, the client may not change that set without proper authorization. This model of capability definition allows for services levels that range from a base set of capabilities to an extended set. Extensions may be added to services by adding to the number of recognized messages.

          In one embodiment, all operations in the distributed computing environment are embodied as XML messages sent between clients and services. Storage (both transient and persistent) providers are examples of

services that enable clients and services to store, advertise, and address content. Clients and services may find each other and broker content using a transient storage space. Services may place a content or service advertisement in a space. The advertisement may describe the content type or the capabilities of the service. Clients may subsequently browse spaces looking for advertisements that match a desired set of capabilities. When  
5 a client finds a matching advertisement, a communication channel may be established which may enable bi-directional message passing to the service backing the advertisement. In one embodiment, the communication channel is authenticated. Results (which are just another content type) from service operations may be returned directly to the client in a response message, advertised and stored in a space, or advertised in a space, but stored persistently. Stored results may be addressed using a URI (e.g. returned in the response message) and may have  
10 an associated authentication credential.

### Message Gates

As discussed above, the distributed computing environment leverages off the use of a data description language, such as XML. XML may be used to describe a target entity (e.g. document, service, or client) to an  
15 extent such that code may be generated to access that entity. The generated code for accessing the target entity may be referred to as a message gate. Thus, in one embodiment, the distributed computing environment differs from other distributed computing environments in that instead of passing the necessary code between objects necessary to access the other object, the environment provides access to XML descriptions of an object or target so that code may be generated based on the XML description to access the target. The distributed computing  
20 environment may use an XML schema to ensure type safety as well as a programming model (e.g. supported messages) without having to agree upon language specific APIs, just XML schemas.

Code generated from an XML schema may also incorporate the language, security, type safety, and execution environment characteristics of the local platform. The local platform may thus have control over the generated code to ensure that it is bug-free and produces only valid data according to the schema. The generated  
25 code may conform to the client's code execution environment (e.g. Java, C++, Smalltalk), as well as its management and security framework (Web-server and/or operating system).

Note that the distributed computing environment does not require that code generated from an XML schema be generated "on the fly" at runtime. Instead, some or all of the code may be pre-generated for categories (or classes) of services, and then linked-in during the platform build process. Pre-generation of code may be  
30 useful for some clients, such as embedded devices, where certain XML schemas are already known. In one embodiment, some or all of the code doesn't actually have to be generated at all. A private code-loading scheme (within the client) might be used in one embodiment to augment the generation process. In addition, the distributed computing environment may specify, in some embodiments, an interface to download code for additional features in accessing a service (see, e.g., message conductors described below). Typically, such  
35 downloaded code may be small and the client may have the option to download the code or not.

The phrase "generated code" may refer to code that originates within the client under the control of the client code execution environment, or to code that is generated elsewhere (such as on the service system or on a space service system) and that may be downloaded to the client system after generation. Binding time, however,

may be at runtime. At runtime, the generated code may be bound to a service address (URI), so that a message may be sent to that service instance.

As discussed above, the interface to any service in the distributed computing environment may be specified by an XML schema, defining the set of messages that a client may send (and receive from) that service.

5 As illustrated in Figure 10, the client 110 and service 112 may each construct a message gate 130 for communicating according to the specified XML schema. From the XML schema advertised for the service 112 (and possibly other information in the service advertisement), a message gate 130a or 130b may be constructed by the client 110a or 110b respectively. A corresponding message gate 130c generated from the same XML schema may also exist on the service 112a. A gate 130 is a message endpoint that may send and/or receive type-safe XML  
10 messages, and that may verify the type correctness of XML messages when sending and/or receiving the messages. The message gate may also provide for authentication and/or other security mechanisms to ensure that the message endpoint is secure. In one embodiment, message gates are always secure.

The distributed computing environment messaging layer described above may be coupled to or may be part of the gate. The messaging layer asynchronously delivers an ordered sequence of bytes, using a networking  
15 transport, from the sender to the receiver, maintaining the notion on both the sender and receiver that this sequence of bytes is one atomic unit, the message. The distributed computing environment does not assume that the networking transport is IP-based. Instead, the messaging layer may sit atop whatever networking transport layer is supported by the device.

Message gates may provide a mechanism to send and receive XML messages between clients and  
20 services. The XML messages may be "typed". For example, the messages may include tags to indicate if a message data field is, e.g., integer, floating point, text data, etc. A message gate may be constructed to verify the type correctness of messages sent or received. A message gate also may authenticate (e.g. securely identify) the sender of a received message. An XML schema may be provided for a service that describes the set of messages accepted by the service and/or sent by the service. A message gate may verify the correctness of messages sent or  
25 received according to the XML schema for which the gate is constructed.

A gate may be constructed as a single atomic unit of code and data that performs type verification and/or message correctness verification and/or sender identification for messages between a client and a service in the distributed computing environment. In one embodiment, once the atomic unit of code and data for a message gate has been created, it cannot be altered as to its typing, message descriptors, and sender identification. In another  
30 embodiment, the gate may be modified as to the contents of the message schema after the gate is created, including deleting, adding, or modifying messages in the message schema.

A message gate is the message endpoint for a client or service in the distributed computing environment. A message gate may provide a secure message endpoint that sends and receives type-safe XML messages. Messages gates may allow clients and services to exchange XML messages in a secure and reliable fashion over  
35 any suitable message transport (e.g. HTTP). For a client, a message gate may represent the authority to use some or all of a service's capabilities. Each capability may be expressed in terms of a message that may be sent to a service. Each such message may be sent through a client message gate which may verify the correctness of the message. The message may be received by a service message gate which may authenticate the message and verify its correctness.



A message gate may provide a secure communication endpoint that type checks XML messages. As further discussed below, a message gate may also provide a mechanism to restrict the message flow between clients and services. In one embodiment when a client desires to access a service, a client and service message gate pair is created, if not already existing. In one embodiment, the service message gate may be created when the service receives a first message from the client message gate. In one embodiment, one or more service message gates may be created when the service is initialized, and may be used to pair with client message gates when created. The creation of a message gate may involve an authentication service that may negotiate the desired level of security and the set of messages that may be passed between client and service. In one embodiment, the authentication service may accept a client ID token (also referred to as a client token), a service ID token (also referred to as a service token), and a data representation language message schema that describes the set of data representation language messages that may be sent to or received from the service. For example, messages may be described that may be sent from a client to a service to invoke the service or to invoke aspects of the service. Messages may also be described that are to be sent from the service, such as response messages and event notification messages. Refer to the Authentication and Security section below for a further discussion of how the authentication service may be used in the construction and use of message gates.

A client message gate and a service message gate pair may allow messages to be sent between the client and the service. In one embodiment, message gates may be created that only send and/or receive a subset of the total set of messages as described in the message schema for a service. This limited access may be used within the distributed computing environment to implement a policy of least privilege whereby clients are only given access to specific individual message types, based on a security policy. Refer to the Authentication and Security section below for a further discussion of security checks for gate usage and gate creation.

Client and service gates may perform the actual sending (and receiving) of the messages from the client to the service, using the protocol specified in the service advertisement (URI of service in the service advertisement). The client may run the service via this message passing. A message gate may provide a level of abstraction between a client and a service. A client may access a service object through a message gate instead of accessing the service object directly. Since the gate abstracts the service from the client, the service's code may not need to be loaded, and then started, until the client first uses the service.

The client gate may also perform verification of the message against the XML schema, or verification of the message against the XML schema may be performed by the service gate, e.g. if the client indicates it has not yet been verified. In some embodiments, verification may not be practical for simple clients and may thus not be required at the client. In some embodiments, verification may be performed by the service. The gates may also perform authentication enablement and/or security schemes. In one embodiment, if a client does not support the protocol specified in the service advertisement, then it may not be able to construct the right gate. To avoid this problem, service advertisements (used for gate construction) may include a list of possible URIs for a service, so a variety of clients may be supported.

A basic message gate may implement an API to send and receive messages. The API moves data (e.g. XML messages) in and out of the gate, validating messages before sending and/ or upon receiving. In one embodiment, message gates may support a fixed minimum API to send and receive messages. This API may be extended to other features as discussed below. As illustrated in Figure 10b, a gate 130 may be generated

according to an XML schema 132. The generated gate code verifies messages based upon the XML schema. The gate may verify correct message types and/or content through the message API. As illustrated in Figure 10b, through the message API a verified message may be sent to a service. The message may be received by a corresponding gate at the service. In response to the message, the service may generate results 180. The service may return result data 182 through its gate. The results data may be the results themselves or a reference to the results, such as a URI to results stored in a space.. In various embodiments, the message API may support synchronous messages (request-response), asynchronous messages (response is disconnected from request), unicast messages (point to point), multi-cast messages (broadcast), and publish and subscribe (event messages), for example. Other type of messages may also be supported, such as remote method invocation messages.

Each message sent by a gate may include an authentication credential so that the receiving gate may authenticate the message. Each message may also include a token which includes information allowing the receiving gate to verify that the message has not been compromised or altered. For example, the sender may compute a hash or checksum of the message which may be verified by the receiver. The sender may also encrypt this token and/or the entire message using the sender's private key and may include in the encrypted message the corresponding public key so that the receiver may verify that the token was not changed. See the section below on Authentication and Security.

A pair of message gates may provide a mechanism for communicating requests from clients to services and response from services to clients. Two associated message gate endpoints may be used to create a secure atomic bi-directional message channel for request-response message passing. Thus, the distributed computing environment may employ a message transport in which a message gate exists on both the client and the service sides. The two gates may work together to provide a secure and reliable message channel.

Turning now to Figure 11a, an illustration is provided for one embodiment showing construction of a gate 130a in a client 110 from a service advertisement or other service description 132. The client may have a gate factory 140 that is trusted code on the client for generating gates based on XML service descriptions. The use of the gate factory 140 may ensure that the gate it generates is also trusted code, and that the code is correct with respect to the service advertisement. As shown in Figure 11b, a gate 130c may also be constructed at a service 112. The client gate 130a and the service gate 130c provide message endpoints for communications between the client and service. In one embodiment, the pieces the gate factory needs to construct a gate 130 are the XML schema of the service (from the service advertisement) and the URI of the service (from the service advertisement). In another embodiment, an authentication credential may also be obtained and used in gate construction by running an authentication service specified in the service advertisement.

A gate factory may provide a trusted mechanism to create message gates. In some embodiments, in order to ensure that a message gate is a trusted message endpoint, the code used to create the gate must be trusted code. A gate factory 140 may be a trusted package of code that is used to create gates. In one embodiment, each client and service device platform that desires to send and receive messages in the distributed computing environment may have a gate factory. In some embodiments, gates may be pre-constructed by a separate gate factory so that a device with pre-constructed gates may not need a full gate factory, or may include a partial gate factory for binding a service URI and/or an authentication credential to the pre-constructed gate at runtime (e.g. when messaging is desired).

A gate factory for a device may generate gate code that may incorporate the language, security, type safety, and/or execution environment characteristics of the local device platform. By constructing gates itself, a device has the ability to ensure that the generated gate code is bug-free, produces only valid data, and provides type-safety. An advantage of a device generating its own gate code as opposed to downloading code for accessing a service is that the client code management environment has the control. The generated code may conform to the client's code execution environment (e.g. Java, C++, Smalltalk), as well as its management and security framework (Web-server and/or operating system). Generated code is also trusted code, because the client's runtime environment was involved in its creation. Trusted security information therefore may also be added by the trusted generated code. Thus, a device may receive an XML message schema for a service and then construct a gate based on that schema to access the device. The XML schema may be viewed as defining the contract with the service and the generated gate code as providing a secure way to execute the contract. Note that open devices, in which un-trusted (e.g. downloaded) code may be run, may be configured so that gates may be generated only by trusted code. Open devices may employ a process model in which gates are enclosed in a protected, isolated code container that is not accessible to tools, such as debuggers, capable of discovering the gate's implementation, especially the gates authentication credential.

A gate factory may negotiate on behalf of a client with a service to create a gate to send messages to the service. Similarly, a gate may be constructed at the service to receive messages from the client gate and send messages to the client gate. Together, the client and service gates may form a secure bi-directional communication channel.

A gate factory may provide a level of abstraction in gate creation. For example, when a client desires to use a service, instead of the client directly creating a gate to access the service, the gate may be created by a gate factory as part of instantiating the service.

The gate factory may create or may include its own trusted message gate that is used to communicate with an authentication service (e.g. specified by a service advertisement) to receive an authentication credential for the gate being constructed. For services that do not restrict access, a gate may be constructed without an authentication credential. The gates for such services may not need to send an authentication credential with each message since the service does not restrict access. The authentication service is an example of a service that does not restrict access, in one embodiment. Thus, a gate factory may be configured to optimize gate construction by checking whether a service restricts access. If the service does not restrict access, then the gate factory may avoid running an authentication service as part of gate construction and may avoid included provisions for an authentication credential as part of the constructed gate. The gate factory may also receive or download an XML message schema (e.g. specified by a service advertisement) to create a gate matching that schema. The gate factory may also receive or download a URI for the service and/or for a service message gate for use in creating the client message gate to communicate with the URI.

In addition, another gate construction optimization may be employed for certain clients that do not desire to perform checking of messages against a service's XML schema. The client may be too thin to perform the checking or may rely on the service gate to perform the checking or may simply choose not to perform the checking (e.g. to reduce gate memory footprint). The gate factory may be configured to receive an indication of whether or not a gate should be constructed to verify messages against the provided XML schema. In some

embodiments, certain clients may have a gate factory that does not provide for message verification against a schema for its constructed gates. In some embodiments, gates may be pre-constructed not to verify messages. In some embodiments, a gate may be constructed to verify outgoing messages only, or verify received messages only. Thus, in some embodiments, a client may avoid or may chose to avoid building some or all of the gate code that checks the messages against the XML schema.

In some embodiments, devices may maintain a cache of gates to avoid constructing them each time the same service is run. For example, when a new gate is constructed by a gate factory, the gate may be maintained in a gate cache. When the gate is no longer being used, it is kept in the gate cache instead of being deleted. If the gate cache becomes full, one or more gates may be removed from the gate cache according to a cache replacement algorithm, such as least recently used. When the gate factory is called to construct a gate, it first checks the gate cache to see if a matching gate already exists so that construction of a new gate may be avoided.

The building of a gate may be made lightweight by appropriate reuse of pieces used to construct other gates. Certain portions of each gate may be the same, and thus may be reused from gate to gate, such as parts of the message verification code. Also, for some devices, common gate code may be built into the system software for the device and shared by all gates on that device. Thus, the gate factory may avoid rebuilding this common code for each gate. Instead, the gate factory may simply bind the gate to this system software portion. For example, a system software portion may be provided to handle the message layer over whatever transports are provided on the device.

Space services in particular may be good candidates for many of the gate construction optimizations described above since a service gate constructed for a space service may perform many of the same functions as other service gates for that space service. Refer to the Spaces section below for more information on space services.

In some instances, a more efficient form of method invocation may exist. For example, if the target service runs in the same Java Virtual Machine as the client application, a more efficient form of method invocation may be to create a Java dynamic proxy class for the service. In such a case, a `java.lang.reflect.Method` invocation may be faster than sending a message. A gate binding time procedure may check for such an optimization and use it instead of running the gate factory to create a gate or bind an existing gate.

In one embodiment, such as for special-purpose clients or small embedded devices, the generation of gate code at runtime may not be desirable due to memory consumption and code generation time. Thus, instead of having a gate factory that generates gates at runtime, in some embodiments gates may be pre-generated and built into the device. For example, message gates may be generated during the build of embedded software as a means of including a built-in secure message endpoint that does not have to be constructed at runtime. Thus, a client with built-in gates may not need a full gate factory, or may require only a partial gate factory for performing certain runtime binding to a built-in gate, such as for the URI and/or authentication credential.

A generation tool may be provided for the pre-construction of gates. The generation tool may include an XML parser, a code generator and a code compiler. In one embodiment, the code generator may be a Java source code generator and the code compiler may be a Java code compiler. During the build of the software for which built-in message gates is desired, the generation tool is run with input from all the relevant XML schemas for which gates are desired.

As an example, if it is desired for a device to have a built-in message gate that can send and receive messages from a digital camera, the build of the device software may include running the gate generation tool with the camera's XML message schema as input. The XML schema may be parsed by the XML parser that may convert the XML schema into an internal form suitable for quick access during a message verification process.

5 The tool's code generator may provide source code for a gate corresponding to the camera's schema. In some embodiments, the generation tool may also compile the source code and the gate code may be linked into the software package for the device. At runtime, the camera service may be discovered in the distributed computing environment. The message URI for the camera service may be bound to the built-in gate for the camera within the device. The binding of the URI to the pre-constructed gate may be performed by a gate constructor within the  
10 device. This gate constructor may be a much smaller, simpler gate factory. When the camera service is instantiated, the URI for the camera service is passed to the gate constructor as an XML message. The gate constructor may then bind the URI to the pre-constructed gate.

Thus, a gate may be partially or fully generated at runtime, or a gate may be pre-generated before runtime with a binding process (e.g. for a URI or credential) performed at runtime. In one embodiment, a gate generation  
15 tool such as the gate factory or the generation tool for pre-constructed gates may be a Java-based tool to provide some level of platform independence. Alternatively, gate generation tools may be provided in any language, such as the native code for a particular device in the distributed computing environment.

Note that the distributed computing environment does not preclude a device from downloading part or all of a gate's code. For example, in some embodiments, a service may provide gate code that may be downloaded by  
20 a client wishing to access that service. However, downloaded code may present size, security and/or safety risks.

A more detailed illustration of possible gate components for one embodiment is shown in Figure 12. A gate may include its address (or name) 150, a destination gate address 152, a valid XML schema (or internal form thereof) 154, and a transport URI 153. In other embodiments, a gate may also include an authentication credential  
156. Some gates may also include a lease 158 and/or a message conductor 160 to verify message ordering.

25 A gate's name 150 may be a unique ID that will (for the life of the gate) refer only to it. A gate may be addressed using its gate name 150. In one embodiment, gate names may be generated as a combination of a string from an XML schema (e.g. from a service advertisement) and a random number, such as a 128-bit random number. The name 150 may allow clients and services to migrate about the network and still work together. In a preferred embodiment, the gate address is independent of the physical message transport address and/or socket  
30 layer. Thus, a gate name may provide a virtual message endpoint address that may be bound and un-bound to a message transport address. In one embodiment, a gate's name may be a Universal Unique Identifier (UUID) that may, for the life of the gate, refer only to it.

A gate name may persist as long as the gate persists so that different applications and clients executing within the same device may locate and use a particular gate repeatedly. For example, a gate may be created for a  
35 first client process executing within a device to access a service. After the first client process has completed its activity with the service, it may release the gate. Releasing the gate may involve un-binding the gate from the first client process's message transport address (e.g. IP and/or Port address). The gate may be stored in a gate cache or repository. A second client process executing within the same device that desires to run the same service may locate the gate by its name and use it to access the service. To use the gate, the second client process may bind the

gate to its message transport address, so that the message endpoint for the second client process is a combination of the gate name and the second client process's transport address. In another example, a client may receive a dynamic IP address (e.g. a mobile client). When the client's transport address changes, a gate name (or gate names) may be re-bound to the client's new transport address so that the client may still access a service(s) that it previously accessed without having to relocate the service and recreate the gate. A gate name may also be useful for process migration. A process and any associated gates may be checkpointed or saved at one node in the distributed computing environment and moved to another node. The process may be restarted at the new node and the associated gates may be bound to the transport address for the new node so that the process will still have access to the external services to which it had access before being migrated. A gate may track the current location of another gate to which it is paired. Thus a service or client may be migrated and still be accessible. For example, replicated or load-balanced service implementations may be abstracted from clients of the service by the gate.

Thus, a gate name 150 provides a flexible mechanism by which to address a message endpoint in the distributed computing environment. A gate name may be used to locate and/or address a gate over a wide range of networks, from a local network to the Internet. Gate names may be independent of message transport so that a message endpoint (gate) may be moved from transport to transport by unbinding and rebinding to different underlying transport addresses (e.g. IP/Port address pairs).

In one embodiment, a gate may also be separated from a service so that the same gate may be used to send requests to different services over time. This may involve un-binding the gate's destination gate address 152 and binding a new destination gate address to the gate.

A gate may be implemented as a layer above a device's transport layer (e.g. networking sockets). Each gate may include a transport reference 153. The gate name 150 may be bound to the transport reference 153 as described above. Multiple gates may share the same message transport. For example, multiple gates may have transport references 153 to the same TCP/IP socket. By sharing the same message transport, the size and complexity of each gate may be reduced. A device in the distributed computing environment may have a large number of gates that need to send and receive messages. The message handling complexity for multiple gates may be reduced by sharing a common message transport. The transport reference 153 may be a transport URI (e.g. URL) or socket reference and may provide a mechanism for naming an underlying transport and sharing the transport with other gates. Multiple local gates may include a reference 153 to the same transport, however, each local gate may behave independently of the other local gates sending and receiving messages to and from its paired remote gate.

The schema 154 may be downloaded from a space into the gate by the gate factory. The schema may be compiled into an internal form suitable for quick access during a message verification process. In one embodiment, the schema may specify two groups of messages: client service messages and provider service messages. The client service messages group includes the description of all messages that the client may send (that the provider supports), and the provider service messages group includes the description of all messages that the provider may send (that the client receives). In one embodiment, either the client or provider may send a particular request to the space service to obtain a response message with either: the entire client service messages, the entire provider service messages, the entire client and provider service messages, or a specific message of

either the client service messages or the provider service messages. In addition, once a gate has been constructed, a client may query as to the capabilities of the service without the gate actually sending a message, but instead by inspecting the gate's set of messages.

As described above, a message gate may verify the sender of the message using an authentication credential, message content for type safety and according to an XML schema. However, it may also be desirable to verify that messages are sent between a client and a service in the correct order. It may be desirable to be able to provision applications (services) for clients to run without any pre-existing specific functionality related to the application on the client (e.g. no GUI for the application on the client). For example, a Web browser may be used on a client as the GUI for a service instead of requiring an application-specific GUI. Of the possible messages in the XML schema, the client may need to know what message next to send to the service. It may be desirable for the client to be able to determine which message to send next without requiring the client to have specific knowledge of the service. In one embodiment, the service may continually send response messages indicating the next input it needs. The service would then accept only the corresponding messages from the client with the requested input specified. Other ad hoc scheme for message ordering may also be employed.

In another embodiment, a message conductor 160 may be employed in the gate or associated with the gate to verify the correct sequence of messages, as opposed to verifying each message's syntax (which may already be performed in the gate according to the schema). Message conductor 160 may provide a more general approach for application provisioning. The message conductor 160 may be specified in a service's advertisement. The message conductor indication in a schema may allow code to be generated on or downloaded to the client during gate construction, which may provide the choreography needed to decide which message to send next to the service. A message conductor may be implemented as a Java application, a Java Script, WML script, or in other programming or scripting languages.

In one embodiment, the message conductor may accept as input an XML document (e.g. from a service advertisement) that presents the valid order or choreography for messages that may be sent between a client and the service. This XML document may also specify user interface information and other rules. The conductor may parse this XML document into an internal form and enforce message ordering (and/or other rules) according to the enclosed ordering information. The conductor may prevent messages from being sent out of order. Or, if a message is sent out of order, an exception may be raised within the sending device. If a message is received out of order, the conductor may send an automatic response message back declaring the ordering error. The sender may then resend messages in the correct order. Note that in some embodiments, part or all of a conductor may be shared by several gates. Thus, a conductor may be linked to multiple gates.

In one embodiment of a distributed computing environment, front ends for services (service interfaces) may be built in to clients. In one embodiment, the service interface may be a preconstructed user interface provided to the client by the service. In one embodiment, the service interface may be provided to the client in the service advertisement. The service interface may interact on the client with the user of the service to obtain input for running the service, and then may display results of running the service on the client. A "user" may be a human, embedded system, another client or service, etc. In one embodiment, a client device may not be able to provision arbitrary services, as the client device may only be able to run services for which it has a front end built in. In one embodiment, a service interface for a service may be implemented in a Web browser on the client.

In one embodiment, a message conductor and/or service interface may be external to the gate and thus abstracted from the gate and client. The abstracted message conductor may provide provisioning of arbitrary services to any client device. In one embodiment, the message conductor may be written in code that may run on substantially any platform. In one embodiment, the message conductor may be written in the Java language. In one embodiment, the message conductor may not require the arbitrary downloading of objects, for example, Java objects, returned to the client device. For example, very large objects may be returned, and the message conductor may choose to not download these very large objects. In one embodiment, the message conductor may send XML messages to services from the client device on behalf of the client. The message conductor may interact with the user of the service to receive input and display results.

In one embodiment, a service interface may be provided that interacts with the client (e.g. thru a user interface) to obtain all information to run the service, and then may display either results of running the service or information regarding the location of results, as appropriate. The service interface may be either part of a message conductor 160 or may be in addition to and work with message conductor 160. The service interface may either be:

1. Built in to the client device and thus run on the client.
2. Downloaded to the client device from the space server.
3. Run on the space server.
4. Run on the service provider.

In one embodiment, to a client, the distributed computing environment space server must support #1 always, indicate if #2 is supported (by advertisement in space), indicate if at least one of #3 and #4 is supported. Note that whether or not it supports #4 depends upon whether or not the service provider supports #4. In one embodiment, to a service provider, the distributed computing environment space server must support #4 always and indicate if it supports #3.

Regardless of where the service interface runs, once a service is activated, the service interface may interact with the client, displaying (remotely) requests for input on the client's display, and then displaying (remotely) results of running the service. Such interaction with the client is implemented in terms of XML messages.

The service interface and/or message conductor may meet the needs of a client user that may have discovered a service, but does not want to read a typically large, dry computer manual to figure out how to use the service. As the service interface and/or message conductor interacts with the user to request all input that the service needs, they may even provide short descriptions of the input requested if the user requests it. Once the service interface has obtained the necessary information from the client, it may send XML messages to the service provider that runs the service. The ordering of the messages may be verified by the message conductor 160 in the gate.

In a preferred embodiment, all messages flow through a gate. A gate may be configured to provide a flow control mechanism. For example, a service may need to handle a large amount of incoming and outgoing messages. Flow control may allow a service to keep up with high traffic volume. Gates may be configured to monitor messages for flow control tags. When a gate receives a message, it may examine that message for a flow control tag. The flow control tags may be XML tags. A message may include either an OFF tag or an ON tag, for



example. If a received message includes an OFF tag, the receiving gate will stop sending messages to its paired destination gate. If the gate receives a message including an ON tag, it may resume sending messages.

Thus, a service-side gate may monitor the use of its resources and trigger flow control if use of its resources exceeds a threshold. For example, a service may reduce its load by sending messages including OFF tags to one or more client gates. The client gates receiving the messages with OFF tags will stop sending messages to the service. Pending messages in the clients may be buffered or may be handled by internal flow control mechanisms. Once the service is able to handle more requests, it may send messages to one or more clients with ON tags so that the clients may resume sending messages. In other embodiments, other flow control tags may be supported in addition to or instead of ON and OFF. Other flow control tags may indicate to reduce message flow or that message flow may be increased.

Message gates may be configured to perform resource monitoring. For example, since all messages may flow through a gate, the gate may be configured to manage and/or track a client's use of a service (and possibly its associated resources such as memory or threads). A gate may be configured to track the activity of a software program, such as a client, by monitoring how much a resource, such as a service, is used or which and how many service resources are used. In one embodiment, a gate may generate or may facilitate generation of a client activity log. Each message and its destination or sender may be logged.

A gate may also be configured to perform resource monitoring for flow control from the local (sending) side of a gate pair. If the client exceeds an allocated bandwidth of service (or resource) usage, the gate may automatically throttle back the flow of messages, for example. Thus, a client-side message gate may automatically trigger different flow control modes by monitoring the flow of outgoing messages. If the outgoing message flow exceeds a threshold, the gate may reduce or shut off its flow of outgoing messages. The threshold may be specified in a service's XML schema or advertisement. In some embodiments, the threshold may be specified only for messages using certain service resources or for all messages.

The gate may also be configured to determine when message flow may be increased or resumed. In one embodiment, the gate may maintain a count of outgoing messages that have been sent without the matching reply (response) received. When matching responses are received by the client-side gate, the count of outstanding request messages may be decremented. When the counts decrements below a specified outstanding request message threshold, the gate may increase or resume sending new request messages.

A gate may be configured to support message-based accounting and/or billing. A billing system may be implemented based upon the number and/or kind of messages sent and/or received by a message gate. Since all messages to and from a client may pass through a gate, the gate may be configured to facilitate charging a client for service usage, for example on a per message basis or "pay as you go". Thus, a billing system may be implemented within the distributed computing environment in which a user could be charged, for example, each time a message is sent and/or received by software running on behalf of the user.

In one embodiment, a message gate may receive billing information from an XML schema, e.g. for a service. The billing information may denote a billing policy and a charge-back URI. The charge-back URI may be used by the message gate to charge time or usage on behalf of a user. A message gate may make a charge-back by sending a charge message to the charge-back URI specified in the XML schema. Gates so configured may be referred to as bill gates. The billing policy may indicate charge amounts per message or per cumulative message

totals, etc. The billing policy may indicate how much and/or how often (e.g. after every x number of messages sent and/or received) to charge the user. The policy may indicate that only certain types of messages trigger charges, such a messages requesting a specified service resource. The billing policy may also indicate different billing models for different clients or classes of clients. For example, a billing policy may be configured (e.g. in a service's XML schema) so that some clients may pay a one-time charge when they create a gate to access the service. The policy may indicate clients that are to pay as they go (e.g. per message), or may indicate clients that are not to be charged at all.

In some embodiments, a client may be too thin to support a full gate, or a client may not include software to directly participate in the distributed computing environment. In such embodiments, a server (such as the space server in which the service is advertised or another server) may be a full or partial proxy gate for the client. The server may instantiate a service agent (which may include a gate) for each service to be used by the client. The service agent may verify permission to send messages; send messages to the provider, possibly queuing them until the provider can accept the next one; send messages to the client, possibly queuing them until the client can accept the next one; and manage the storing of results in a result or activation space. See also the Bridging section herein.

For example, as illustrated in Figure 13, a client may be a conventional browser 400 that does not support gates to participate directly in the messaging scheme described above. The browser 400 may be aided by a proxy servlet (agent) 402. The browser user may use a search engine to find a Web page that fronts (displays the contents of) a space advertising services within the distributed computing environment. The user is able to point and click on the space Web page and, with the help of the servlet, to access services. The Web pages may include scripts, for example, Java or WML scripts, which may be used in connecting the browser to the proxy servlet. Scripts may also be used to send messages to the proxy servlet. The servlet agent may translate Web page actions into messages on behalf of the browser client. These actions may include navigating a space, starting services, and returning results. Result page URIs (referencing pages containing XML) may be returned directly (or translated into HTML or WAP if needed) to the browser, for display to the user. Thus, the browser-based client does not need to know how to start services, nor which messages to send during the service usage session. For example, a user of a WAP browser (e.g. on a cell phone) may connect to a space page, browse its contents (services), and then start a service, all by pointing and clicking. The agent 402 provides the client interface between the conventional client and the distributed computing environment.

The distributed computing environment may include several different types of message gates for communicating between clients and services that support different features. For example, as discussed above, some gates may support flow control or billing. Another type of message gate may support a form of remote method invocation. This type of gate may be referred to as a method gate.

A gate is a secure message endpoint that sends and receives type-safe messages, e.g. XML messages. The remote method invocation (RMI) style gate may be referred to as a method gate. The direct data-centric gate may be referred to as a message gate. A *method* gate may be implemented as a "layer" on top of a *message* gate. The exact implementation may be defined in the platform binding.

Figure 14 illustrates the use of a method gate to provide a remote method invocation interface to a service. Method gates provide a method interface between clients and services. A method gate may be bi-directional, allowing remote method invocations from client to service and from service to client. A method gate

172 may be generated from XML schema information 170 (e.g. from a service advertisement in a space). The XML schema information 170 includes XML defining a method interface(s). From this information, code may be generated as part of the gate for interfacing to one or more methods. Each method invocation (e.g. from a client application 176) in the generated code may cause a message to be sent to the service containing the marshaled method parameters. The message syntax and parameters to be included may be specified in the XML schema. Thus, the method gate 172 provides an XML message interface to remotely invoke a service method. The method gate may be generated on the client or proxied on a server, such as the space server where the service method was advertised or a special gateway server.

A service may have a corresponding method gate that implements or is linked to a set of object methods that correspond to the set of method messages defined in the service's XML schema. There may be a one to one correspondence between the object methods implemented by or linked to the service's method gate and the method messages defined by the service's XML schema. Once a service's corresponding method receives a message from a client to invoke one of the service's methods, the service's method gate may unmarshal or unpack the parameters of the message invocation and then invoke the method indicated by the received message and pass the unmarshalled parameters.

The method gate may provide a synchronous request-response message interface in which clients remotely call methods causing services to return results. The underlying message passing mechanics may be completely hidden from the client. This form of remote method invocation may deal with method results as follows. Instead of downloading result objects (and associated classes) into the client, only a result reference or references are returned in XML messages, in one embodiment. An object reference 178 may be a generated code proxy (e.g. results gate) representing the real object result 180 (still stored out on the net, for example). In other embodiments, the client may choose to receive the actual result object. In addition, once a client has received a result object reference, the client may use this reference to receive or manipulate the actual result object. In one embodiment, the result reference includes one or more URIs to the real result.

The real result object(s) may be stored in a service results space (which may be created dynamically by a servlet, for example). This temporary results space may act as a query results cache. The results cache (space) may be patrolled by server software (garbage collector) that cleans up old result areas. Results returned from each method invocation may be advertised in the results space. A result itself may be or may include a method that could then be remotely instantiated by a client, thus generating its own method gate. Therefore, the distributed computing environment may support recursive remote method invocation.

As mentioned above, when a client uses a method gate to remotely invoke a service method, a reference to the method results may be returned from the service method gate instead of the actual results. From this reference, a results gate may be generated to access the actual result. Thus, the client or client method gate may receive a result URI and perhaps a result XML schema and/or authentication credential for constructing a gate to access the remote method results.

In one embodiment, a service gate may create a "child gate" for the results. This child results gate may share the same authentication credential as its parent gate. In some embodiments, results may have a different set of access rights and thus may not share the same authentication credential as its parent. For example, a payroll service may allow a different set of users to initiate than to read the payroll service's results (paychecks).

A service method gate may return a child results gate to the client gate as the result of the method. The client may then use the results gate to access the actual results. In one embodiment, the software program (client) receiving the results gate cannot distinguish between the results gate and the result itself in which case the results gate may be an object proxy for the actual result object. The results gate may also be a method gate that supports remote method invocation to result objects. In this manner, a chain of parent and child method/results gates may be created.

In one embodiment, the method gates and remote methods may be in Java. In this embodiment, method results are correctly typed according to the Java typing system. When a Java method is remotely invoked as described above, the results gate may be cast into the Java type that matches the result type. In this embodiment, method gates may be used in the distributed computing environment to allow remote Java objects to behave as local Java objects. The method invocation and results may appear the same to the client Java software program whether the real object is local or remote.

See the Spaces section below for a further discussion on the use of spaces for results.

Method gates provide a method interface to clients, instead of just a raw message interface. In one embodiment, a method gate may be implemented on top of a message gate. The message gate provides the method gate with transport access, message content validation, and message content access (get content and set content methods). In one embodiment, each method invocation in the generated code (i.e. method gate) causes a single synchronous message to be sent to the service containing the marshaled method parameters. The method gate may then causes the current thread to block, waiting for a response message from the service.

This style of programming may be referred to as synchronous request-response programming. Clients call methods causing services to return results. The underlying message passing mechanics are completely hidden from the client. This form of RMI deals with method results in a unique and interesting way. In one embodiment, instead of downloading objects (and associated classes) into the client, only result object references (Advertisements or Advertisement URIs) are returned. In this embodiment, given an object reference, a results gate may be generated that gives access to the real object (still stored out on the net).

In one embodiment, some results produced by a service are advertised in a space and ultimately accessed using a results gate. The results gate may or may not contain the same security credential as the input gate used to generate the results. Because input to a service is asynchronous from its output (the results), the results may have a different set of access rights associated with it. Using a B2B scenario, a payroll service may allow a different set of users to initiate payroll than to read the payroll service's results (paychecks).

In one embodiment, results gate generation for message gate results may be manually initiated. In-line results (e.g. XML documents sent as a response from a service) can be accessed using the message content access (e.g. get and set) methods available on message gates. Method results gate generation may be automatically initiated. The method gate model of programming hides results gate generation, creating a seamless, remote method invocation programming model without the overhead of class loading or requiring the application programmer to manually generate results gates.

Figures 45a-45e are flow diagrams illustrating various embodiments of mechanisms for communicating between clients and services in a distributed computing environment using method gates. In Figure 45a, at 2100, a message including a representation of a computer programming language (e.g. Java) method call may be generated

on the client device. In one embodiment, the message may be in a data representation language. In one embodiment, the data representation language is XML. In one embodiment, a client process may make a method call, and the method call may be marshaled into a representation of the method call included the message. The representation of the method call in the message may include, but is not limited to, an identifier (e.g. method name) that identifies the method call, and zero or more parameter values for the method call. The representation of the method may be in the data representation language. For example, the elements in the representation may be one or more tags (e.g. XML tags) in the message.

In one embodiment, a method gate may access the method call generated by the client process, and then may marshal the method call into the message. In one embodiment, a message including a representation of a method call may be generated on the client when no actual method call was made. In this embodiment, a process on the client may invoke computer programming language methods on a service without actually generating computer programming language method calls. For example, a client may include one or more "canned" messages that the client may send to the service to invoke one or more methods of the service. Thus, the client may use messages to request the service to perform methods without a process on the client actually making a method call.

At 2102, the client may send the message to the service. In one embodiment, the client method gate may send the message to the service. In one embodiment, the client method gate may send the message directly to the service. In another embodiment, the client method gate may provide the message to a client message gate, which may then send the message to the service.

At 2104, after the service receives the message, a function may be performed on the service in accordance with the representation of the method call in the received message. In one embodiment, the service may unmarshal or unpack the method call from the received message, invoke the method indicated by the received message and pass the unmarshaled parameter values to the invoked method. In one embodiment, the unmarshaling and invoking may be performed by a method gate on the service. In one embodiment, instead of invoking the method, the service may perform a function (e.g. other method or some other action) in response to the message. For example, the service may execute a function that generates the desired results of the method call without invoking a method on the service. In another example, the service may have previously generated results data for the method call, and may provide the results data to the client in response to the message without invoking the method.

At 2106, the function on the service may generate results data in response to the message. At 2108, the results data may be provided to the client. In one embodiment, the results data may be returned directly to the client (e.g. in a message). In another embodiment, the results data may be stored in the distributed computing environment (e.g. on the service device, or on a space service external to the service device) and an advertisement may be provided to the client for accessing the stored results data. The client may then use the advertisement to set up a results gate for accessing the results data. In another embodiment, the service may return a results gate to the client for accessing the results data.

In one embodiment, the client may transform a method call into one or more messages that may be sent to the service, wherein the messages do not include information that may be unmarshaled into a method call, but instead include information that may be used by the service to perform a function on behalf of the client. In this embodiment, the service may not know that the messages were originally generated from a method call. In one

embodiment, a client method gate may transform a method call generated on the client into one or more messages requesting the service to perform one or more functions for the client, but not including a marshaled method call that the service may unmarshal into a method call. These messages may still be considered a "representation" of the method call, but may not be in a form that the service recognizes as a marshaled method call that may be unmarshaled to regenerate the method call.

In one embodiment, the service may transform one or more messages requesting the service to perform one or more functions into a method call. In this embodiment, no method call may have been made on the client to generate the messages (the client may not have generated the one or more message in response to a method call). Thus, the client may not know that the service is invoking a method to perform the requested function(s). In one embodiment, a service method gate may receive the message(s) from the client and construct a method call from the information in the message(s).

In Figure 45b, a client process executing within a client device may make a method call (i.e. invoke the method) at 2110. In one embodiment, the method call may be a call to a Java method. In one embodiment, the called method may not be implemented locally on the client device, but is implemented on a service device external to the client device. At 2112, a client method gate on the client device may receive the method call. The client method gate may then marshal the method call into a data representation language message. In one embodiment, the data representation language is XML. The message may include an identifier of the method and one or more parameter values of the method. The identifier may be a name, number, or other value used to identify the method to the receiver of the message. A method call may include one or more parameters, and when called, the caller supplies values for these parameters. In one embodiment, more than one method call may share the same identifier, and may be distinguished by the parameters of the method.

At 2114, the client method gate may send the message to the service device. In one embodiment, the client method gate may send the message directly to the service method gate. In another embodiment, illustrated in Figure 45c, the client method gate may provide the message to a client message gate at 2124. The client message gate may then send the message to a service message gate at 2126. The service message gate may then provide the message to the service method gate at 2128. The embodiment illustrated in Figure 45c frees the method gates from the responsibility of handling the sending and receiving of messages, and simplifies the programming model of the distributed computing environment by compartmentalizing the RMI functionality and the message handling functionality.

In one embodiment, the client may attach a credential to the message for verifying the message (and client) on the service. In one embodiment, the credential may have been obtained by the client from an authentication service in the distributed computing environment. In one embodiment, the service may have provided information to the client identifying the authentication service to use (e.g. in a service advertisement). In one embodiment, the service may use the same authentication service to authenticate the client (e.g. when a first message is received from the client). The service may then check each message from the client to verify that the message includes the proper credential for the client. In one embodiment, the service method gate may perform the verification. In another embodiment, a service message gate may perform the verification, and may then pass the verified message to the service method gate. See the Authentication and Security section for more information on credentials and verification.

Returning to Figure 45b, at 2116, the service method gate may unmarshal or unpack the method call from the received message, invoke the method indicated by the received message and pass the unmarshaled parameter values to the invoked method. The service method gate may use the identifier included in the message to locate the template for the method call. The service method gate may implement or may be linked to a set of methods that correspond to the set of method messages defined in the service's XML schema. There may be a one to one correspondence between the object methods implemented by or linked to the service's method gate and the method messages defined by the service's XML schema. In one embodiment, a method gate may be created on a client in accordance with a message schema provided to the client by the service, e.g. in a service advertisement. In one embodiment, a gate factory may be used to generate the method gate on the client.

At 2118, the invoked method may be implemented or performed on the service. At 2120, the invoked method may produce results output from the invocation in accordance with the parameter values received in the method invocation. At 2122, the results of the method invocation may be provided to the client process that originally invoked the method. In one embodiment, the service may directly provide the results to the client in one or more results messages. In another embodiment, the service may place the results in a space and may provide a results advertisement to the client for accessing the results. Figure 45d and 45e illustrate other embodiments where a results gate may be provided to the client for accessing the results.

In Figure 45d, at 2130, the service method gate may provide a results reference to the service message gate. In one embodiment, the results reference may be an advertisement to the results. In another embodiment, the results reference may be an address, e.g. a URI, for the results. At 2132, the service message gate may send the results reference to the client message gate in a message. At 2134, the client, after receiving the message, may create a results gate from the results reference message. For example, a results advertisement may be provided in the message, and the client may create the results gate in accordance with the results advertisement in a similar manner to creating message gates from advertisements as described elsewhere herein. At 2136, the client may use the results gate to access the results. For example, the results may be on the service device, and the service may have generated a service results gate. The client results gate may be generated to communicate with the service results gate, e.g. the URI of the service results gate may have been included in the results advertisement. Alternatively, the service may have stored the results elsewhere in the distributed computing environment and the client results gate may be configured to communicate with a results gate set up for the results. For example, the results may be on a space, and the client results gate may communicate with a results gate on the space.

In Figure 45e, the service may create a results gate at 2140. The service may then send the results gate to the client (in a message) at 2142. The received results gate may then be used by the client to access the results. This embodiment frees the client from the responsibility of setting up the results gate.

To the client process that originally invoked the method, the process of RMI as described herein is transparent. To the client process, it appears as if the method is being invoked locally, and that the results are being provided locally. Thus, the method gates, in combination with the message passing mechanism, may allow "thin" clients to execute processes that would otherwise be too large and/or complex to execute on the clients.

A Java platform method gate implementation example follows. The actual Java method gate implementation for any Java platform is defined in the distributed computing environment platform binding. Each Java method gate granting access to a result is actually a Java class instance (an object) that implements the

result's interface. For example, if the result were an object of type Table, the result method gate class may be defined as follows:

```

    public class TableMethodGate implements Table {
5      public Cell getNextCell();
    }

```

The TableMethodGate object is cast to type Table before being returned as the method invocation result. The process is recursive. That is, when the getNextCell method is invoked, a CellMethodGate class and object instance are generated to represent the getNextCell result:

```

10    public class CellMethodGate implements Cell { }

```

The choice of which gate type (message or method) to use with a particular service is addressed in combination by the platform binding and each service advertisement. Some platforms may not support method gates. If a platform does support method gates, the binding may define its precise implementation. Secondly, a service advertisement's interface may or may not lend itself to RMI-style programming. Those service interfaces that do support a RMI-style programming model are flagged with the following XML attribute:

```
<MethodGateInterface=true>
```

Message gates may also support publish and subscribe message passing for events. Message gates with event support may be referred to as event gates. A service's XML schema may indicate a set of one or more events that may be published by the service. An event gate may be constructed from the XML schema. The event gate may be configured to recognize some or all of the set of events published by a service, subscribe to those events, and distribute each event as the event is produced by the service.

The set of events for a service may be described in the service's XML message schema. For each event message in the XML schema, the event gate may subscribe itself as a consumer of that event. In one embodiment, an event gate subscribes to all events indicated by the XML schema. Each event message may be named using an XML tag. The event gate may subscribe by sending a subscription message including the XML tag for the event to be subscribed to.

When a corresponding event occurs with the service, the service may send an event message to subscribers indicating the occurrence of the event. The event message may contain an XML event document and may be sent to each subscribed gate. When a subscribed gate receives the event message, the XML event document is removed from the message and the process of distribution begins. Event distribution is the process of handing out the event document within the client platform. Each event consumer within the client platform may subscribe with the event gate for each type of event. On Java platforms, the typing system is Java (converted from the XML event type).

The event consumer may supply an event handler callback method to the event gate. The event gate may store a list of these subscriptions. As each event message arrives at the gate (from the service producing the event), the gate traverses the list of client consumers and calls each handler method, passing the XML event document as a parameter. In one embodiment, the XML event document is the only parameter passed to the handler callback method.



In one embodiment the event gate automatically subscribes itself for events on behalf of the local consumer clients. As clients register interest with the gate, the gate registers interest with the event producer service. A client may also un-subscribe interest, which causes the gate to un-register itself with the service producing the event.

5 An event gate may type check the event document using the XML schema just like a regular message gate does in the standard request-response message passing style described above. An event gate may also include an authentication credential in messages it sends and verify the authentication credentials of received event messages.

Note that any combination of the gate functionality described above may be supported in a single gate. Each type has been described separately only for clarity. For example, a gate may be a message gate, a method  
10 gate and an event gate, and may support flow control and resource monitoring

### Service Discovery Mechanisms

In one embodiment, the distributed computing environment may include a service discovery mechanism that provides methods for clients to find services and to negotiate the rights to use some or all of a service's  
15 capabilities. Note that a space is an example of a service. The service discovery mechanism may be secure, and may track and match outgoing client requests with incoming service responses.

A service discovery mechanism may provide various capabilities including, but not limited to:

- Finding a service using flexible search criteria.
- Requesting an authorization mechanism, for example, an authentication credential, that may convey to the  
20 client the right to use the entire set or a subset of the entire set of a service's capabilities.
- Requesting a credential, document, or other object that may convey to the client the service's interface. In one embodiment, the service's interface may include interfaces to a requested set of the service's capabilities.
- The tracking of discovery responses to the original requests. In one embodiment, each client request may  
25 include a collection of data that may also be returned in matching responses, thus allowing the requests and responses to be correlated.

In one embodiment of the distributed computing environment, a service discovery mechanism may provide a flexible search criteria based upon an extensible grammar. In one embodiment, a service name, service type, and other elements, if any, being searched for may be matched with elements in an XML document. In one  
30 embodiment, the XML document is the service advertisement for the service. XML may provide a flexible, extensible grammar for searching. XML also may provide type safety for matching elements. In one embodiment, the service names and service types may be type checked with the element types in the XML service advertisement.

In one embodiment, a distributed computing environment may include a mechanism for clients to  
35 negotiate service access rights. In one embodiment, the mechanism may be used to negotiate for a subset of a service's full capabilities. The result of the negotiation may be an authorization such as an authentication credential that conveys to the client the right to use the requested subset of the service's capabilities.

In one embodiment, the service discovery mechanism may allow a client to request a security capability credential from a service. In one embodiment, the client may present to the service a set of desired capabilities in

the form of a protected (secure) advertisement. The service may then respond with a capability credential that may convey to the client the rights to use the requested capabilities described in the protected advertisement.

In one embodiment, the distributed computing environment may include a mechanism for a client to negotiate service access rights and to then obtain a security credential or document that may be used to present the service's access interface to the set or subset of the service's capabilities that were requested by the client.

In one embodiment, a client that receives a capability credential from a service may generate a custom service access interface document that may be referred to as a "complete advertisement." In one embodiment, the complete advertisement may be an XML document. The generated advertisement may provide access to the service capabilities as granted to the client by the received capability credential. In one embodiment, an interface may be provided by the advertisement only to the service capabilities to which the client has been granted access by the capability credential. In one embodiment, the client may be granted access to only required capabilities and to which the client has access privileges.

In one embodiment, the distributed computing environment may provide a mechanism by which a client may negotiate capabilities with services. In one embodiment, the client may negotiate its capabilities to the service. The service may then customize results based on the parameters negotiated with the client. For example, a client that is capable of one bit display at a resolution of 160x200 may negotiate these parameters to the service, thus allowing the service to customize results for the client.

The following is included as an example of an XML capabilities message and is not intended to be limiting in any way:

```
<type name="Capabilities">
  <element name="display" type="string"/>
  <element name="memory" type="string"/>
  <element name="mime" type="string"/>
  ....
</type>
```

The distributed computing environment may include a mechanism that may allow clients to negotiate how a service is to return results of a service invocation. In one embodiment, during a capability credential request, a means by which to choose one of the results return methods may be conveyed to the service. The service may then generate a custom service advertisement that may convey to the client the results mechanism to be used, as well as the service interface.

In one embodiment, the distributed computing environment may include a mechanism for tracking service discovery search requests and responses to the requests. In one embodiment, search request and response messages may include a field that may be used to include a string or an XML document. In one embodiment, the string or XML document included in the field of a request message is also returned in the response message. In one embodiment, the string or XML document is required to be returned in the response message. In one embodiment, the string or XML document may include additional information inserted in or appended to the string or document when returned in the response message. In one embodiment, this mechanism may be used in debugging complex systems. In one embodiment, this mechanism may also provide to clients a method for

choosing services to access by using the string or XML document to pass custom search information between a client and service that may only be understood by the client and service.

#### Matching Component (Service) Interfaces

5           The distributed computing environment may provide a mechanism for matching a component (for example, a service) specification interface with a requested interface. For example, a client (which may be a service) may desire a service that meets a set of interface requirements. Each component may have a description of the interface to which it conforms. The specification interface matching mechanism may allow a component that best matches a requestor's interface requirements to be located. The specification interface matching  
10 mechanism may also allow for "fuzzy" matching of interface requirements. In other words, the mechanism may allow matching without requiring the exact specification of all aspects of the interface, thus providing a nearest match (fuzzy) mechanism. In one embodiment, the specification interface matching mechanism may be implemented as a multi-level, sub-classing model rather than requiring specification at a single interface level.

15           In one embodiment, a component may use an XML Schema Definition Language (XSDL) to describe its interface. XSDL may provide a human-interpretable language for describing the interface, simplifying activities requiring human intervention such as debugging. In one embodiment, the interface description may be provided as part of an advertisement (for example, a service advertisement) as described elsewhere in this document.

20           Using the specification interface matching mechanism, a basic desired interface may be compared to a set of component' interface descriptions. One or more components matching the basic desired interface may be identified. The interface descriptions may include subclass descriptions describing more specifically the interfaces provided by the components. In the search process, the class type hierarchy may be examined to determine if a given class is a subclass of the search type. In one embodiment, subclasses may inherit properties of the base class, and thus the subclass-specific information may not be examined in this phase. Thus, the search may be performed generically. The identified components may be searched at the next (subclass) level. The search may  
25 become specific to the subclass and may be performed by interpreting the subclass information included in the interface description. The search may continue through one or more subclasses until one or more components is determined which may provide the nearest match to the requestor's desired interface.

30           In one embodiment, an interface matching mechanism may provide the ability to distinguish among two or more components that implement similar interfaces. In one embodiment, the interface matching mechanism may provide the ability to distinguish among different revisions of the same component.

35           In one embodiment, a component description may be provided that includes a specification of the interface to which the component conforms. The component description may also include information about the component itself. The interface description and/or the component information may be used to differentiate among different implementations of a given interface. The component descriptions may include a canonical identifier and version information. The version information may allow component revisions to be distinguished. In one embodiment, the component description may be provided as part of an advertisement (for example, a service advertisement) as described elsewhere in this document.

          In one embodiment, components may be searched for a particular canonical identifier. Two or more components may be identified with matching canonical identifiers. One or more components may be selected

from among the components with matching canonical identifiers. The selection procedure may use an interface specification version, a component implementation specification, a component implementation specification version, other information or a combination of information from the component description to produce a set of one or more components that best match the requestor's requirements.

5

### Spaces

As mentioned above, the distributed computing environment relies on spaces to provide a rendezvous mechanism that brokers services or content to clients. Figure 15 illustrates the basic use of a space 114. Service providers may advertise services in a space 114. Clients 110 may find the advertisements in a space 114 and use the information from an advertisement to access a service using the XML messaging mechanism of the distributed computing environment. Many spaces may exist, each containing XML advertisements that describe services or content. Thus, a space may be a repository of XML advertisements of services and/or XML data, which may be raw data or advertisements for data, such as results.

A space itself is a service. Like any service, a space has an advertisement, which a client of the space must first obtain in order to be able to run that space service. A space's own advertisement may include an XML schema, a credential or credentials, and a URI which indicate how to access the space. A client may construct a gate from a space service's advertisement in order to access the space. A client of a space may itself be a service provider seeking to advertise in that space or modify an existing advertisement. Or a client of a space may be an application seeking to access a service or content listed by the space. Thus, spaces may provide catalysts for the interaction between clients and services in the distributed computing environment.

A space may be a collection of named advertisements. In one embodiment, naming an advertisement is the process of associating a name string with an advertisement. The association may take place upon storing an advertisement in a space. Removing an advertisement from a space disassociates the name from the advertisement. A space may be created with a single root advertisement that describes the space itself. Additional advertisements may be added to a space. An advertisement's name may locate the advertisement within the space, including specifying any necessary graphing information such as a hierarchy of names. In a preferred embodiment, the distributed computing environment does not dictate the structure of a space. That is, spaces may be structured as, for example, a flat un-related set of advertisements or a graph of related advertisements (e.g. commercial database). Since, in a preferred embodiment, the distributed computing environment does not dictate how a space actually stores its content, spaces may be supported by small to large devices. For example, a simple space may be tailored to fit on small devices, such as PDAs. More advanced spaces may be implemented on large servers employing large commercial databases.

As mentioned above, a space may contain advertisements for services in the distributed computing environment. An advertisement may provide a mechanism for addressing and accessing services and/or content within the distributed computing environment. An advertisement may specify a URI for a service. In some embodiments, the URI may allow for the service to be accessible over the Internet. An advertisement may also include an XML schema for the service. The XML schema may specify a set of messages that clients of the service may send to the service to invoke functionality of the service. The XML schema may define the client-service interface. Together, the URI and the XML specified in an advertisement may indicate how to address and

access the service. Both the URI and schema may be provided in XML as an advertisement in a space. Thus, a mechanism for addressing and accessing a service in a distributed computing environment may be published as an advertisement in a space. Clients may discover a space and then lookup individual advertisement for services or content.

5           Figure 16 illustrates advertisement structure according to one embodiment. An advertisement 500, like other XML documents, may include a series of hierarchically arranged elements 502. Each element 502 may include its data or additional elements. An element may also have attributes 504. Attributes may be name-value string pairs. Attributes may store meta-data, which may facilitate describing the data within the element.

10           In some embodiments, an advertisement may exist in different distinct states. One such state may be a drafted state. In one embodiment, advertisements may initially be constructed in a drafted state that exists outside the bounds of a space. The creator of an advertisement may construct it in a variety of ways, including using an XML editor. Access to elements and attributes in the drafted state may be at the raw data and meta-data levels using any suitable means. Typically, events are not produced for changes made to advertisements in the drafted state. Therefore, the creator of the advertisement may be free to add, change, or delete elements as well as to  
15 achieve the desired attribute set, and then publish the advertisement for the rest of the distributed computing environment to see.

          In one embodiment, another possible state for advertisements is a published state. Advertisements may move to the published state when inserted into a space. Once the advertisement is in a space, interested clients, and services may locate it, e.g. using its name and/or its elements as search criteria. For example, search criteria  
20 may be specified as an XML template document that may be compared (e.g. by the space service) with the advertisements in the space. Published advertisements may represent "on-line" services ready for clients to use. The message address (URI) of the service may be stored as an element in the advertisement. Advertisements that are removed from the space may transition back to the drafted state where they may be discarded or held. Removal may generate an event so interested listeners may be made aware of the change. Message gates are  
25 typically created from published advertisements.

          In one embodiment, yet another possible state for advertisements is a persistent archived state. An archival procedure may turn a live published advertisement into a stream of bytes that may be persistently stored for later reconstruction. Archived advertisements may be sent (e.g. in their raw XML form) from the space to an archival service. The URI for an advertisement's archival service may be stored as an element in the  
30 advertisement. XML may provide a format for storing and retrieving advertisements and representing the state of advertisement elements sufficient to reconstruct the advertisement object(s). Advertisements may be stored in other formats as well, depending on archival service implementation. The process of making a published advertisement persistent may prepare the advertisement for the persistent archived state. Persistent advertisements may be stored (e.g. by an archival service) for future use in a persistent storage location such as a file or a  
35 database. A space through the archival procedure may enable advertisements to be stored, however the space does not necessarily play a role in how persisted advertisement entries are actually stored. How persisted advertisements are stored may be determined by the advertisement's archival service. Typically, no events are generated on behalf of archived advertisements. Also, changes may not be allowed for advertisements in the persistent archived state.

Advertisements may be archived and removed or just archived. If an advertisement is archived without removing it from the space, the space will store a shadow version of the advertisement. Access to an archived service may cause the advertisement to “fault-in” from its persistent backing store on demand. This feature may allow advertisements to be filled, from LDAP (Lightweight Directory Access Protocol) entries for example, on demand.

Figure 17 illustrates one example of advertisement state transitions that an advertisement may undergo during its lifetime. First, an advertisement may be constructed, as indicated at 1. During construction, the advertisement is in the drafted state. Then, the advertisement may be inserted in a space, as indicated at 2. The advertisement may be inserted as a published parent. The advertisement is in the published state after being inserted in a space. An event (e.g. AdvInsertEvent) may be generated when the advertisement is inserted in the space. Events are more fully discussed below. The advertisement may be archived and made persistent, as indicated at 3, which may transition the advertisement to the persistent archived state. An advertisement may also be published from the persistent archive state, as indicated at 4. An advertisement may be removed from a space and transition back to the drafted state, as indicated at 5. An event (e.g. AdvRemoveEvent) may be generated when the advertisement is removed.

In one embodiment, the archived, persistent state is not used. In this embodiment, state changes 3 and 4 also are not used. In this embodiment, an advertisement is either in the drafted state or in the published state.

Advertisements stored in a space may have the following standardized elements and/or attributes: version (may be an element), creation date (may be an attribute), modification date (may be an attribute), implementation service URI (may be an element), and/or persistence archival service URI (may be an element).

A space itself is typically a service. A space service may provide the ability to search for advertisements in the space, which may include searching the space by type of advertisements. A space service may also provide facilities to read advertisements, write (publish) advertisements, and take (remove) advertisements. A space may also provide the ability to subscribe for space event notification messages. Some spaces may provide extended facilities, such as facilities to navigate space relationship graph by position; read, write or take advertisement elements; read, write or take advertisement attributes; and subscribe for advertisement event notification messages. Space facilities are described in more detail below. A space’s capabilities are embodied in a space advertisement's message schema. From the message schema, space address, and authentication credential, a client message gate may be created to access the space and its facilities.

Spaces and all advertisements within a space may be addressed using URIs. In one embodiment, space and advertisement names may follow URL naming conventions. The use of URIs, e.g. URLs, for addressing spaces may allow spaces to be addressable throughout the Internet, in some embodiments.

The space message recipient (a space service) may be specified using a URI which may have been received in a service advertisement for the space. The URI may include a protocol, host, port number, and name. The protocol may name the protocol that may be used to move messages between clients and the space (reliable or un-reliable sockets, for example). The host and port number may be protocol dependent IDs. The name may be the space name followed by advertisement, element and/or attribute name. In one embodiment, a pathname may be used to identify an advertisement in a space. Pathnames may be either absolute or relative. Absolute pathnames name the space as well as an advertisement. Relative pathnames are relative a designated

advertisement within an assumed space. In one embodiment, the syntax rules governing the construction of pathnames is that of the URI (Uniform Resource Identifier). In that embodiment, advertisement and space names therefore may not contain any URI reserved characters or sequences of characters. Pathnames to elements and attributes may also be specified using a URI. In general, element and attribute names may be appended to the  
5 pathname of an advertisement, such as:

`http://java.sun.com/spacename/advertisement/element/attribute.`

In one embodiment, the distributed computing environment may include a mechanism that allows a client to discover the URI of a space but restricts access to the service advertisement for the space. In one embodiment, rather than returning the full advertisement to the space, the URI of the space and the URI of an authentication  
10 service for the space may be returned. In order for the client to access the documents or services advertised in the space, the client first may authenticate itself to the authentication service at the URI provided in the return message. The authentication service may then return an authentication credential that may allow the client partial or full access to the space. When the client receives the authentication credential, the client may attempt to connect to the space to access the documents or service advertisements in the space.

The distributed computing environment may provide a mechanism or mechanisms that may enable a client to connect to a space. Embodiments of a connection mechanism may provide for client-space addressing, client authorization, security, leasing, client capabilities determination, and client-space connection management. A client-space connection may be referred to as a session. In one embodiment, a session may be assigned a unique session identification number (session ID). The session ID may uniquely identify a client-space connection. In  
15 one embodiment, a session lease mechanism may be used to transparently garbage collect the session if the client does not renew the lease.

The following is an example of using such a connection mechanism according to one embodiment. A client may obtain an authentication credential. In one embodiment, the space may provide an authentication service in response to a client's request for access to the space. The client may obtain the authentication credential  
25 through the authentication service. When the client receives the authentication credential, the client may initiate a connection to the space by sending a connection request message. In one embodiment, the connection request message may include the URI address of the space service, the authentication credential for the client and information about the connection lease the client is requesting. After the space receives the connection request message, the space may validate the message. In one embodiment, an XML schema may be used to validate the  
30 message. The client may then be authenticated using the authentication credential. In one embodiment, the information received in the connection request message may be used to determine the capabilities of the client to use the space. In one embodiment, each client of a space may be assigned its own set of capabilities for using the space. In one embodiment, an access control list (ACL) that may include capability information about one or more clients of the space may be used in client capabilities determination. In one embodiment, the information  
35 received in the connection request message may be used to look up the client's capabilities in the ACL.

After authenticating the client and determining the client's capabilities, the connection lease to grant the client may be determined. After the lease is determined, the structure for maintaining the client-space connection may be generated. A session ID for the connection may be generated. In one embodiment, each client-space connection may be assigned a unique session ID. In one embodiment, an activation space may be created and

assigned to, or alternatively a pre-existing activation space may be assigned to, the client-space session. In one embodiment, an activation space may be used to store results of services for the client when using the space. In one embodiment, a client's capabilities may be used to determine if an activation space is to be created for the client. For example, a client may not have capabilities to access an activation space to store and retrieve results.

5 A message or messages may be sent to the client informing the client that the connection has been established. The message or messages may include the session ID and information about the lease. The client may then use the space including, but not limited to: advertisement lookup, advertisement registering, and advertisement retrieval. In one embodiment, the connection may remain open until the allocated lease expires or until the client sends a message requesting lease cancellation to the space. In one embodiment, the client may be responsible for  
10 renewing the lease before the lease expires. If the lease expires before the client renews the lease, the connection may be dropped, causing the client to lose the connection to the space. In one embodiment, to reconnect, the client may be required to repeat the connection procedure.

In one embodiment, a client of a space may obtain a space's advertisement several different ways. Some of the ways a client may obtain a space's advertisement are illustrated in Figure 18. For example, a space  
15 discovery protocol may be provided as part of the distributed computing environment. Space discovery is a protocol a client or service may use to find a space. A listener agent 202 may be configured associated with one or more spaces to listen for discovery requests. The discovery listener agent 202 may listen on various network interfaces, and may receive either broadcast requests or unicast requests (at the URI of the agent) from clients 200a looking for a space(s). The listener agent 202 then responds with the service advertisement(s) or URIs for  
20 the service advertisements of the requested space(s). In one embodiment, the listener agent is, in general, separate from the space, because its functionality is orthogonal to the functionality of a space service. However, the listener agent may be implemented on the same device or a different device as a space service.

In one embodiment, the discovery protocol may be a service advertised in a default space. A client may instantiate the discovery protocol from the client's default space in order to discover additional spaces. The  
25 discovery protocol may be pre-registered with a client's default space. Alternatively, the discovery protocol may register itself with the default space by placing an advertisement in that space, e.g., when a client connects to a local network serviced by the discovery service.

In one embodiment, the space discovery protocol may be mapped to underlying device discovery protocols for other platforms, such as SLP, Jini, UPnP, etc. Thus, a client may use the discovery protocol of the  
30 distributed computing environment to find services in other environments. A bridge to these other environments may be provided, and advertisements provided to services in these other environments so that clients of the distributed computing environment described herein may access them. Refer to the *Bridging* section.

For each advertised discovery protocol, the distributed computing environment may create a subsequent results space to hold the results of the discovery protocol. In one embodiment, space services in the distributed  
35 computing environment may use the Multicast Announcement Protocol (multicast UDP) to announce themselves on a LAN. A listener agent may record this information. A device (either a client or service) may use the Multicast Request Protocol (multicast UDP) to initiate discovery of a space manager. In one embodiment, the space managers respond with information indicating the URI of their respective spaces. Alternatively, a listener agent may respond for multiple spaces. The discovery response may also include a short string that labels the each



space (e.g. obtained from keywords of the space), and information that can be used to set up a TCP connection, for example, with each space manager to perform operations on the respective space. Since the requesting device may receive responses from more than one space manager (or multiple space listings from a listener agent), this information may help the client select which space it wishes to connect to.

5 In addition to the multicast discovery described above, the discovery service may also perform discovery using unicast messaging (e.g. over TCP) that can be used to discover a space manager at a known address on the network (e.g. the Internet, other WAN, LAN, etc). The unicast discovery message may include a request for a space service at a known URI to provide its service advertisement. The multicast and unicast discovery protocols are defined at the message level, and thus may be used regardless of whether the devices participating in the  
10 discovery support Java or any other particular language.

The discovery protocol may facilitate the proliferation of clients independently of the proliferation of server content that supports those clients within the distributed computing environment. For example, a mobile client may have its initial default space built into its local platform. In addition to local services advertised in the default space, the mobile client may have services that search for additional spaces, such as a service to access the  
15 discovery protocol or a service to access space search engines.

In one embodiment, the distributed computing environment space discovery protocol may define a set of XML messages and their responses that may allow clients to:

- Broadcast protocol-defined space discovery messages on their network interfaces.
- Receive from listeners XML messages describing candidate spaces that those listeners  
20 represent.
- Select one of those discovered spaces as default, without the client needing to know the address of the selected space.
- Obtain information on the selected space, such as its address, so the client may later find that same space via means outside of the discovery protocol (useful if later the client wants  
25 to access a space which is no longer local, but which still is of interest to the client).

In some embodiments, the multicast and unicast discovery protocols may require an IP network. Although these discovery protocols meet the needs of devices that are IP network capable, there are many devices that may not be directly supported by these discovery protocols. To meet the needs of such devices in discovering spaces in the distributed computing environment, a pre-discovery protocol may be used to find an IP network capable  
30 agent. The pre-discovery protocol may include the device sending a message on a non-IP network interface requesting a network agent. The network agent may set up a connection between itself and the device. Once the connection between device and agent is set up, the agent participates in the discovery protocol on IP networks on behalf of the device for which it serves as agent. The network agent may also provide an interface for the device to the distributed computing environment in general. For example, gates may be constructed in the agent on behalf  
35 of the device for running services advertised in discovered spaces. See the *Bridging* section.

Another way that clients may locate spaces in the distributed computing environment is by advertisement of a space in another space. A space is a service, therefore, like any other service, it can be advertised in another space. As shown in Figure 18, a client 200b may find an advertisement 206 in a first space 204a for a second space 204b. Space 204b may in turn include advertisements to additional spaces. Because a service

(implementing a space) may also act as a client, spaces may exchange advertisements or chain together to provide a federation of spaces, as illustrated in Figure 19. Any number of spaces may be included in the distributed computing environment. The number and topology of spaces may be implementation dependent. For example, spaces implemented on an IP network might each correspond to a different subnet.

5           A third way a client may locate a space is through running a service 208, as shown in Figure 18. A service 208 may be run which returns as its results the service advertisements of space services. Since service advertisements are XML documents and since the distributed computing environment may include the Internet, service 208 may be a Web-based search tool. An example of such a service is the space look-up service described in conjunction with Figure 4. In one embodiment, spaces within the distributed computing environment may be  
10 implemented as Web pages. Each Web page space may include a keyword that may be searched upon to identify the Web page as a space in the distributed computing environment. The space may include other searchable keywords as well to further define the space. A client may connect to a search service 208 and supply keywords to the search service in the form of XML messages. The search service may receive the keywords from the client and feed the keywords to an Internet search engine, which may be a conventional or third-party search engine. The  
15 search service may return the results from the Internet search engine to the client, either directly as XML messages or by reference to a results space. The results may be the URIs of spaces matching the search request. Alternatively, the search service may contact spaces identified by the search, obtain the service advertisement for each such space, and return the space service advertisements to the client, either directly as XML messages or by reference to a results space. The client may then select a space from the search results and construct a gate (by  
20 itself or through a proxy) to access the selected space. Once the selected space is accessed, the client may look up service advertisements within that space, which may lead to additional spaces.

As described above, a space may be an XML-based Website, and as such may be searched via Internet Web search mechanisms. A space may include Internet searchable keywords. Some devices, such as small client devices, may not support an Internet browser. However, such devices may still perform Internet searches for  
25 spaces within the distributed computing environment. A device may have a program that accepts strings of keywords, which may be sent to a proxy program on a server (e.g. a search service). The proxy may send the strings to a browser-based search facility (e.g. an internet search facility) to perform the search. The proxy may receive the output of the search and parse it into strings (e.g. XML strings) representing each URI for the search results and send the response strings back to the client. Thus, a client may locate spaces through the Internet  
30 without having to support a program such as a Web browser. More capable devices may avoid the use of a proxy and initiate an Internet-based search service directly.

A fourth way a client may locate a space is by obtaining or receiving information about a newly created empty space or a spawned space when an existing space is spawned. An existing space may include an interface for spawning an empty space with the same functionality (e.g. same XML schema) as the space from which it is  
35 spawned. Spawning of spaces is further described below.

Once a client of a space finds the advertisement of a space service, that client of the space may run the space service, as it would any other service. Note that the client of the space service may be another service (e.g. a service seeking to advertise in the space). In one embodiment, as illustrated in Figure 20, to run a space service, the client of the space may first run an authentication service for the space to obtain an authentication credential,

as indicated at 300. The authentication service may be specified in the service advertisement of the space service. The client of the space uses the authentication credential, the XML schema of the space (from space's service advertisement), and the URI of the space (from space's service advertisement) to construct a gate for the space, as indicated at 302. The client of the space may then run the space service by using the gate to send messages to the space service. A first such message is indicated at 304.

For embodiments employing authentication, when the space service receives the first message from the client, with the authentication credential embedded, the space service uses the same authentication service (specified in the service advertisement of the space service) to authenticate the client, thus establishing its identity, as indicated at 306. The space service may determine the client's capabilities and bind them to the authentication credential, as indicated at 308.

As indicated at 310, a client of a space may run various space facilities by sending messages to the space service. In one embodiment, when a client of a space sends a request to the space service, it passes its authentication credential in that request, so the space service can check the request against the client's specific capabilities.

Each space is typically a service and may have an XML schema defining the core functionality of the space service. The XML schema may specify the client interface to the space service. In one embodiment, all space services may provide a base-level of space-related messages. The base-level space functionality may be the basic space functionality that is capable of being used by most clients, including small devices such as PDAs. It may be desirable to provide for additional functionality, e.g. for more advanced clients. Extensions to the base-level space may be accomplished by adding more messages to the XML schema that advertises the space. For example, in one embodiment, the base-level messages do not impose any relationship graph upon the advertisements. Messages, for example, to traverse a hierarchy of advertisements may be a space extension. Such additional functionality may be provided through one or more extended XML space schemas or schema extensions for a space. The extended schemas may include the base schema so that clients of an extended space may still access the space as a base space.

In one embodiment, a base space service may provide a transient repository of XML documents (e.g. advertisements of services, results of running services). However, a base space service in one embodiment may not provide for advanced facilities to support persistence of space content, navigation or creation of space structure (e.g. hierarchy), and a transactional model. A mechanism for supporting persistence, hierarchy, and/or transactions is by extending the XML schema. Since extended spaces still include the base XML schema, clients may still treat extended spaces as base spaces, when just the base space functionality is all that is need or all that can be supported.

In one embodiment, the base space may be transient. The base space may be acceptable for many purposes. Service providers may register their services in various spaces. In one embodiment, services must continuously renew leases on the publishing of information in the spaces. By this nature, the services advertisements may be transient in that they may often be rebuilt and/or reconfirmed. However, it may be desirable to provide for some persistence in a space. For example, a space that has results may provide some persistence for users that want to be sure that results are not lost for some time. In one embodiment, persistence may be provided for by specifying a space interface where the client may control which objects in the space are

backed by a persistent store and manage the maintenance of that persistence store. The persistence interface may be specified with extended XML schema for the space defining the interfaces for persistence.

In one embodiment, a base space may provide an interface where an XML document may be added to a space and identified by a string. The base space may not provide any hierarchy for the various so named XML documents in the space. In embodiments where hierarchy support is desired, additional interfaces may be defined (extending the XML schema) where the user can specify a hierarchy. Other interfaces may be specified to navigate the hierarchy or navigate a relationship graph by position. However, other users may still use the base space interfaces to access those same documents, without any hierarchy. Interfaces for other space structure may be provided for as well in extended space schemas.

Extended XML space interfaces may also be provided for space transaction models. For example, an extended space XML schema may be provided specifying an interface for ACID transactions. ACID is an acronym used to describe four properties of an enterprise-level transaction. ACID stands for Atomicity, Consistency, Isolation, and Durability. Atomicity means that a transaction should be done or undone completely. In the event of a failure, all operations and procedures should be undone, and all data should rollback to its previous state. Consistency means that a transaction should transform a system from one consistent state to another consistent state. Isolation means that each transaction should happen independently of other transactions occurring at the same time. Durability means that completed transactions should remain permanent, e.g. even during system failure. Other transaction models may also be specified in extended space schemas.

Extended space schemas may be XML documents that specify the message interface (e.g. XML messages) for using extended space features, functionality or facilities. A space may have a base schema and multiple extended schemas. This may facilitate provided different levels of service to different clients depending upon the client authentication.

Besides extensions for space persistence, structure, and transactions, other space extensions may also be specified as desired. For example, extensions may be provided to manipulate advertisements at the element or attribute level: read, write or take advertisement elements; read, write or take advertisement attributes; and subscribe for advertisement event notification messages. A space may provide virtually any number of facilities and arrange them in base and extended schemas as desired. In one embodiment, all base spaces must provide for advertisement reading, writing, taking, and lookup facilities, and space event subscriptions.

Various space facilities may be provided. In some embodiments, a facility may be provided for the establishment of a session with the space. In one such embodiment, the rest of the space functionality is not available until this is done. In other embodiments, the notion of a session is not provided for, or is optional and/or implementation dependent.

Another space facility may be to add or remove a service advertisement to or from the space. A space facility may also be provided for adding or removing an XML document (not an advertisement, but perhaps a result in a space). The space service may check for uniqueness of an item before allowing the addition of the item. For example, each item added to the space may be associated with a user-specified string that identifies the item and that may be used to check for the uniqueness of the item.

In one embodiment, a client may request a listing, tree or other representation of all services advertised in the space. The user then may scroll or maneuver through the advertisements and select the desired service. A

space may also provide a look-up facility that allows a client to search for a service by providing keywords or string names. In one embodiment, a space facility may provide a mechanism to look up a space entry that has been added to the space. The look up facility may search by string to match for name, or wildcard, or even database query. The look up facility may return multiple entries from which the client may select one or perform a further  
5 narrowing search. In one embodiment, the look-up facility may provide a mechanism to locate a service advertisement matching a particular XML schema. The client may indicate a particular XML schema, or part of a particular XML, to be searched for within the space. Thus, a service may be searched for within a space according to its interface functionality.

Another space facility that may be provided in the distributed computing environment is a mechanism  
10 that allows services and clients to find transient documents based upon a typing model such as XML. The mechanism may be a general-purpose, typed document lookup mechanism. In one embodiment, the lookup mechanism may be based upon XML. The lookup mechanism may allow clients and services to find documents in general, including services through service advertisements.

In one embodiment, a space lookup and response message pair may be used to allow clients and services  
15 to find XML documents stored within a network transient document store (space). The space may be a document space used to store a variety of documents. In one embodiment, the documents are XML documents or non-XML documents encapsulated in XML. Spaces are further described elsewhere herein. The lookup messages may work on any kind of XML document stored in the space, including service advertisements and device driver advertisements. In one embodiment, a client (which may be another service) may use a discovery mechanism as  
20 described elsewhere to find one or more document spaces. Then, the client may use space lookup messages to locate documents stored in the space.

The distributed computing environment may include a mechanism that allows services and clients to subscribe to and receive events about the publication of XML documents. Events may include the publication of and removal of XML documents to and from a transient XML document repository such as a space. In one  
25 embodiment, an event may be an XML document that refers to another XML document.

In one embodiment, a space event subscription and response message pair may be used to allow clients and services to subscribe for events regarding documents that are added to or removed from a space. In one embodiment, an event subscription may be leased using the leasing mechanisms described elsewhere herein. In one embodiment, a subscription may be cancelled when the lease is cancelled or expires. In one embodiment,  
30 renewing the lease to the subscription may renew a subscription.

In one embodiment, an event subscription message may include an XML schema that may be used as a document matching mechanism. Documents that match the schema may be covered by the subscription. In one embodiment, any document added to a space and that matches the XML schema may generate a space event message.

A space facility may also be provided to which a client may register (or unregister) to obtain notification  
35 when something is added to or removed from the space. A space may contain transient content, reflecting services that are added and removed from the space. A mechanism may be provided to notify a client when a service becomes available or becomes unavailable, for example. A client may register with an event service to obtain such notification. In one embodiment, a client may register to be notified when a service having a name matching a

specified string or a schema matching a specified schema (or schema portion) is added or deleted from the space. Thus, a query to register with the space event notification facility may be the same as or similar to that of the service look up facility described above.

Events may be typed. In some embodiments, the event facilities supported by spaces may allow for event listeners to take advantage of, e.g., Java class (or XML types) hierarchies. For example, by listening for AdvElementEvent, the listener will receive events of type AdvElementEvent and all of its sub-classes (XML types). Thus, for this example all events pertaining to element changes (though not advertisement insertion and removal) are received.

By way of further example, subscribing to or listening for a top-level event class or type, e.g. SpaceEvent, will result in the reception of all space events. Event class types may be distinguished via, for example, the Java *instanceof* operator or the XML typing system.

An event may include a URI to the affected advertisement or element. For example, AdvertisementEvent and all its sub-classes may contain a reference (e.g. URI or URL) to the affected advertisement. AdvElementEvent and its subclasses may be examined for the name of the affected element. The previous element value (URI or URL), may be available, for example, from AdvElementRemoveEvent and AdvElementValueChangeEvent.

A space event type hierarchy for one embodiment is illustrated in Figure 21. Types may be defined in XML and usable in Java or any other suitable object-oriented language such as C++.

A space may provide a facility for a client to instantiate a service advertised in the space. Service instantiation is the initialization done that allows a client to be able to run a service. On embodiment of service instantiation is illustrated in Figure 22. To instantiate a service, a client may first select one of the service advertisements published in the space, as indicated at 320. The client may use the various facilities, such as the look up facility, provided by the space to look up the various advertisements in the space. Then the client may request the space to instantiate the service, as indicated at 322.

In one embodiment, service instantiation may include the following actions. After the client requests the space service to instantiate the selected service, as indicated at 322, the space service may then verify the client is allowed to instantiate the requested service, as indicated at 324. The space service may perform this verification by examining an authentication credential included in the client's message. The authentication credential is the credential the client received when it established a session with the space service. The space service may verify if the client is allowed to instantiate the requested service according to the client's authentication credential and capabilities indicated for that client. See the Authentication and Security section herein.

Assuming the client is authorized, the space service may also obtain a lease on the service advertisement for the client with the lease request time specified by the client, as indicated at 326. Leases are further discussed below. The space service may then send a message to the client which includes the allocated lease and the service advertisement of the service, as indicated at 328. In one embodiment, the client may run an authentication service specified in the service advertisement and obtain an authentication credential, as indicated at 330. See the Authentication and Security section herein for more information on an authentication service. Next, as indicated at 332, the client may construct a gate for the service (for example, using the authentication credential and the XML schema and service URI from the advertisement). Refer to the Gates section herein. The above described communication between the client and space service is performed using the XML messaging of the distributed

computing environment. The client may then run the service using the constructed gate and XML messaging. The service may similarly construct a service gate for XML message communication with the client.

To summarize, an example use of a space is discussed as follows. A client may access (e.g., connect to) a space service. (A service may act as a client for the purpose of accessing or otherwise using a space.) The space service may store one or more service advertisements and/or other content in a space, and each of the service advertisements may include information which is usable to access and execute a corresponding service. The space service may include a schema which specifies one or more messages usable to invoke functions of the space service. For example, the schema may specify methods for reading advertisements from the space and publishing advertisements in the space. The schema and service advertisements may be expressed in an object representation language such as eXtensible Markup Language (XML). In accessing the space service, the client may send information such as an XML message (as specified in the schema) to the space service at an Internet address. In accessing the space service, the client may search the one or more service advertisements stored in the space. The client may select one of the service advertisements from the space. In one embodiment, the client may send an instantiation request to the space after selecting the desired service advertisements from the space. A lease may be obtained for the desired service, and the lease and the selected service advertisement may be sent by the space service to the client. The client may then construct a gate for access to the desired service. The desired service may be executed on behalf of the client.

Another facility provided by a space service may be the spawning or creation of an empty space. This space facility may allow a client (which may be a service to another client) to dynamically create a new space. In one embodiment, this space facility may include an interface for spawning an empty space with the same functionality (same XML schema or extended schema) as the space from which it is spawned. This facility may be useful for generating (e.g. dynamically) spaces for results. For example, a client may spawn a space a request a service to place results or advertise results in the spawned space. The client may pass the spawned space URI and/or authentication credential to the service. Or a service may spawn a space for results and pass the spawned space URI and/or authentication credential to the client. In some embodiments, once a space is spawned, it may be discovered just like other spaces using one or more of the space discovery mechanisms described herein.

By using a mechanism in which a space may be created via an interface in another space (e.g. a space spawning facility), new spaces may be created efficiently. For example, in one embodiment, storage for the spawned space may be allocated using the same facility used by the original space for storage. Also, a spawned space may share a common service facility with its original (or parent) space. For example, a new URI may be assigned to the new space. In one embodiment, the new URI may be a redirection to a common space facility shared with the original space. Thus, a newly spawned space may use the same or some of the same service code as that of the original space.

Space facilities may also include security administration, for example, to update the various security policies of the space, and other administrative facilities. For example, the number and age of advertisements may be controlled and monitored by a root space service. Old advertisements may be collected and disposed. See, e.g., the Leases section herein for when an advertisement may be considered old. The service implementing the space may be under the control of an administrator. The administrator may set policy in a service dependent manner. Space facilities may also include a facility to delete an empty space.

Certain spaces may include facilities or services to further support the proliferation of certain clients, such as mobile clients. For example, services in spaces that a mobile client may discover, e.g. via the discovery protocol, may provide support for mobile clients, such as:

- Assigning and administering temporary network addresses for the client.
- Proxying message passing for the client.
- Providing search facilities for additional spaces. For example, a service may allow a client to specify keywords through a simple interface. The service then uses the keywords in conjunction with Web search engines to search for spaces on the Web, as further described herein. In other embodiments, a search service may constrain clients to searching only a few supported spaces within the distributed computing environment.

As mentioned earlier (see Figure 9 and accompanying text), spaces may provide a convenient mechanism for storing results from a service run by a client. Using a space for results may allow a small client to receive in pieces the results of running a service. Some services may generate a large amount of results. By using a space to store the results from a service, clients that do not have the resources to receive the full results at once may still use the service. Moreover, by using a space to store results, a service running on a fast busy server may be freed from interacting directly with a slow client when returning large results. Thus, the service may be freed sooner for use by other clients.

A space may provide a convenient mechanism for accessing a result by different clients and/or at different times. For example, a client may not be able to use the entire result, but a user may want to access the rest of the result later using another client that can access it. For example, the result could be stock quote information, showing the current price of a stock (accessible by a PDA), and showing a chart of stock prices (accessible by a laptop later). Also, using a space in the distributed computing environment for results may allow a client to feed the result of one service into another service, without the necessity of downloading the result first. For example, in the case of the stock quote information above, the PDA could feed the chart into another service, which prints the chart, without the PDA having to download the chart itself. Thus, a results space may provide a mechanism for a client to pass to another client or service without the client having to handle or receive the results.

In different embodiments, the decision to use a space for results may be mandated by the service, mandated by the client, and/or requested by the client. A service may suggest the use of a space for its results, e.g., in its advertisement. In one embodiment, either the client or the service may spawn a new space for results or use an existing space for results. See the description herein regarding spawning spaces.

In one embodiment, the use of a space for results does not necessarily mean that the service must put all results in that space. There may be alternatives for any result a service generates. For example, part or all of the result may be sent in-line in a message to the client. Alternatively, the result may be put in the space, and then a notification message may be sent to client, referencing the result (e.g. including a URI to the result or to an advertisement for the result). Another option may be to put the result in the space, with notification via an event from the space. For example, the client and the service may agree to call the result some particular name, and then the client may register with the space (using a space facility such as described above) to receive an event when a result so named is added to the space. See the description above on event notification.



Thus, several different mechanisms may be employed within the distributed computing environment for a service to return results to a client. The actual results may be returned to the client by value in an XML message, or results may be returned to the client by reference with the actual results (or advertisement for the actual results) put in a space and the client receiving a message referencing the results in the space. Moreover, results, or results advertisements, may be placed in a space and the client notified by event.

Another mechanism for handling results may be for the client to specify another service for the results to be fed to. For example, when a client runs a service that will produce results, the client may instruct that service (e.g. through XML messaging) to send the results to another service for further processing. This may involve the client indicating the URI of an advertisement for the other service so that the result-producing service may generate a gate to the other service in order to run the other service and pass it the results. In this example, the result-producing service may be a client of the other service. In some embodiments, the client may send the schema or a pre-constructed gate to the result-producing service to access the service for further processing. An example of a service for further processing is a display service that may display the results for the original client. This display service may be on or associated with the same device as the client.

Result spaces and method gates may allow the distributed computing environment to provide a simple remote method invocation that is practical for thin clients with minimal memory footprints and minimal bandwidth, because it need not have the adverse side effects of huge program objects (along with needed classes) being returned (necessarily) across the network to the client as in conventional remote method invocation techniques. Instead, results may be returned to a result space, and only if desired (and if they can reside on the client) are the actual objects downloaded to the client.

The mechanism by which the distributed computing environment may provide for remote method invocation is as follows (refer also to the description of method gates in the Gates section herein). An object may be advertised (e.g. as a service or as part of a service) in a space. The advertisement includes a reference that contains the URI (e.g. URL) of the object, along with other access parameters, such as security credentials and XML schema. A client may have or may construct a client method gate for the object, which for every method of the object (or service) itself may have a wrapper method that takes the method parameters and creates a request XML message to invoke a method of the object. The XML message is sent to a service gate that invokes the actual method on the service object. When that method returns a result object, the service gate may post the result object in a results space, and may return a message to the client with a reference to the result object.

Thus, for a client to invoke a remote method, the client first sends a message to instantiate an object (e.g. service), such as described above. In one embodiment, instantiation of an object may include the creation or spawning of a results space. In another embodiment, results space creation may be independent from the object instantiation. Instantiation may return the object URI to the client, and the client and service gates may be dynamically created when a client requests instantiation. In some embodiments, a results space may already exist and be advertised by the object (service). Some part or all of the gates may also have been pre-constructed or reused.

Once a client has initiated an object, a local call of the appropriate client method gate will affect a remote call to the actual remote object, as described above. The remote method invocation approach of the distributed computing environment may be recursive, with object references returned to the client, instead of the objects itself,

when the client gate is called. Note that such returned objects may already be instantiated. In some embodiments, the client may make a decision to download an entire object itself, rather than just remotely invoke it.

A method or service invoked as described above may generate a child gate that is associated with the results document. The method may return a child gate (or the schema, URI and credentials for the client to  
5 construct a child gate) for the references instead of the references themselves. The client may then access the references through the child gate. The child gate may also be a method gate.

As described above, this remote method invocation provided by the distributed computing environment allows the real result object(s) to be stored in a service results space (which also may be created dynamically, by a servlet for example). The results space may be temporary. The results space may act as a query results cache.  
10 The results cache may be patrolled by server software (garbage collector) that cleans-up old result areas. Distributed garbage collection may be employed, as result spaces may fill up until they are destroyed by a client indicating it no longer needs the space, or by an administrator on a server setting appropriate limits.

Turning now to Figure 23, an illustration of a default space 350 is provided. The distributed computing environment may provide at least one default space so clients can find an initial set of advertisements. A device  
15 may have a default space that exists locally, with a built-in pre-constructed gate. The services advertised in that default space may exist locally on that device, and they may provide system software that enables or facilitates the device's participation in the distributed computing environment.

The default space 350 may include one or more mechanisms 352 to locate external spaces, as shown in Figure 23. One service in the default space may run the space discovery protocol described above to find external  
20 spaces. Also, external spaces may be advertised in the default space. Additionally, a service (e.g. a search engine or a proxy service to a search engine) may be advertised in the default space that determines or finds external spaces. Each space may be analogous to a file system mount point. Thus, the distributed computing environment may provide searchable, dynamic mount points to services. A default space may be a client's initial mount point to the distributed computing environment.

A default space or access to a default space may be built in to a device. Through the default space and local services that may exist on the device, a client execution environment for the distributed computing environment may be provided. A device's local services and default space service may have built-in pre-constructed gates. One of the built-in services listed in the default space may be a service to run the discovery protocol so that the client may locate additional (e.g. external) spaces. A default space may include a built-in  
30 service that provides an execution environment for clients that allows the client user to browse spaces, select, and then instantiate services. Such a service may provide a simple user interface that allows a client to enter strings (e.g. keyword for space searches), view or browse result references (e.g. space listings, or service listings within a space), select items (e.g. to choose and instantiate a service), etc.

Devices that primarily provide a service may also include a default space and may include a built-in  
35 service in the default space that allows a service to manage advertising itself in various spaces. For example, a device, such as a printer, may have a built-in default service that finds (perhaps through the discovery protocol) a space on a local area network and adds an advertisement for the printer service to that space. This service may also maintain the printer service advertisement within the LAN space, for example, by renewing its lease or updating the printer's XML schema, etc.

For some devices that provide a service, the overhead of finding a space to advertise its service and maintain that advertisement is undesirable. In one embodiment, rather than searching for and maintaining a space or spaces to publish service advertisements, services on some devices may transmit their advertisements in response to connection requests. For example, a printer device with a printer service that is available on a proximity basis may not maintain an advertisement in a space (on the device or external to the device). Instead, when another device establishes a connection with the printer device (for example, a user with a laptop running a client desires to print a document), the printer service may transmit the service advertisement to provide the XML service schema for connecting to and running the service that provides printing functionality on the printer device. Also, some devices may only maintain advertisements for their services in a certain vicinity or local network. Such a device may not desire to support or may not have access to transports for broader accessibility.

One example of a service device in which it may be desirable for the device to avoid or limit maintaining service advertisements in a space is a device whose functionality is available on a proximity basis. Proximity-based services may provide advertisements of their functionality upon request. These advertisements may not be broadly accessible. For example, proximity-based services may be provided in a wireless communications system. The term “wireless” may refer to a communications, monitoring, or control system in which electromagnetic or acoustic waves carry a signal through atmospheric space rather than along a wire. In most wireless systems, radio frequency (RF) or infrared (IR) waves are used. Typically, in proximity-based wireless systems, a device comprising a transceiver must be within range (proximity) of another device to establish and maintain a communications channel. A device may be a hub to connect other devices to a wireless Local Area Network (LAN).

As mentioned, embodiments of the distributed computing environment may provide a mechanism using a lookup space that allows clients to rendezvous with services. In a proximity computing environment, one embodiment of the distributed computing environment may provide a service discovery mechanism that clients may use to discover services without using lookup spaces as rendezvous points. An example of a proximity computing environment is an IrDA point-to-point communications environment. In a proximity computing environment, the proximity mechanism may find the “physical” location of the service for the client. For example, in an IrDA environment, the client device may be physically pointed at the device including the service(s) that the client desires to use.

The proximity service discovery mechanism may enable the client to directly look for service advertisements rather than sending a lookup request to a lookup space to look for service advertisements. Since the client device may have established a proximity connection to the service device, the client may directly request the desired service. For example, a PDA client device may establish a proximity connection to a printer device; the client may “know” to request a printer service connection on the printer device.

In one embodiment, the client may send a proximity service discovery message to the service device. The message may include information that may specify a desired service on the service device to which the client device has a proximity connection. In one embodiment, a service on the service device may respond to the proximity service discovery message, and may send to the client the service advertisement that the client may use to connect to the desired service. The proximity service discovery message may also include information that may

be used to authenticate the client and to establish the client's capabilities on the service. Using the received service advertisement, the client may establish a gate to establish communication with the desired service.

Nevertheless, it may still be desirable to publish advertisements for services that do not desire to or cannot maintain their advertisements in a space that is broadly accessible. In one embodiment of a distributed computing environment, a device that establishes a connection with a device that does not publish its service advertisement(s), such as a proximity-based device, may publish service advertisements received from the non-publishing device. For example, a device that establishes a connection with a proximity-based device and that has an alternate transport connection(s) may publish (or republish) service advertisements received from the proximity-based device in the alternate transport environment, thus allowing the proximity-based device service(s) to be used by other devices (through the (re)published service advertisements) which are outside the normal proximity range of the device.

The publishing device may locate a locally published service advertisement for the proximity-based device through a discovery and/or lookup service, or alternatively the service advertisement may not be published by the local service device, but instead may be sent to the publishing device by the local device upon the establishment of a connection, as described above. In one embodiment, the republished service advertisement may be made available as long as the device maintaining the advertisement is connected to or able to connect to the local device. For example, if the publishing device is disconnected from the local device (for example, moves out of proximity range of the device), the service advertisement may be made stale or removed. A lease mechanism may be provided to allow the space containing the advertisement to send lease renewal messages to the publishing device. The publishing device may verify its connection to the local device, thus allowing the space to detect when the local device is no longer available. Rules for how the service advertisements are republished may be provided by the local device or by an administrative policy for the local vicinity (e.g. proximity area) or local network.

Figure 24 illustrates an example of a device bridging proximity-based devices onto another transport mechanism to allow the services provided by the proximity-based devices to be accessed by devices outside the proximity range of the devices, according to one embodiment. A publishing device 1404 may be connected to a network 1412, such as an Ethernet LAN or the Internet, etc., and may establish and maintain proximity connections 1414 with proximity devices 1400 and 1402. Proximity connections may be wireless connections or wired LAN connections, for example. Proximity devices 1400 and 1402 may each send a service advertisement to the publishing device 1404 upon connection, or, alternatively, the publishing device may locate the service advertisements using a discovery and/or lookup service for the proximity connections. The publishing device 1404 may then make the services provided by the proximity devices available to other devices 1408 and 1410 on the network 1412 by republishing the service advertisements 1416 and 1418 in space 1406. Space 1406 may be stored on the publishing device or on other devices connected to the LAN (including devices 1408 and 1410).

Other devices on the LAN including devices 1408 and 1410 may then discover space 1406 and look up the republished service advertisements 1416 and 1418 for the proximity-based devices, establish gates to communicate to those services (device 1404 may act as a proxy or bridge) on the proximity-based devices 1400 and 1402 using the XML message passing methods described previously, and send requests and receive results to

the proximity devices. Publishing device 1404 may act as a bridge between the network 1412 and the proximity connections 1414 to the proximity-based devices.

### Leases

Leases may be used in the distributed computing environment to deal with partial failure, resource synchronization (scheduling), and to provide an orderly resource clean-up process. Leases may help the overall distributed system manage independent clients and services that may come and go. The various resources that clients obtain from services (including space services) may be leased from those services. In general, not every resource can or needs to be leased. In one embodiment, it is up to the implementation of each particular service to determine which of its resources need to be leased. In particular, resources used by a large amount of clients simultaneously may not need leasing or instead may require custom leasing protocols. This class of leasing may be left to the service provider. Custom protocols, such as those to implement transactions for example, may be built upon the base leasing scheme. In one embodiment, the base leasing model is a relative time-based model.

Services may issue leases to clients and provide operations on those leases. In one embodiment, all such lease functionality of a service is part of that service's XML schema. Thus, a client may use its gate (corresponding to the service and constructed for the service's XML schema) to perform lease operations. In one embodiment, all services that issue leases provide the following lease operations (only allowed by the owner of the lease): (i) renewing a lease (parameters specified: lease (e.g. lease ID, lease credential), new lease time requested), and (ii) canceling a lease (parameter specified: lease (e.g. lease ID, lease credential)). In one embodiment, all leases are granted for a particular amount of relative time (duration of lease) that may be negotiated. The requestor may specify a certain amount of time (e.g. in seconds), and the grantor may grant the lease for any amount up to that time. In one embodiment, a -1 value may be used to specify an indefinite lease.

In one embodiment, a service advertisement may include one or more leasing addresses. In one embodiment, the leasing addresses may be URIs. Standard leasing messages to renew and cancel service resource leases may be sent to a leasing URI. An example lease URI:

```
<leaser>service1://resource1</leaser>
```

An advertisement may also include various leasing messages as described above. Leasing messages may include messages to renew and cancel leases for resources of the service. In one embodiment, the messages may be comprised in an XML schema in the advertisement.

The leasing mechanism may provide a mechanism to detect service and client failure. Leases may also provide a mechanism to provide shared and exclusive resource access. In one embodiment, all service resources either have no lease (resource is not leased and therefore available), a shared lease (resource accessed by multiple clients), or an exclusive lease (resource is accessed by exactly one client at a time). In one embodiment, all resources begin in the no lease state. A no lease state signifies there is no current access to the underlying resource, and indicates that there is an interest in the resource remaining in existence and thus available for leasing. The leasing level may be increased from none to shared, none to exclusive, or shared to exclusive. Lease isolation levels may also be decreased from exclusive to shared, exclusive to none, and shared to none. In one embodiment, clients may voluntarily increase or decrease the lease isolation level, or may be requested by the service to do so. A response message from the service may indicate if the isolation level change was accepted.

Request-response message pairs may be employed to claim, release, and renew a lease. Each message may be tagged using a reserved XML tag to indicate that the message is a leasing message. The distributed computing environment doesn't necessarily define the complete composition of the message. In such an embodiment, service developers may append custom message content, as long as, the message is tagged as a leasing message.

In one embodiment, clients that use leased resources may be expected to: (i) claim the resource as shared or exclusive, (ii) release the resource claim (if requested or if finished with resource), and (iii) respond to renewal messages (with another claim at same or different isolation level). Renewal messages may be sent (e.g. in regular intervals) by services to detect client failure cases. The interval (at which the renewal message is sent) may be service specific. If a response to the renewal message isn't issued after a specific amount of time (e.g. based on a time noted in the service advertisement), a resource reclamation process may begin within the service, revoking the lease completely. In such an embodiment, renewal messages sent to clients should be handled in a timely fashion. Figure 25 illustrates the use of renewal messages both between a client and an instantiated service and between a service provider and a space service. Note that both cases may be considered as the use of renewal messages between a client and a service, since a service provider may be a client to a space's advertisement service.

Renewal messages may arrive in an "out of band" fashion that may be inconvenient for the client to handle. That is, the client cannot predict when a renewal message will be sent from the service. Out of band message handling may complicate the client's logic and increase its complexity. To solve this problem, an automatic lease renewal mechanism may be implemented to relieve the client of the responsibility of handling the out of band messages, and thus reduce client complexity. In the automatic lease renewal mechanism, each gate (message, method, and/or event gate) may receive renewal messages and automatically respond to them without help from the client. The default response to a renewal request is to claim the lease at its current level. Each message gate may contain a single, set-aside renewal response message that is automatically sent to the advertisement space service when the gate receives the renewal message. This "out of band" message is handled on behalf of the client, yielding a cleaner client programming model. In one embodiment, the gate may allow clients to register lease event handlers to specify different isolation levels in the response message.

Standard leasing messages may be defined in the distributed computing environment. In one embodiment, additional leasing messages may be defined by custom leasing models. In one embodiment, every service that issues leases may specify a URI where renew and cancel leasing messages may be sent. Leasing messages may include embedded credentials for authenticating the sender of the message. In one embodiment, a client may receive the credential (e.g. authentication credential) from an authentication service at service instantiation and embed the credential in messages sent to the service. In one embodiment, the authentication service may have been specified in the service advertisement for the service. The service may then authenticate the credential when received in a message from the client. In one embodiment, the service may send the credential when first received to the same authentication service used by the client to generate the credential. Thus, the issuing and embedding of credentials in leasing messages may be used to provide a secure leasing environment. For example, the embedding of a credential in a cancel lease message may effectively prohibit anyone but the

authorized, credentialed client (and the service issuing the lease) from canceling the lease. See the "Authentication and Security" section for more detail.

Figure 44 is a flow diagram illustrating a mechanism for leasing resources. In step 2000, a client may request a lease on a resource provided by a service. In one embodiment, leases may be time-based, i.e. granted for a period to the client. In another embodiment, leases may be non-time-based leases that are maintained until cancelled by the client or the service. In one embodiment, the service may be a space service, and the resource may be a service advertisement for another service and leased to the client by the space service. In one embodiment, the service may be a space service, the client may itself be a service, and the resource may be the publishing of a service advertisement by the space service on behalf of the client/service. In one embodiment, the client may send a request message to the service that specified the resource and requests the lease on the resource. In one embodiment, the message may specify a requested lease period. In one embodiment, a client message gate may send the lease request message to the service on behalf of the client. In one embodiment, the lease request message may be an XML message.

In step 2002, the service may grant the lease on the resource to the client. In one embodiment, the service may receive a lease request message from the client. The service may then grant the lease on the resource. In one embodiment, the lease request message may include a requested lease period. In one embodiment, the service may grant the lease for a granted lease period less than or equal to the requested lease period. In one embodiment, the requested lease period may be for an indefinite lease (i.e. the period does not expire). In this embodiment, the client or service must cancel the lease, as the lease itself does not expire.

The service advertisement provided to the client may be used in establishing an initial lease of resource(s) provided by the service and requested by the client during access of the service. In one embodiment, the lease on the resource may be granted at service instantiation time. In this embodiment, the client may not send a lease request message to the service requesting the lease. In this embodiment, the service may grant an initial lease on the resource or resources to the client when instantiated from the service advertisement. For example, a space service may, in response to a request message from a client, instantiate a service from a service advertisement on the space service. The service may grant the client leases on one or more resources provided by the service when instantiated without requiring the client to explicitly send a message requesting the leases.

In step 2004, the client may request renewal of the lease. In one embodiment, the service may send a lease renewal request message to the client. In one embodiment, the lease renewal request message may be sent to the client prior to expiration of a previously granted lease period. The client may respond to the message with a lease renewal response message to the service requesting renewal of the lease. In one embodiment using time-based leasing, the lease renewal response message may include a requested lease period. In another embodiment using non-time-based leasing, the lease renewal response message may request that the lease be continued. In one embodiment, the client may return a lease renewal response message that instructs the service that the lease is no longer required. In one embodiment, the client may not send a lease renewal response message, and the service might assume, when no response message is received by the service, that the client no longer requires the lease. For example, the client may have been disconnected from the network. This provides the service with a mechanism for detecting non-used leases and for garbage collecting resources including leasing resources.

In one embodiment, the service may not send a lease renewal request message to the client. In this embodiment, the client may instead monitor a granted lease period and send a lease renewal message to the service prior to the granted lease period expiring. The lease renewal message may specify the resource that is being leased and a requested new lease period for the lease of the resource. In one embodiment, the requested lease period may be for an indefinite lease (i.e. the period does not expire). If the client no longer desires the lease, the client may not send the renewal message, and thus may abandon the lease.

In one embodiment, a client message gate may handle lease renewal on behalf of the client process, thus freeing the client process from responsibility of handling lease maintenance. In one embodiment, the client message gate may automatically respond to lease renewal request messages send from the service. In one embodiment, a default lease renewal response message may be compiled into the gate and automatically sent to the service upon the gate receiving the lease renewal request message. In another embodiment, the service may not send lease renewal request messages. In this embodiment, the client gate may automatically send lease renewal messages. In one embodiment, the automatic sending may be performed periodically. In one embodiment, the client message gate may monitor a currently granted lease period and may send a lease renewal message prior to the currently granted lease period expiring.

In one embodiment, a lease may be at one of several access levels including exclusive access and shared access. Exclusive access gives the client exclusive rights to the resource, prohibiting other clients from accessing the resource for the duration of the lease. Shared access gives other clients the right to contemporarily lease the same resource as the client, that is, to obtain a lease to the resource that overlaps the period of the lease held by the client. In one embodiment, the client may hold a lease at one access level, and may send a lease renewal message requesting the lease at another access level.

In step 2006, the service, subsequent to receiving a lease renewal message from the client, the service may grant renewal of the lease of the resource to the client. The lease renewal message may have been sent in response to a lease renewal request message sent from the service to the client or may have been sent automatically by the client prior to a previously granted lease period expiring. In one embodiment, the lease may be granted for a granted lease period. In one embodiment, the lease renewal message may have requested a lease renewal period. In one embodiment, the granted lease period may be less than or equal to the requested lease period. In one embodiment, the service may deny the lease renewal request by the client. For example, the client may have exceeded a maximum cumulative lease time, or another client may require exclusive lease access to the resource. In one embodiment, the service may grant the lease for less than the requested lease period. In one embodiment, the service may send a message to the client to inform the client if the lease has been renewed. In one embodiment, the message may include the granted lease period.

In step 2008, the client may send a message to the service requesting cancellation of the lease. The message may specify the resource for which the client has a lease to be cancelled. In step 2010, the service may cancel the lease. The service may cancel the lease in response to receiving a cancel lease request message as described in step 2008. In one embodiment, the service may also cancel the lease if a granted lease period expires without receiving a lease renewal message from the client. The service may also cancel the lease for a variety of other reasons. For example, another client may request exclusive access to the resource, or the resource may



become unavailable. In one embodiment, the service may send a message to the client to inform the client if the lease has been cancelled.

In one embodiment, a security credential, such as an authentication credential described below, may be included in lease messages sent between the client and service as described in Figure 44. For example, the client may embed the security credential in lease renewal and lease cancel request messages sent to the service. The service, upon receiving a message, may examine the credential to verify it is from the leaseholder, and thus to verify the authenticity of the message. This provides security in the leasing mechanism by preventing entities not having the proper credentials from modifying the client's current lease(s) with the service.

In one embodiment, the lease messages sent between the client and the service may all be in a data representation language. In one embodiment, the data representation language may be eXtensible Markup Language (XML). In one embodiment, all messages may be sent and received by a service message gate and a client message gate. In one embodiment, the lease messages may be described in an XML message schema provided to the client and used to construct the client message gate. In one embodiment, the XML message schema may have been acquired by the client in a service advertisement, for example, retrieved from a space service.

The leasing mechanism may also provide a mechanism to detect stale advertisements. When a service publishes its advertisement in a space, that service obtains a lease on this publishing of its advertisement. Each advertisement may contain a time by which the service promises to renew the advertisement. In one embodiment, all time-out values are specified in seconds. If the service continues to renew its lease, the space is provided some assurance that the service advertised is still being offered. The renewal time may be counted down towards zero by the space service. If the service does not renew its lease, the service may have failed, or it may no longer wish to, or be able to provide the service. When the lease is not renewed, the space service marks the service advertisement stale, so it does not make it available to clients. Services renew advertisements by sending a renewal message to the space. The space service receives these messages and resets the advertisement renewal time back to its initial value.

In one embodiment, stale advertisements are not automatically deleted. Depending upon the policies of the space, it may choose to delete stale service advertisements that have expired for a reasonably long period of time. The deletion policy may be set by the space service. The space service may search for stale advertisements and either delete them or bring them to the attention of an administrator, for example.

A space service may use leases to manage the resources its facilities provide to clients (including other services) of the space. For example, when a client desires to use a service, the space service may request a lease for the client as part of service instantiation. Service instantiation may be performed to allow a client to run a service. To instantiate a service, a client may first select one of the service advertisements published in a space. The client may use the various facilities provided by the space to look up advertisements in the space. Then the client may request the space to instantiate the service. The lease acquired during service instantiation is on use of the service advertisement (not the same as the lease on publishing of the service advertisement). It should be noted that the space service may allow multiple clients to have a lease on use of a service advertisement if the

advertisement has an indication it is shared. Otherwise, the space service only allows one client at a time to have a lease on the service advertisement (exclusive).

Another example of how a space service may use leases to manage the resources its facilities provide to clients is when a client of the space registers to be notified when XML documents (e.g. service advertisements) are added or removed from a space. The registering client of the space may obtain a lease on this subscription to notifications. This lease enables the space service to know whether to continue sending notifications. Such a lease may not be necessary when a client has established an active session with the space. Also, note that when a client of a space (could be a service) establishes a session with the space, the client may obtain a lease on the session. This allows the space to manage any resources associated with the session.

In another embodiment, the distributed computing environment may employ a leasing mechanism that is not time-based. The lease may be generated when an object is claimed for use. Instead of a time-based mechanism, the claim method may accept a callback that notifies the current leaseholder that some other party wishes access the same object (e.g. service). Thus, as an alternative embodiment to time-based leases, instead clients may make claims on space objects (e.g. services). When another client desires a lease that is incompatible with the current leaseholder's lease, the service may send a "callback message" to the client. Upon receiving the callback message, the client (i.e. client gate) may invoke a callback method to decide on a response to the callback message (keep the lease, cancel the lease, change the access level to shared, etc.). Once a response has been determined, the client gate sends a response message to the service. This distributed mechanism for managing leases may be implemented using the XML message-passing layer.

For a non-time-based lease embodiment, the distributed computing environment may provide lease support for several levels (or kinds) of access that allow a distributed algorithm to determine lease compatibility. Those levels may include: (i) keep the object in the space (keepInSpace), (ii) read the object in the space (readShared), and (iii) read exclusively the object in the space (readExclusive).

#### Authentication and Security

The distributed computing environment provides for spontaneous and heterogeneous distributed systems based upon an asynchronous message passing model, where data and/or objects may be represented in a representation language such as XML. In the distributed computing environment, clients may connect to services throughout the Internet, for example. The distributed computing environment may enable large numbers of network devices to work together in a reliable, dynamic, and secure fashion. The distributed computing environment may define a protocol that substantially enables interoperability between compliant software components (clients and services).

In the context of the distributed computing environment, a device may be a networking transport addressable unit. Clients and services may be implemented as Universal Resource Identifier (URI) addressable instances of software or firmware that run on devices.

Internet space is inhabited by many points of content. A URI is a method used to identify any of those points of content, whether it be a page of text, a video or sound clip, an image, software, firmware or other Internet content. The most common form of URI is the Web page address, which is a particular form or subset of URI called a Uniform Resource Locator (URL). A URI typically describes the mechanism used to access the resource,

the specific computer that the resource is housed in and the specific name of the resource (typically a file name) on the computer.

Clients and services (both may be implemented on devices as software and/or firmware) may be connected over the Internet, a corporate intranet, a dynamic proximity network, within a single computer, or by other network connection models. The size and complexity of the devices supporting clients and services may range, for example, from a simple light switch to a complex, highly available server. Example devices include, but are not limited to: PDAs; cellular phones; notebook, laptop, and more powerful PCs; and more powerful computer systems, up to and including supercomputers. In some embodiments, the distance, latency, and implementation of clients and services may be abstracted, with a common discovery and communication methodology, creating a “black box” effect. This definition approach allows software implementation issues to be dealt with by the underlying platform, yielding a loosely coupled system that may be scaled to Internet proportions.

The distributed computing environment may provide an Internet-centric programming model including WEB and XML content representation, dynamic device discovery, and secure device communication that is accessible from a wide range of network devices. The distributed computing environment may include a network-programming model abstracted above the CPU level. The programming model may include the following properties:

- URI addresses
- Strongly typed data called content (addressed with URIs)
- Substantially unlimited amount of persistent content storage (e.g. stores), (containing XML and non-XML content, such as that identified by MIME types)
- Substantially unlimited amount of transient content memory called spaces (containing XML content)
- Descriptive XML metadata (data about data) content advertisements that may be stored in a space to notify interested clients.
- A substantially unlimited number of instructions (embodied as messages)
- Secure message endpoints (gates) addressed by URIs
- Data flow support (event messages) to coordinate work flow between distributed software programs

Services and clients may run as programs within the distributed computing environment. Services may advertise their capabilities to clients wishing to use the service. Clients may or may not reside within the same network device, and that device's code execution environment may or may not support the Java platform.

Using URIs to address content and message endpoints gives the distributed computing environment a powerful addressing scheme. The address may specify the location of the content or endpoint, and may specify the route (or transport protocol) to be used. Items addressed using URIs also may have an associated security credential. The security credential may be used to control what clients are allowed access to the item, as well as which operations authorized clients are allowed to perform on that item.

The high degree of access provided by the distributed computing environment may be controlled by appropriate authentication and security systems and methods. Authentication and security in the distributed computing environment may include, but are not limited to: verifying the typing correctness of XML content in a message; securely identifying the sender to the receiver; a mechanism to check the integrity of messages sent from a client to a service and vice versa; and a mechanism of describing a service's set of accepted messages to a client

and enforcing the message requirements on messages received at the service. The above listed security and authorization features may be leveraged in a single, atomic unit of code and data. The atomic unit of code and data may be dynamically created. In one embodiment, once created, the atomic unit of code and data may represent a message endpoint (gate), and may not be altered as to the security and authorization policies implemented during creation.

A gate may represent the authority to use some or all of a service's capabilities. Each capability may be expressed in terms of a message that may be sent to a service. Gates may also be used for failure case detection when a client leases resources.

Authentication and security may also include a mechanism for verifying that a client attempting to use a service is authorized to use the service; that the space from which the client receives the service advertisement from is authorized to provide the service advertisement; and/or that the service advertisement itself is authorized.

Message passing may be implemented in a messaging layer as the means of communicating requests from clients to services and of the services responding with results to the clients. The messaging layer of the distributed computing environment may substantially guarantee that valid XML messages are sent, and may provide mechanisms enabling a language-independent security model. In the messaging layer, a sending message endpoint may be linked to a receiving message endpoint. The two associated message endpoints may provide a secure, atomic, bi-directional message channel suitable for request-response message passing between a client and a service.

In embodiments of a distributed computing environment, an advertisement may be published in a space for a service. An advertisement may be an XML document that includes the XML schema and URI of the service. The service may also include a service ID token or credential in the advertisement, and may specify in the advertisement an authentication service to be used by both the client and the service. A client may then locate the service advertisement on the space, and use the advertisement to instantiate a message gate on the client. The client may use the authentication service specified in the advertisement to obtain an authentication credential for sending in messages to the client. In one embodiment, the client may pass the service ID token or credential from the service advertisement to the authentication service, and the authentication service may then use the service token or credential to generate the authentication credential for the client. In one embodiment, the client may include a gate factory that receives the necessary information to create the message gate, and the gate factory may construct the message gate and communicate with the authentication service to obtain the authentication credential for the client. A corresponding service message gate may be instantiated at the service.

The client, at some point, sends a first message to the service. In one embodiment, the client message gate may embed the client's authentication credential constructed by the authentication service in the message. When the service receives the message, it may use the same authentication service to verify the authentication credential received in the message. By sharing the same authentication service, any of a variety of authentication protocols may be employed, with the details of generating the authentication credentials separated from the client and the service. Thus, a client may use different authentication credential protocols with different services.

In one embodiment, the authentication service may determine the capabilities of the client (e.g. what the client is allowed to do on the service) upon first receiving the client authentication credential from the service. The capabilities of the client may be bound to the client's identity. Then, the client's message gate may embed the

authentication credential in every message sent from the client to the service. The messages may be received by the service message gate and then checked by the authentication service to ensure that the message is from the client and that the message request is within the capabilities of the client. In another embodiment, the service message gate may handle capability determination and message checking for capabilities without using the authentication service.

The client and service message gates may work together to provide a secure and reliable message channel. The gates may serve as secure message endpoints that allow the client to run the service by sending and receiving secured, authorized XML messages to and from the service.

Operations in the distributed computing environment may be embodied as XML messages sent between clients and services. The protocol used to connect clients with services, and to address content in spaces and stores, may be defined by the messages that can be sent between the clients and services. The use of messages to define a protocol may enable many different kinds of devices to participate in the protocol. Each device may be free to implement the protocol in a manner best suited to its abilities and role.

A service's capabilities may be expressed in terms of the messages the service accepts. A service's message set may be defined using an XML schema. An XML message schema may define each message format using XML typed tags. The tag usage rules may also be defined in the schema. The message schema may be a component of an XML advertisement along with the service's message endpoint (gate) used to receive messages. Extensions (more capabilities) may be added to services by adding messages to the XML message schema.

In the distributed computing environment, authorized clients may be able to use all of a service's capabilities, or may be limited to using a subset of the service's capabilities. In one embodiment, once a set of capabilities has been given to a client, the client may not change that set without proper authorization. This model of capability definition may allow for services levels that run from a base set of capabilities to an extended set.

Service instantiation may be performed to allow a client to run a service. To instantiate a service, a client may first select one of the service advertisements published in a space. The client may use the various facilities provided by the space to look up advertisements in the space. Then the client may request the space to instantiate the service. Service instantiation may include, but is not limited to, the following steps:

1. Client requests space service to instantiate a service.
2. Space service verifies client is allowed to instantiate the service.
3. Space service obtains a lease on the service advertisement for the client with the lease request time specified by the client. Alternatively, the service advertisement may be provided to the client without using the leasing mechanism.
4. Space service sends a message to the client that includes the lease allocated in steps 3, and the service advertisement of the service.
5. Client runs the authentication service specified in the service advertisement, and obtains an authentication credential.
6. Client constructs a client message gate for communicating with the service.

In order to provide trust between clients and services in the distributed computing environment, a series of dynamically generated numbers (keys, or tokens) may be used as security or authentication credentials for

clients. One or more credentials may be used to verify the right of a client to use a service and to verify messages between the client and the service. Each client and service may have a unique credential.

The type of authentication credential needed to use a service may be returned to the client conducting a service search. In one embodiment, an authentication credential is an opaque object that must be presented each time a client uses a service. In one embodiment, the authentication credential may be presented by a message gate on behalf of a client in every message sent to a service. No matter what kind of authentication credential is required by a service, by using an authentication service external to the client and the service, the client and the service may not need to be aware of the authentication credential structure or of the authentication process.

An authentication credential may also include a transport-specific ticket in addition to the service ticket. When running a service, depending upon the networking transport specified in the service advertisement, the transport may provide a secure connection. In some cases, if the data link layer is already secure, it may not be necessary to use a secure transport over the already secure data link layer.

The concept of an authentication credential is abstract enough to allow various levels of security based upon credential implementation. Levels of security may include, but are not limited to:

1. None (no message security - credential is empty or no credential)

Messages with empty credentials or no credentials may be sufficient when security is enforced by the physical connectivity properties of the transport. For instance, a smart light switch connected to just one light switch controller is secure because the switches are wired in a secure manner.

2. Signed messages (digital signatures)

Signed messages may include a digital signature that enables the service (receiving the message) to verify the origin (client) of the message.

3. Encrypted messages (transport may handle this)

Encrypted messages add another level of security by scrambling the message contents so that another credential is required to unscramble it.

4. Capability messages (service functionality and user aware)

This level of security may provide for security capabilities on a user-by-user basis (e.g. what the user is allowed to do), and may allow for fine-grained access control to services and individual service functions.

Multiple levels of security zones may be used, due to the heavyweight implementation necessary to enforce the higher levels of security (capabilities & encryption). If the message transport supports (or helps support) these security levels, the support may be leveraged to provide security level bridge services that bridge one level of security to another.

As mentioned above, services without any security model may accept empty authentication credentials. For services that do not restrict access, a gate may be built without an authentication credential or with an "empty" authentication credential. The gates for such services may not send an authentication credential with each message, or may send an empty credential. The authentication service is one example of a service that may not restrict access. Other services may require a user and password pair.

Authenticating Service Access using Credentials

In some embodiments, a mechanism for verifying that a client attempting to run a service is an authorized client, for verifying that the service advertisement received by the client is an authorized service advertisement, and/or for verifying that the space from which the client received the service advertisement is authorized may be based upon a public key/private key asymmetric cryptographic mechanism. In this mechanism, an authorized  
5 sending entity may embed a public key in a message and encrypt the message including the public key with its private key. An entity receiving the encrypted message may decrypt the message using the public key and find the same public key embedded in the decrypted message, and thus verify that the message is from the authorized entity, since only that entity has the private key necessary to encrypt the message. Thus, an entity may issue a credential that is substantially unforgeable, and that other entities may decrypt (with the appropriate public key) to  
10 verify messages sent by the entity.

In one embodiment, messages in the distributed computing environment may include several layers of encrypted public keys for authorizing the entities in the client-service communications model. In one embodiment, a service may build a credential C1 including its public key X1. The service may then encrypt the credential using its private key Y1. The service may include the encrypted credential C1 in a space as part of its service  
15 advertisement. The space then may build a new credential C2 including credential C1 and the space's public key X2. The space may then encrypt the credential C2 with its private key Y2. When a client requests the service from the space, the space sends the service advertisement and credential C2 to the client. When the client constructs a gate, it has the gate send messages to the service including another credential C3 which includes encrypted credential C2 and the client's public key X3. C3 may be encrypted using the client's private key Y3  
20 prior to sending. The client's public key X3 and the space's public key X2 may also be sent with the messages. In one embodiment, the space's public key X2 may be included in C3, and thus encrypted in C3. In this embodiment, the client's public key X3 may be sent unencrypted in the messages. In another embodiment, the client's public key X3 and the space's public key X2 may be sent unencrypted in the messages.

After the gates are created, in one embodiment, the client may send a message including encrypted  
25 credential C3 and public key X3 to the service. In one embodiment, the space's public key X2 may be included in C3. In another embodiment, public key X2 may be included (unencrypted) in the message external to C3. When the service receives the message, it may decrypt credential C3 using the received client's public key X3 and check the public key X3 embedded in the decrypted credential C3 against the received public key X3 used to decrypt the message, thus verifying the message is from an authorized client. The service may then decrypt credential C2  
30 (extracted from decrypted credential C3) with the space's public key X2, and check the public key X2 embedded in the decrypted credential C2 against the space's public key X2, thus verifying that the space credential C2 came from an authorized space. In one embodiment, the space's public key X2 may have been included in credential C3. In another embodiment, the space's public key X2 may have been included in the message, external to C3. In yet another embodiment, the service may obtain the space's public key X2 elsewhere, for example, from the space  
35 itself. Finally, the service may decrypt credential C1 (extracted from decrypted credential C2) with the service's public key X1, and check the decrypted credential to verify that the credential was created by the service (the credential should include the public key of the service).

Various key generation algorithms may be used in the distributed computing environment. The composition of keys may be hidden from both clients and services; thus, the client and service may not care what key generation algorithm is used.

A Kerberos ticket is one example of a security credential that may be used in the distributed computing environment. Kerberos is a secure method for authenticating a request for a service in a computer network. Kerberos lets a user request an encrypted "ticket" from an authentication process that can then be used to request a particular service. The user's password does not have to pass through the network.

Mechanisms may be provided by the distributed computing environment to substantially guarantee that messages sent between clients and services are not compromised. In one embodiment, a sender may embed a token containing information that may be used by the receiver to verify that the message has not been altered. There are several methods for generating the information to embed in the message. In one embodiment, a hash of the message may be computed and sent with the message. Hashing may include the transformation of a string of characters into a usually shorter fixed-length value or key that represents the original string. Upon receiving the message, the receiver may recompute the hash and check it against the sent hash. If the message has been altered, it is highly unlikely that the same hash will be generated. The sender may encrypt the hash and send the corresponding public key in the encrypted message to substantially ensure that the hash is not compromised.

In other embodiments, an error detection scheme such as cyclic redundancy checking may be used. Cyclic redundancy checking is a method of checking for errors in data that is transmitted on a communications link. In an embodiment using cyclic redundancy checking, the sender applies an n-bit polynomial to the message and appends the resulting cyclic redundancy code (CRC) to the message. The receiver applies the same polynomial (which may also be passed in the message) to the message and compares its result with the result appended by the sender. If they agree, the message has been received successfully. If not, the sender may be notified to resend the message.

Gate factories may also play a role in security, since a gate factory may be "trusted" code. Using a trusted gate factory to generate gates may help to ensure that gates are trusted code, and that the code is correct with respect to the service advertisement. Clients may be required to present a client ID token or credential to the gate factory as a means of authentication. Services may present a service ID token or credential to clients (e.g. through an advertisement) when a client wishes to create a gate. As discussed herein, a client and service token pair may be used to create a third credential that may be used to allow the client to send messages to the service. This third credential may be referred to as an authentication credential. An authentication credential may be created by an authentication service during the authentication process. In one embodiment, the service may use any authentication policy at its disposal. In one embodiment, the authentication service administers the authentication policy on behalf of the service, and thus the service does not have to be aware of the particular authentication policy being used.

The client may construct its gate using an authentication credential that the client receives by running an authentication service specified in the service advertisement. This may allow the constructed gate to send the authentication credential with each message to the service. When the service receives the first authentication credential in a first message from the client, the service may use the authentication service specified in the service



advertisement to authenticate the client, and thus may establish a binding of the authentication credential to the identity of the client.

As previously discussed, some results produced by a service may be advertised in a space and ultimately accessed using a results gate. The results gate may or may not contain the same security credential as the input gate used to generate the results. Because input to a service may be asynchronous from its output (the results), the results may have a different set of access rights associated with it. For example, a payroll service may allow a different set of clients to initiate payroll than to read the payroll service's results (paychecks). Thus, a client may have to go through a separate authentication process to obtain access rights to the results, which may include receiving an authentication credential for the results from an authentication service specified in an advertisement for the results.

Message gates may offload most security checks from services. Services may focus on providing capability and authenticating clients. A principle of least privilege may be supported by giving clients access to only those capabilities that are requested (or assigned).

Security checks may occur when a gate is created and/or when a gate is used (when messages are sent and/or received). When a client requests access to an advertised item (service), the process of gate creation may begin. During this process, the client gate factory may work with the service to mutually authenticate each other. The checks performed at gate creation time may be extensive, and may minimize the number of checks performed during gate usage. After the service has authenticated the client, the service may determine specific capabilities for the client (e.g. what the client is allowed to do on the service), and associate the capabilities with the client's authentication credential. These specific capabilities may specify what operations the client is allowed to perform on the service. Since the gates may ensure that every message contains the authentication credential, the service can then check each request when it is received against the capabilities of the authenticated client.

Gate creation checks may ensure that a client has permission to use some or all of the service capabilities designated by the XML message schema. In one embodiment, these checks may be implemented using access control lists (ACLs) in conjunction with an authentication service such as Kerberos. A challenge-response sequence (such as a password) may also be used to authenticate a client. In some embodiments, a hardware-based physical identification method may be used to authenticate the client. For example, the user may supply a physical identification such as a smart card for identification and authorization. Other mechanisms for authentication may be used in other embodiments.

In one embodiment, whatever means is used to authenticate the client, the authentication may be invisible to both the client and service, the gate factory may be aware of which authentication service to use, and the authentication service handles the authentication mechanism and policies. Gate factories may be product and environment dependent, or may even be controlled by a configuration management system. In one embodiment, the degree and method of client isolation may be platform dependent, but is known to the gate factory. In some embodiments, a hardware-based physical identification method may be used to authenticate the client. For example, the user may supply a physical identification such as a smart card for identification and authorization. Other mechanisms for authentication may be used in other embodiments.

Message gates in the distributed computing environment are typically associated with a single client. The gate factory may determine the means of association. The checks performed at message send time may ensure that

the proper client is using the gate. In one embodiment, gates may be passed in messages, and may be cloned if a new client wishes to use the gate. The cloning process may perform a new set of creation checks.

Once a client of a space (the client may be another service) finds the advertisement of a space service, the client of the space may run the space service, as it would any other service. Running a space service may involve using an authentication mechanism. Running a space service may include, but is not limited to:

1. The client of the space may first run an authentication service that may be specified in the service advertisement of the space service to obtain an authentication credential.
2. The client of the space may use the authentication credential, the XML schema of the space (from space's service advertisement), and the URI of the space (from space's service advertisement) to construct a gate for the space. In one embodiment, the client may pass the information to a gate factory to construct the gate.
3. The client of the space may run the space service by using the gate to send messages to the service.
4. When the space service receives the first message from the client, with the authentication credential embedded, the space service may use the same authentication service used by the client to obtain the authentication credential to authenticate the client, thus establishing the client's identity.
5. The space service may then determine the client's capabilities (e.g. what the client is allowed to do on the space service) and bind the capabilities to the authentication credential.

As discussed in the Spaces section, a space's facilities may include an interface for spawning an empty space with substantially the same functionality (same XML schema) as the space from which it is spawned. The spawning facility may be useful, among other things, for dynamically generating spaces for results. When a requestor has spawned a space, only the requestor may be allowed to access the spawned space. For example, the spawned space may be for storing results from a service that the client needs to keep secured. This security may be ensured by:

- Creating an initial root authentication credential, and initializing the authentication service of the spawned space, so that the authentication service only authenticates the root authentication credential, and so that it returns no other authentication credentials (no other clients of the spawned space allowed initially).
- Initializing the security policies of the spawned space so that the root identity associated with the root authentication credential has access to all facilities of the space, including the security administration facilities.
- Returning the root authentication credential and the service advertisement of the spawned space to the requestor of the spawned space.

The requestor may build a gate to access the spawned space, since it is returned the authentication credential and the service advertisement of the spawned space. In one embodiment, only the requestor and clients or services that the requestor passes the authentication credential and the spawned space's service advertisement may access the spawned space. Such limiting of access to the spawned space may be useful when a client and

service are using that spawned space to store results, for example, if the client and service desire to keep the results private.

After running a service, the client may change the authentication policies of the spawned space using a security administration space facility, and other clients or services may then access the spawned space. In addition, the spawned space's service advertisement may be made available to other clients of the spawned space (the other clients may be services) using the discovery protocol or other means.

The message transport layer in a distributed computing environment may include mechanisms for protecting the security and integrity of communications among clients and services during transport. This security may be referred to as "wire security" or "transport security" to distinguish it from the authentication security implemented by the messaging system including gates. Encryption of messages may be provided at the message transport layer of the distributed computing environment. Services that request an encrypted transport may do so by tagging the XML advertisement. The gate factory may then create a gate (or gates) that uses a secure message transport such as those provided by Bluetooth and HTTPS.

HTTPS (Secure Hypertext Transfer Protocol) is a Web protocol that encrypts and decrypts user page requests as well as the pages that are returned by the Web server. HTTPS may use a multi-bit key size (may vary from 40 to 128- bit or more) for a stream encryption algorithm (e.g. RC4), to provide an adequate degree of encryption for commercial exchange. HTTPS may be used as a transport in the distributed computing environment.

Bluetooth is an emerging peer-to-peer wireless communications standard. The Bluetooth key generation algorithms may be used in the distributed computing environment. Bluetooth may support encryption keys. Encryption keys are transport dependent, while client, service, and combination keys may be transport independent.

Figure 26a - An authentication service providing an authentication credential to a client

Figure 26a is a flow diagram illustrating an authentication service providing an authentication credential to a client according to one embodiment. A client in the distributed computing environment may desire a service to perform one or more functions on behalf of the client. In one embodiment, an authentication service may be provided for use by the client and the service when setting up a secure messaging channel. An authentication service may perform functions for the client and/or service including authenticating the client and/or service and negotiating the desired level of security and the set of messages that may be passed between the client and service. The authentication service may be a process that is executing within the distributed computing environment. The authentication service may be executing on the same device as the service and/or the client, or alternatively the authentication service may be executing on a separate device such as an authentication server. In one embodiment, the authentication service may be an Internet-based service. The authentication service may have its own address, for example, a Universal Resource Identifier (URI), through which the client and/or service may communicate with the authentication service. In one embodiment, the address of the authentication service may be provided to the client in the service advertisement for the service. The client and service sharing an authentication service may help insure that a secure messaging channel may be established between the client and the service, as any of several security and authentication protocols may be used in the messaging channel.

In one embodiment, a client may present a client identification token or credential to an authentication service. The client token or credential may be sufficiently unforgeable to be used as proof of the client's identity. The authentication service may then check the client identification token or credential, and issue to the client an authentication credential that only the authentication service can create. The authentication credential that is returned to the client is then sent in every message by the client to the service. In one embodiment, the client message gate is created by a gate factory, which includes the authentication credential in the message gate, and thus the message gate includes the authentication credential in every message that it sends to the service on behalf of the client. When receiving a message, the service may then check the authentication credential. Since only the authentication service can create the authentication credential, the service knows that the client did not forge the authentication credential. In one embodiment, the service may pass the authentication credential to the same authentication service used by the client to ensure the authentication credential is valid, to verify that the client is an authorized client, and to find out the identity of the client.

All services, including space services and authentication services, may authenticate their clients. Once a service authenticates a client, the client may access the service. For example, in the case of a space service, a client may then obtain XML advertisements from the space.

In one embodiment, a service may have a prearranged credential that all clients of the service are to use. In this embodiment, the authentication may provide the prearranged credential to a requesting client. Any client presenting the prearranged credential to the service may be approved by the service.

In step 1000, the client may request an authentication credential from the authentication service. In one embodiment, the client may search for and locate a service advertisement for the desired service. In one embodiment, the service advertisement may include an advertisement for the authentication service to be used to obtain an authentication credential to be used in accessing the service. In one embodiment, the service advertisement may include an address such as a URI for the authentication service. In one embodiment, the client may send information to the authentication service requesting the authentication credential. In one embodiment, the client may send information to a gate creation process, for example, a gate factory, and the gate creation process may access the authentication service to obtain the authentication credential.

In step 1002, the authentication service may generate an authentication credential for the client. The authentication credential may be a data element or data structure that may be embedded in messages in a messaging system and that may allow receivers of the messages to authenticate the sender of the message, to verify the message is from an authorized sender, and to verify that the message is a message the sender is allowed to send to the receiver. In one embodiment of a distributed computing environment, an authentication credential may be unique to the messaging channel set up between a particular client and a particular service. Step 1002 is further illustrated and described in Figure 26b. In step 1004 of Figure 26a, the authentication service may return the authentication credential to the client. In one embodiment, the authentication credential may be returned directly to the client. In one embodiment, the authentication credential may be returned to a gate creation process, for example, a gate factory, which may then use the authentication credential in generating a gate.

Figure 26b - An authentication service generating an authentication credential

Figure 26b is a flow diagram expanding on step 1002 of Figure 26a and illustrating an authentication service generating an authentication credential according to one embodiment. In step 1002a, in one embodiment, the authentication service may obtain a client token and a service token. In another embodiment, the authentication service may obtain only a client token. In one embodiment, the client token may be a unique identifier for the client in the distributed computing environment. In one embodiment, the service token may be a unique identifier for the service in the distributed computing environment. For example, the public keys from a public/private key encryption mechanism may be used as unique identifiers for the client and the service. In one embodiment, the client may receive the service token in the service advertisement, and the client may provide the client token and the service token to the authentication service. In another embodiment, the client may provide the client token and the service advertisement URI to the authentication service, and the authentication service may retrieve the service token from the service advertisement.

In step 1002b, the authentication service may verify the client and/or the service. In one embodiment, the authentication service may use the client token and the service token obtained in step 1002a to verify the client and/or service. In another embodiment, only a client token was obtained in step 1002a, and thus only the client token is used to verify the client in step 1002b. In one embodiment, the client may have previously registered its client token with the authentication service, and the authentication service may compare the received client token to the registered client token to verify the client as a valid client. In one embodiment, the client may access the authentication service using a challenge/response mechanism such as a logon account with password and thus may be verified as a valid client. In one embodiment, the service may have previously registered with the authentication service, and may have provided its service token to the authentication service. The authentication service may then verify that the client is attempting to access a valid service by comparing the received service token to the previously registered service token. Other types of client and service authentication may also be used. For example, the client may provide a digital signature or digital certificate that the authentication service may use to authenticate the client and/or to authenticate the service the client is trying to access.

In step 1002c, the authentication service may generate an authentication credential. In one embodiment, the authentication credential may include an authentication token that only the authentication service can create. In one embodiment, the authentication service may use the client token and the service token in generating the authentication credential. In another embodiment, the authentication service may use just the client token to generate the authentication credential. In yet another embodiment, the authentication service may not use an obtained token in the generation of the authentication credential, but may instead use an authentication credential generation algorithm to generate a substantially unforgeable authentication credential. In one embodiment, the authentication service may combine the service token and client token to create a unique authentication credential. For example, the service token and client token may be 64-bit values, and the two tokens may be combined to generate a 128-bit authentication credential. Other embodiments may use other methods to generate an authentication credential.

#### Figure 41 - Creating a gate

Figure 41 is a flow diagram illustrating the creation of a gate for a client according to one embodiment. In one embodiment, a gate factory may be trusted code on the client for generating gates based on XML service

descriptions. In another embodiment, the gate factory may reside on a separate device and may be used by the client to generate gates. For example, a gate factory service may be accessible by the client to generate gates. The use of the gate factory may ensure that generated gates are trusted code, and that the code is correct with respect to the service advertisement.

5 Security checks performed at gate creation time may be extensive, and thus may minimize the number of security checks that need to be performed during gate usage. Security checks during gate creation may help ensure that a client has permission to use the set of service capabilities designated in the message schema retrieved from the service advertisement. In one embodiment, the security checks may be implemented using Access Control Lists (ACLs) in conjunction with an authentication service. In one embodiment, a challenge/response sequence  
10 (such as a logon and password account) may be used to authenticate a client. In one embodiment, the client authentication and gate creation security checks may be hidden from the client and service, the gate factory may only be aware of the authentication service to be used, and the authentication service may be aware of the authentication mechanism and policies.

In step 1010, the gate factory may obtain an authentication credential for the client to use in  
15 communicating with a service. In one embodiment, the client may have previously obtained the authentication credential from an authentication service and may then provide the authentication credential to the gate factory. In another embodiment, the gate factory may obtain the authentication credential from the authentication service.

In one embodiment, the gate factory may also obtain a message schema for the service. In one embodiment, the gate factory may obtain the message schema from the client. In another embodiment, the gate  
20 factory may receive the message schema from a service advertisement. For example, the client may supply a URI for the service advertisement to the gate factory, and the gate factory may connect to the service advertisement using the URI to obtain the message schema. The message schema may describe the set of messages that may be sent to or received from the service. For example, messages may be described that may be sent from a client to a service to invoke the service or to invoke aspects of the service. Messages may also be described that may be sent  
25 from the service to the client, such as response messages and event notification messages. In one embodiment, the messages may be XML messages, and the message schema may be an XML message schema.

In step 1012, the gate factory may generate a client message gate. In one embodiment, the gate factory may embed the authentication credential as data in the generated message gate so that the message gate code may access the authentication credential. In another embodiment, the authentication credential may be stored  
30 externally to the message gate on the client. In one embodiment, a URI for the service may also be embedded in or provided to the gate by the gate factory.

In step 1012, the gate factory may also use the message schema in generating the client message gate. The message schema may be used to define the set of messages that the client may send to the service through the message gate. The gate factory may compile the message schema into the gate. The message schema may be  
35 compiled by the gate factory into the gate in an internal form suitable for quick access during the message verification process. Access to a service may be restricted for a particular client using the schema, thus giving the client less than full access to the service. In one embodiment, when the client obtains the service advertisement, for example, from a space, based upon the capabilities and/or access rights of the client, a restricted message schema may be provided to the client for the service. Thus, the gate factory may compile a restricted message

schema into the client message gate, thus restricting the client's access to the service. In one embodiment, the authentication service may determine a subset of the total set of messages that the client may send to the service. One or more levels of access may be provided for a service in the distributed computing environment. One level of access may provide a client of the service with access to all of the request messages in the message schema for the service, and thus to substantially all of the functions provided by the service to clients in the distributed computing environment. Other levels may provide a client of the service with access to various subsets of the request messages in the message schema, and thus to various subsets of the functionality of the service. In one embodiment, levels of access may also be determined by a client's capabilities. For example a thin client may not be able to download large data files, and thus may be restricted from using a message requesting the download of a large data file.

In one embodiment, the client may provide information about the client to the authentication service to determine an access level for the client. In one embodiment, the information may include a request for a specific level of access to the service. In one embodiment, the gate factory may provide the information to the authentication service to determine the access level of the client. Thus, the gate factory may generate a client message gate that is capable of sending a subset of the entire set of messages described in the message schema to the service based upon the capabilities and/or access level of the client.

In step 1014, the gate factory has generated the client message gate, and may notify the client that the gate has been generated. In one embodiment, the client message gate is a distinct code module that is accessible by the client. In one embodiment, the client message gate resides on the client. The client may then generate messages and pass the messages to the client message gate, which may verify the messages and send the messages to the service. Embodiments of a gate pair mechanism for the client and service to exchange messages is further described in Figures 42a-42c. Embodiments of gate factories are further described elsewhere herein.

A gate comprises code and data, and thus may itself be passed in a message. This provides an alternative method for creating gates on clients and/or services. In one embodiment, a gate passed in a message may be cloned if a new client wishes to use the gate. The cloning process performs a new set of gate creation security checks including authentication of the new client. A new, unique authentication credential may be generated for the new client and embedded in the cloned gate.

#### Figure 42a - A client sending a message to a service

Figure 42a is a flow diagram illustrating a client sending a first message to a service according to one embodiment. In step 1020, the client may send a message to the client message gate. In one embodiment, the message may be an XML message. In step 1022, the message gate may embed an authentication credential in the message prior to sending the message. In one embodiment, the authentication credential may have been provided by an authentication service as part of gate construction as described above.

In one embodiment, the message gate may verify the data representation language type correctness, syntax, etc. of the message. In one embodiment, the message gate may compare the message to a message template in a data representation language message schema to determine data representation language type correctness of the message. In one embodiment, the message may be an XML message, and the message gate may check the message against an XML message schema. In one embodiment, the message schema may have

been provided by an authentication service as part of gate construction as described above. In one embodiment, the message gate may locate a message template for the message in the schema and compare the various items or fields in the message to the message template to determine type correctness of the items.

In one embodiment, the first message may be a request message received from the client to be sent to the service, and the message gate may determine if the message and/or the requested service function(s) specified by the message are in the allowed subset of messages and/or service functions the client may send to the service. In one embodiment, the message gate may compare the message to the subset of allowed messages in the message schema to determine if the message is allowed. In one embodiment, an access level to the service provided to the client by the authentication service may be used to determine the subset of allowed messages the client may send to the service. In one embodiment, the first request message may request the service to establish a communications channel with the client. In one embodiment, the communications channel comprises a gate pair. The gate pair may comprise a client message gate and a service message gate. In one embodiment, the service message gate may not exist on the service when the first message is sent to the service.

In step 1024, the client message gate may send the first message to the service over the communications channel connecting the client to the service. In one embodiment, the client message gate may send the message to a service URI. In one embodiment, the service URI may have been provided to the client in the service advertisement. In one embodiment, the client message gate may be created for a specific service URI so that all messages are sent to the specific service URI, thus creating a message channel from the client to the service. In one embodiment, the request message may include an address for the client message gate so that the service may establish a communications link to the client through the client message gate. Examples of addresses that may be used for message gates include, but are not limited to: Universal Unique Identifiers (UUIDs) or URIs. The process of a service receiving a first message from a client is illustrated and described in Figure 42b.

Figure 42b - A service receiving a message from a client

Figure 42b is a flow diagram illustrating a service receiving a message from a client and using an authentication service to authenticate the message according to one embodiment. In step 1030, the service may receive a first message from the client. In one embodiment, the service message gate may not exist on the service when the first message is received by the service. In one embodiment, the client message gate may send the first message to a URI at the service, and the service may receive the first message from the client and then may generate a service message gate. In one embodiment, a mechanism on the service may be configured to generally receive messages including messages from clients at a URI provided to the client in the service advertisement. Upon receiving a first message from a client, the service may generate a service gate to thus establish a communications channel with the client through the gate pair consisting of the service message gate and the client message gate. In one embodiment, an address (for example, a UUID or URI) for the client message gate may be provided to the service in the first message from the client and may be used in generating the service message gate. In one embodiment, the service message gate may communicate only with the client message gate and thus with the client associated with the message gate. Thus, in some embodiments, there may be at least one unique service message gate for each client that is currently in communication with the service.



As described above, the client message gate may have embedded an authentication credential in the first message sent to the service. In step 1032, the service may send the authentication credential to an authentication service. In one embodiment, the authentication service may be the same authentication service used by the client to generate the authentication credential. In one embodiment, the service message gate may send the authentication credential to the authentication service. In one embodiment, the entire message may be sent to the authentication service.

In step 1034, the authentication service may perform verification of the authentication credential. In one embodiment, the authentication service may include a copy of the authentication credential from the creation of the authentication credential. In one embodiment, the authentication service may compare the authentication credential received from the service with the copy of the authentication credential. If the authentication credentials match, in step 1036, the authentication service may notify the service that the authentication credential has been verified and appears to be valid. If the verification process fails, the authentication service may notify the service that the authentication credential appears to be invalid.

In one embodiment, the authentication service may establish an access level for the client to access the functionality of the service. In one embodiment, the client may have established an access level for the service with the authentication service. In one embodiment, the authentication service may notify the service of the access level of the client. The access level of the client may be used by the service to determine a subset of request messages as described in the service message schema that the client may send to the service.

In step 1038, if the authentication service notified the service that the authentication credential is valid in step 1036, the service may generate a service message gate to pair with the client gate to form a gate pair. The service message gate may include the authentication credential to embed in messages sent from the service to the client, and for comparison with the authentication credential in messages received from the client. The service message gate may also include an address (such as a UUID or URI) for the client message gate. The service message gate may also include access level information for the client for verifying that messages received from the client are in the subset of allowed messages the client may send to the service. The service message gate may also include a message schema for type checking and verifying the syntax of messages received from the client and for use in verifying if messages are in the allowed subset of messages. In one embodiment, the service may create a new service message gate. In another embodiment, a service message gate may already exist prior to step 1038 that may be used to generate the service message gate to communicate with the client. In this embodiment, the service may not create a new gate, but instead may update the existing gate with information about the message channel to be established between the client and the service.

In one embodiment, after the service generates the service message gate, the service may send a message to the client. The message may include information to identify the service message gate to the client message gate and thus to establish the communications channel between the client and the service using the message gate pair. In one embodiment, the message may include an address (such as a UUID or URI) for the service message gate.

#### Figure 42c - Exchanging messages with embedded authentication credentials

Figure 42c is a flow diagram illustrating the general process of a client and service exchanging messages with embedded authentication credential according to one embodiment. In one embodiment, after the client

message gate and the service message gate are established, the client and service may no longer require the services of the authentication service. When sending messages, the client and service message gates may embed the authentication credential in the messages. When receiving messages, the client and service message gates may verify the message by comparing the embedded authentication credential with the copy of the authentication credential included in the gate.

In step 1040, the sender (client or service) message gate may embed an authentication credential in a message prior to sending the message. In one embodiment, the authentication credential may have been provided by an authentication service. In one embodiment, the message may be an XML message.

In one embodiment, the sender message gate may also verify the data representation language type correctness, syntax, etc. of the message prior to sending the message. In one embodiment, the sender message gate may compare the message to a message template in a message schema to determine type correctness of the message. For example, the message may be an XML message, and the message gate may include an XML message schema. The sender message gate may locate a message template for the message in the schema and compare the various XML items or fields in the message to the message template to determine type correctness of the items.

In one embodiment, the sender message gate may check the allowability of the message. In one embodiment, the message may be a request message received from a client to be sent to a service, and the message gate may determine if the requested function(s) specified by the message are in the subset of functions provided to the client by the access level the client established with the service through the authentication service. In one embodiment, the message gate may compare the message to a subset of allowed request messages in a message schema to determine if the message is allowed. In one embodiment, if the message is a response message from a service to a client, the message may not be checked for allowability. In another embodiment, response messages from the service to the client may be checked by the client message gate to insure that the client is authorized to receive the response message.

In step 1042, the sender (client or service) message gate may then send the message to the destination (client or service) message gate over the communications channel connecting the source (client or service) to the destination (client or service). In one embodiment, when receiving the message, the receiver message gates may verify the sender of the message by comparing the embedded authentication credential with the copy of the authentication credential included in the gate.

In one embodiment, the message may be encrypted before sending. In one embodiment, the message gate may perform the encryption. In another embodiment, a process external to the message gate may perform the encryption. For example, the message gate may pass the completed message to a driver process for a communications channel, and the driver process may perform encryption of the message. In one embodiment, encryption and decryption of messages may be performed by a transport mechanism (e.g. HTTPS).

In step 1044, the receiver (client or service) message gate may receive the message sent in step 1042. In one embodiment, if the message is encrypted, the message may be decrypted by a process prior to being received by the message gate. In another embodiment, if the message is encrypted, the message gate may decrypt the message. In step 1046, the receiver message gates may authenticate the sender of the message by comparing the embedded authentication credential with the copy of the authentication credential included in the receiver gate.

In some embodiments, some services may not require authentication credentials for at least some clients. In one embodiment, a client wishing to access a service for which no authentication credential is required for the client may generate a message gate without using an authentication service. In another embodiment, an authentication service may return a null, empty or otherwise generic authentication credential to a client that does not require authentication to use a service. In one embodiment not requiring authentication, the message gates may send messages without embedding authentication credentials. In another embodiment, a null, empty or otherwise generic authentication credential may be embedded in messages by the message gates.

In one embodiment, the receiver message gate may verify the data representation language type correctness, syntax, etc. of the message upon receiving the message. In one embodiment, the receiver message gate may compare the message to a message template in a message schema to determine type correctness of the message. For example, the message may be an XML message, and the message gate may include an XML message schema. The receiver message gate may locate a message template for the message in the schema and compare the various XML items or fields in the message to the message template to determine type correctness of the items.

In one embodiment, the receiver message gate may check the allowability of the message. In one embodiment, the message may be a request message received from a client, and the message gate may determine if the requested function(s) specified by the message are in the subset of functions provided to the client by the access level the client established with the service through the authentication service. In one embodiment, the receiver message gate may compare the message to a subset of allowed request messages in a message schema to determine if the message is allowed.

In one embodiment, the sender and the receiver may verify the message for type correctness and/or allowability. In another embodiment, the sender may perform message verification. In yet another embodiment, the sender may not perform message verification, and the receiver may perform message verification. In still yet another embodiment, no verification may be performed.

Some clients may be too "thin" to support the full functionality of a client message gate. These clients may not perform some or all of the request message verification prior to sending request messages and the response message verification subsequent to receiving response messages as described above. For example, some simple client devices may include a small set of request messages that may be sent to a service, and a small set of responses that may be accepted from the service. In one embodiment, a minimal client message gate may be constructed for the client device that sends request messages and receives response messages without performing the message verification as described above. In another embodiment, a proxy client message gate may be set up on another device that may provide some or all of the message verification, sending, and receiving as described above for the client.

#### Figure 43 - Checking the integrity of messages

Figure 43 is a flow diagram illustrating a mechanism for checking the integrity of messages according to one embodiment. In step 1050, the sender gate, acting on behalf of a client or a service, may embed a token in a message to be sent. This token is separate and distinct from the authentication credential as described above. The token may include information allowing the receiving gate to verify that the message has not been compromised or

altered. For example, the sender may compute a hash or checksum of the message that may be verified by the receiver. The sender may also encrypt this token and/or the entire message using the sender's private key and include in the encrypted message the corresponding public key so that the receiver may verify that the token was not changed. In step 1052, the sender gate may send the message. In step 1054, the receiver gate, acting on behalf of a service or a client, may receive the message. In step 1056, the receiver gate may examine the message, and the embedded token, to verify that the message has not been compromised.

There are several methods for generating the token to embed in the message. In one embodiment, a hash of the message may be computed and sent with the message. Hashing may include the transformation of a string of characters into a usually shorter, fixed-length value or key that represents the original string. Upon receiving the message, the receiver may recompute the hash and check it against the sent hash. If the message has been altered, it is highly unlikely that the same hash will be generated. The sender may encrypt the hash and send the corresponding public key in the encrypted message to substantially ensure that the hash is not compromised.

In other embodiments, an error detection scheme such as cyclic redundancy checking may be used. Cyclic redundancy checking is a method of checking for errors in data that is transmitted on a communications link. In an embodiment using cyclic redundancy checking, the sender applies an n-bit polynomial to the message and appends the resulting cyclic redundancy code (CRC) to the message. The receiver applies the same polynomial (which may also be passed in the message) to the message and compares its result with the result appended by the sender. If they agree, the message has been received successfully. If not, the sender may be notified to resend the message.

Other embodiments may include other methods for generating, embedding and checking tokens for checking messages for errors or malicious tampering.

#### Bridging Devices to the Distributed Network Environment

There may be devices, external to the distributed computing environment, which do not support the message passing model implemented by the distributed computing environment. These devices may provide services that may be useful to clients in the distributed computing environment. The distributed computing environment may include a mechanism to bridge such external devices to the distributed computing environment so that clients in the distributed computing environment may access the services offered on such devices. The distributed computing environment may also leverage existing device discovery protocols for discovering such external devices for use in the distributed computing environment.

Many technologies define discovery protocols for publishing and monitoring a network's device composition. These technologies include, but are not limited to: Jini, SLP, Bluetooth, and UPnP. Furthermore, many I/O buses such as LonWorks, USB and 1394 also support dynamic discovery protocols. The distributed computing environment may leverage device discovery technologies by wrapping their implementations in an API. Leveraging other device discovery protocols and providing a method to bridge to other discovery protocols may allow the distributed computing environment to discover devices or services on a wide variety of network and I/O buses. Device discovery in the distributed computing environment may thus be applicable to a wide range of devices including small devices such as PDAs, even if they do not participate directly in the distributed computing environment. Discovery protocols may be defined at the message level.

A bridging mechanism may be provided for “wrapping” one or more specific device discovery protocols, such as Bluetooth’s, in a messaging API for the distributed computing environment. Wrapping may include framing the device discovery protocol with code and/or data (the API) so that the protocol can be run by clients and/or services in the distributed computing environment that would not otherwise be able to run it. When run, the bridging mechanism may allow for a discovery agent that discovers devices by a specific device discovery protocol to publish services for those devices in a space in the distributed computing environment. The services present an XML message schema interface to clients in the distributed network environment, and are capable of operating the various devices discovered by the specific device discovery protocol. Thus, service advertisements may be published for the services that operate the various devices discovered by the underlying wrapped device discovery protocols. The advertised services thus bridge devices (or services) external to the distributed network environment to clients on the distributed network environment.

Figure 27 illustrates one embodiment of a distributed computing environment with a space 1200. One or more discovery agents 1204 may participate in an external discovery protocol and bridge to the distributed computing environment through bridging mechanism 1202. When the wrapped device discovery protocols are run, discovery agents 1204 through bridging mechanism 1202 may publish service advertisements 1206a-1206c in space 1200, wherein each one of advertisements 1206a-1206c corresponds to a device or service discovered by one of discovery protocols 1204 outside the distributed computing environment. Clients may then access the external devices using the service advertisements 1206a-1206c in space 1200 to instantiate services on one of the agents 1204 that operates the corresponding external device or service.

Thus, clients of the distributed computing environment may use discovery agents wrapping device discovery protocols to find devices. A service acting as a bridge to these devices may be published in a space and advertised, so clients of the distributed computing environment may access the services provided by the external devices. The advertised service is a service within the distributed computing environment that is able to invoke a device outside the distributed computing environment via another protocol or environment, thus bridging the outside device/service to the distributed computing environment. A client within the distributed computing environment “sees” only the advertised service within the distributed computing environment and may not even be aware of the outside device/service.

In one embodiment, the distributed computing environment may provide a version of a space discovery message protocol, such as the discovery protocol described in the Spaces section, that may be mapped to an underlying external device discovery protocol, including the wrapped device discovery protocols described above. The mapped discovery protocol may register itself or be registered with a space, e.g. a default space, by placing an advertisement in that space. For each advertised discovery protocol, a subsequent results space to hold the results of the discovery protocol may be provided.

Figure 28 illustrates an example of the space discovery protocol mapped to a Bluetooth discovery service 1220 according to one embodiment. The Bluetooth discovery service 1220 may first register 1230 with the distributed computing environment. The Bluetooth discovery service 1220 may be wrapped in a bridging API, and an advertisement 1225 for the discovery service 1220 may be added 1232 in space 1224. A client or service may locate the discovery service advertisement 1225 on space 1224. When the discovery service 1220 is executed (utilizing the API wrapper as a bridge between the discovery protocol 1220 and the distributed computing

environment 1222), a new space 1226 may be created 1234 to store the results of the discovery process. The discovery service 1220 may store the results (again through the API wrapper) to discovery results space 1226 as one or more advertisements 1227. Alternatively, results of executing discovery service 1220 may be stored to space 1224 or other pre-existing spaces in the distributed computing environment. A similar method as illustrated in Figure 28 may be used to discover devices and other services using other underlying discovery protocols.

As mentioned above, there may be devices, external to the distributed network environment, which do not support the message passing model implemented by the distributed network environment. These devices may have clients that may want to use services provided in the distributed computing environment. The distributed computing environment may provide a mechanism to bridge the external clients or client devices to the distributed computing environment so that the clients on the external devices may access services in the distributed computing environment.

Agents may be provided that serve as clients in the distributed computing environment to bridge external clients to the distributed computing environment, allowing the external clients to access services published in the distributed computing environment. In one embodiment, an agent may have an XML-enabled back end capable of communicating with services in the distributed computing environment using the message passing model, and a proprietary protocol (e.g. a protocol supported by the external device) on the front end to interface to the external device, and thus to the external client. Thus, a client external to the distributed computing environment may locate and access services in the distributed computing environment through the bridging agent, and may send requests to the services and receive responses from the services, including results data. For example, an external client may use the bridging agent to run space discovery in the distributed computing environment, look up advertised services, and invoke services in the distributed computing environment.

In one embodiment, the distributed computing environment may provide a bridging mechanism for accessing Jini services from a distributed computing environment client. Since Jini services may require Remote Method Invocation (RMI), and since clients in the distributed computing environment may communicate to services using messages such as XML messages, a protocol bridging mechanism may be provided to enable the access of a Jini Service by a distributed computing environment client. In one embodiment, a connector mechanism may be defined that enables the dynamic advertisement of Jini services in distributed computing environment spaces, and that also may enable the accessing of a Jini service proxy from clients in the distributed computing environment. In one embodiment, there may be Jini services that may not be bridged to the distributed computing environment.

In one embodiment, an agent may be provided as a service in the distributed computing environment that bridges the Jini RMI protocol used by Jini services to XML messaging used by distributed computing environment clients. When the agent is started, the agent may perform a lookup on the Jini spaces for Jini services that have a set of attributes. For every registered Jini service, the agent may generate an XML advertisement that may correspond to the service and may register the advertisement in a space in the distributed computing environment. In one embodiment, an agent may register for event notification in the Jini Lookup service, and thus may be informed when a new Jini service is registered. When informed of a new Jini service, the agent may perform a lookup in Jini spaces to locate newly advertised Jini services and to update the distributed computing environment space with new XML advertisements for the new services. In one embodiment, when a Jini service is removed,

the agent may receive an event notifying of the removal of the Jini service. The agent may then remove the XML advertisement for the service from the space.

In one embodiment, to invoke a Jini service via an XML advertisement in a distributed computing environment space, a client may look up the service advertisement in the space and may send valid messages to the agent to access the service. The agent may invoke the proxy service corresponding to the Jini service by invoking the corresponding method through an RMI call to a service proxy. If the proxy is not instantiated, the agent may download the proxy code and instantiate a new instance of the proxy object. In one environment, every client connection may have a different proxy-instance. The incoming message from the client may be converted by the agent into a method call for the proxy. The result from the method call may be returned to the client as an outgoing message.

In one embodiment, only simple Java types may be used as arguments to an RMI method. If complex Java types are required, then one or more data advertisements may be passed as arguments to the call, where the data advertisements may indicate the location and access method of data for the complex Java types. In one embodiment, the agent may perform initial conversion from XML messages to an RMI method call invocation dynamically. Since, the agent knows the service interface, it may generate the corresponding set of messages that are advertised to the client.

Figure 29 illustrates bridging a client 1250 external to the distributed computing environment to a space 1254 in the distributed computing environment. Bridging agent 1252 may serve as the go-between between client 1250 and space 1254. Bridging agent 1252 may communicate with client 1250 in a communications protocol understandable by the client 1250. Bridging agent 1252 may map the client's communications protocol into the XML messaging protocol necessary to communicate with space 1254 perform the facilities provided by space 1254. Bridging agent 1252, at client 1250's request, may locate and run services on space 1254. For example, client 1250 may request a list of all services of a particular type from space 1254. Bridging agent 1252 may locate service advertisements 1256a-c and return the results to client 1250. Alternatively, the results may be posted in a results space, and the location of the results may be returned to the client 1250. Client 1250 may then choose to execute service advertisement 1256a, and may send a message (in the client 1250's communications protocol) to bridging agent 1252. Bridging agent 1252 may then send the XML request message(s) necessary to execute the service represented by service advertisement 1256a, and may return the results of the service to client 1250. Methods of handling the results of the service other than directly returning the results to the client 1250 may be used as described above in the section titled Spaces. Bridging agent 1252 thus may act as a service of the external client 1250 (via the external client's protocol) and as a client within the distributed computing environment to bridge a service within the distributed computing environment to the external client.

Sometimes, even within the distributed computing environment, clients and services cannot directly communicate with each other, only to a common space. In this case, the space service will automatically create a service proxy that bridges client to service. The proxy's main job is to route messages between client and service through the space. The service proxy may be created dynamically. The creation mechanism may be dependent upon space implementation. Refer to Figure 30 for an illustration of a proxy mechanism. A client 554 and a service 556 may not be able to communicate directly within the distributed computing environment, e.g., because they support different transport or network protocols. However, they both may be able to communicate with a

space 552 that supports both protocols. The space service may create a proxy 550 to bridge the client 554 to the service 556. A common form of proxy is a browser proxy. A browser proxy (most commonly implemented as a servlet) may translate conventional Web page requests into messages. Refer also to the description of space search services (and proxies therefore) in the Spaces section herein.

5       The distributed computing environment may provide a mechanism for bridging clients in the distributed computing environment to enterprise services. In one embodiment of a distributed computing environment, a method for bridging clients to enterprise services may include a client within the distributed computing environment, a bridge service within the distributed computing environment, and an enterprise service within the enterprise environment. The distributed computing environment bridge service serves as a bridge service between  
10   the client and the enterprise service. An enterprise may be a corporation, small business, non-profit institution, government entity, or other kind of organization. An enterprise may utilize an enterprise computing environment for conducting a portion of its business. The enterprise computing environment may include various enterprise services. Clients in the distributed computing environment may desire to use services in the enterprise computing environment. An enterprise service may be based on a number of architectures, such as three tiered client/server  
15   architectures. An example of an architecture that may be used to implement an enterprise service is Enterprise JavaBeans. Enterprise JavaBeans (EJB) is an architecture for setting up program components, written in the Java programming language, that run in the server parts of a enterprise environment using a client/server model. In object-oriented programming and distributed object technology, a component is a reusable program building block that may be combined with other components in the same or other computers in a distributed network to form an  
20   application. EJB is built on the JavaBeans technology for distributing program components (Beans) to clients in a network. To deploy an EJB Bean or component, it must be part of a specific application, which is called a container. In Enterprise JavaBeans, there are two types of beans: session beans and entity beans. An entity bean is described as one that, unlike a session bean, has persistence and can retain its original behavior or state. Using EJB, programs may be deployed across substantially all major operating systems. EJB's program components are  
25   generally known as servlets (little server programs). The application or container that runs the servlets is sometimes called an application server.

      The bridge service interacts with the client via XML message passing to gather input parameters necessary to make requests to the enterprise service outside of the distributed network environment. For example, the bridge service may be looked up and instantiated by the client just as any other service in the distributed  
30   computing environment. The bridge service then may interact with the enterprise service to run the enterprise service. This interaction may use an interprocess communications architecture that the enterprise service can understand. As an example, if an enterprise service is implemented with Enterprise JavaBeans (EJB), a bridge service may communicate with the enterprise service using EJB. The bridge service may then receive results from the enterprise service and may return the results directly to the client (in XML messages) or may place the results  
35   in a space in the distributed network environment (e.g. a results space). To the client, the bridge service appears to be the only service (the enterprise service is hidden to the client), so the client does not have to support the architecture of the enterprise service. Multiple distributed network environment clients may use the same bridge service (each using a unique gate pair) to interact with the enterprise service.



The bridge service or other agent may publish an advertisement for the bridge service (and thus for the enterprise service) in a space in the distributed computing environment. For example, a bridge service or other bridge agent may use Java Reflection to examine Beans for services in an enterprise system implemented with EJB, and then create service advertisements for bridge services to the Beans and publish those advertisements in spaces in the distributed computing environment. Reflection is a method for Java code to discover information about the fields, methods and constructors of classes, and to use reflected fields, methods, and constructors to operate on their underlying counterparts on objects, within security restrictions. The Reflection API accommodates applications that need access to either the public members of a target object or the members declared by a given class. Once the bridge services are advertised, clients may access the bridge services (and thus the corresponding enterprise services) similarly to any other advertised services in the distributed network environment, without knowledge of the architecture of the enterprise service providing the services.

#### Client Displays

There are several methods in which results from a service run by a client may be displayed in a distributed computing environment. Devices that may display results may include, but are not limited to: CRTs on computers; LCDs on laptops, notebooks displays, etc; printers; speakers; and any other device capable of displaying results of the service in visual, audio, or other perceptible format. The methods for displaying results may include, but are not limited to:

- The service may return results to a client directly or by reference, and the client may handle the display of the results.
- The service may return results to a client directly or by reference, and the client may pass the results to a display service directly or by reference, and the display service may display the results.
- The service may directly handle the displaying of the results.
- The service may pass the results to a display service directly or by reference, and the display service may display the results.

In the last method of displaying results, the client may specify the display service. For example, there may be a display service on or associated with the device on which the client resides that the client wishes to use to display the results of the service. When the client runs the service, the client may send a message to the service specifying the service advertisement of the client's display service. The service may then build a gate that allows it to send messages to the client's display service. Thus, when displaying results, the service invoked by the client becomes a client of the client's display service and sends its results (directly or by reference) for display to that display service. More detail on the client-service relationship, gates, and messaging is included in other sections of this document.

Conventional application models are typically based on predetermined, largely static user interface and/or data characteristics. Changes to conventional applications may require code modification and recompilation. The mechanisms described for advertising services and for specifying XML message schemas for communicating with services in the distributed computing environment may be used to provide a mechanism for applications (clients, services, etc) to describe dynamic display objects. Using the dynamic display objects, application behavior may

be altered without having to download new code, recompile, or re-link the application. Display schemas may be provided for displaying the same results in different formats, for extracting portions of the results for display, and for displaying the results on different display devices.

Figure 31 illustrates one embodiment of a client 1300 with associated display 1302 and display service 1304 according to one embodiment. An advertisement 1306 for display service 1304 may be registered on space 1308. An advertisement 1312 for service 1310 may be registered on space 1314 by service 1310. Alternatively, service advertisement 1312 and display service advertisement 1306 may be registered on the same space. Client 1300 may search for and discover (1320) service advertisement 1312 on space 1314, and may then set up a gate to send requests to (and receive results or responses from) service 1310. In one embodiment, the messages may be in the form of XML messages specified in an XML schema received as part of advertisement 1312. Client 1300 may send one or more messages (1322) to service 1310. The one or more messages may include messages for running service 1310 and for instructing service 1310 to send results to display service 1304 for display, and may specify the location of display service advertisement 1306. The advertisement location may be specified as a Uniform Resource Identifier (URI).

The messages from client 1300 to service 1310 may instruct service 1310 to perform one or more operations that produce displayable results. Service 1310 may retrieve display service advertisement 1306 from space 1308 based upon the location information received from client 1300. The service advertisement may include the XML message schema and other information necessary to interface with display service 1304. Service 1310 may then set up a gate to send requests to (and receive results from) display service 1304. In other embodiments, messages from client 1300 to service 1310 may include the XML schema and other information needed for service 1310 to construct a gate to display service 1304, or may include a pre-constructed gate to display service 1304.

During, or after completing, operations requested by client 1300, service 1310 may send the results of the operations to display service 1304 in the manner specified by the schema for display service 1304 (e.g. encapsulated in XML messages specified in the XML message schema or by reference as parameters for the display service). In this regard, service 1310 may be a client of display service 1304. Display service 1304 may then format and display the results received from or indicated by service 1310 on display 1302 for the client.

In some embodiments, service 1310 may post the results of operations to a space such as a results space (not shown). Service 1310 may then send a message to display service 1304 including a reference to the stored results of the operations. In one embodiment, the reference may be in the form of a URI. The display service 1304 may then retrieve the results from the space and display the results on display 1302.

Conventional application models are typically based on predetermined, largely static user interface and/or data characteristics. Changes to conventional applications may require code modification and recompilation. The mechanisms described for advertising services and for specifying XML message schemas for communicating with services in the distributed computing environment may be used to provide a mechanism for applications (clients, services, etc) to describe dynamic display objects. Using the dynamic display objects, application behavior may be altered without having to download new code, recompile, or re-link the application.

The dynamic display objects may be described in XML schemas. These schemas may be advertised in spaces. These schemas may be referred to as display schemas or presentation schemas. An application (or other

services acting on behalf of the application) may then access the schemas from the service advertisements to display data based upon formatting, data type, and other information stored in the schemas.

The following is an example of a schema containing dynamic display objects:

```
<element name="delivery" type="Space:shipto" minOccurs="0" />
<type name="TextField">
  <element name="Address" type="string"/>
  <element name="City" type="string"/>
  <element name="State" type="string"/>
  ...
  ...
  ...
</type>
```

The above schema may be changed to the following without requiring an application recompile:

```
<element name="delivery" type="Space:shipto" minOccurs="0" />
<type name="TextField">
  <element name="Name" type="string"/>
  <element name="Address" type="string"/>
  <element name="City" type="string"/>
  <element name="State" type="string"/>
  ...
  ...
  ...
</type>
```

Figures 32A and 32B illustrate examples of using schemas of dynamic display objects according to one embodiment. In Figure 32A, application 1320 (may be a client, a service, or other application) has been implemented with presentation schema advertisement 1324 stored in space 1326. A presentation schema advertisement may include elements describing the data types, formatting specifications, fonts, locations, colors, and any other information used for displaying data for the application on display 1322. There may be multiple presentation schema advertisements for application 1320. For example, there may be one schema for each display page in a series of display pages (for example, Web pages on a Web site).

In one embodiment, application 1320 may invoke a discovery and/or lookup service to locate presentation schema advertisements. The discovery and/or lookup service may return an XML document listing one or more advertisements, and URIs to each of the schemas describing a particular display format, etc. Application 1320 may then select a presentation schema or schemas from the XML document. Application 1320 may then parse the schema, breaking out the elements of the schema into user interface components. The components then may be used to locate, format, and display results data on the appropriate display. The result data may be from running a service or from a results space, for example. Thus, as opposed to having a static or predetermined display, the application 1320 is configured to display results according to a presentation schema that may be dynamically changed without requiring a rebuild of the application.

Presentation schemas may be provided for displaying the same results in different formats, for extracting portions of the results for display, and for displaying the results on different display devices.

In one embodiment, one or more presentation schema advertisements may be stored in one or more spaces in a distributed computing environment. As copies of an application are invoked on one or more devices, each copy of the application may run a search for services to discover advertisements for the presentation schemas used by the applications. Thus, a central, persistent store of the display information may be kept for multiple instances of the application or for other applications. The display information may be modified in the central location without requiring the recompilation and/or reinstallation of the applications.

In Figure 32B, client 1328 may locate a service advertisement for service 1330 on a space. When invoking service 1330, client 1328 may pass a location of presentation schema advertisement 1324 on space 1326 to service 1330. When service 1330 is ready to provide results to client 1328, it may display the results on display 1322 (which may be coupled to the device on which client 1328 is running) using the display information from the presentation schema provided by presentation schema advertisement 1324. To change the way the results are displayed, the XML messages in the presentation schema advertisement 1324 may be modified, or a different presentation schema may be selected, without requiring changes at the client 1328 or service 1330. Service 1330 may be a display service.

A client, application or service may provide a plurality of display schemas for displaying results of various operations provided by one or more services. Alternatively, a display schema may include information for displaying a variety of results for one or more clients. Thus, client 1328 may use one display schema or a plurality of display schemas. Two or more display schemas may be provided for formatting and displaying the same results with different formats, or on different displays. For example, one display schema for a set of results may be provided for displaying results on a display screen, and another for printing the results. Also, copies of the same application, client or service may run on devices with different display capabilities, so two or more display schemas may be provided for supporting the display requirements of the different devices.

#### String Management

String handling in conventional systems is generally not very efficient, especially for variable sized strings, and may be wasteful of memory space, e.g. as the string is copied and/or moved in memory. This inefficiency in string handling may be particularly problematic in small memory footprint systems such as embedded systems. The amount of memory, particularly stack space and space for dynamic allocation, may be limited in small footprint systems. Thus, a more efficient method of handling strings in programs executing within small footprint systems such as embedded systems is desirable.

Figure 33A illustrates a typical string representation in the C programming language. In C, a string may be represented by a character pointer 1450 (string1) containing a memory location (address) of the first character of a string 1452. Other characters follow the first character in the string 1452, and are typically stored in consecutive addressable byte locations in memory. Characters in C strings are typically 8-bit. The characters in C strings may be any ASCII character. A C string must be terminated by a NULL character. NULL is platform defined as one of the 256 possible 8-bit values, but is typically the binary value 0b00000000. The string 1452 occupies 13 bytes (12 string characters plus the terminating character).

An example of a string operation in C is the `strlen()` function, typically provided with standard C library implementations. The `strlen()` function takes a string pointer as input and returns the length (in bytes) of the string, not including the terminating character. For example, passing the character pointer 1450 to the `strlen()` function would return the length 12. The `strlen()` function may be implemented by “walking” the string until the terminating character is located, counting each character.

String copying in C is typically handled by a `strcpy()` or a `strncpy()` C library functions, which are implemented as:

```
char *strcpy(char *dest, const char *src);
char *strncpy(char *dest, const char *src, size_t n);
```

The `strcpy()` function copies the string pointed to by the character pointer `src` (including the terminating character) to the string pointed to by character pointer `dest`. The strings may not overlap, and the destination string `dest` must be large enough to receive the copy.

The `strncpy()` function is similar, except that not more than `n` bytes of `src` are copied. Thus, if there is no terminating character among the first `n` bytes of `src`, the result will not be terminated. If desired, an instruction may be placed in the code following a `strncpy()` to add a termination character to the end of the `dest` string. In the case where the length of `src` is less than that of `n`, the remainder of `dest` will be padded with nulls. The `strcpy()` and `strncpy()` functions return a pointer to the destination string `dest`.

Figure 33B illustrates an example of the results of the `strncpy()` function on string 1452, when `strncpy()` is called with the following parameters:

```
strncpy(string2, string1+3, 5);
```

where `string2` is character pointer 1454 pointing to the first byte after the terminating character of string 1452, `string1+3` is character pointer 1450 incremented by 3 bytes, and 5 is the number of characters (bytes) to be copied from the source location `string1+3` to `string2`. After copying, the next character after the five characters copied from `string1` may be set to the terminating character (the character may have been initialized to the terminating character prior to the copy). Thus, the two strings now occupy  $(13 + 6) = 19$  bytes of memory. If the `strcpy()` function was applied with character pointer 1450 as the source string, the original string 1452 and the resultant new string would occupy  $(13 * 2) = 26$  bytes.

Figure 33C illustrates an efficient method for representing and managing strings in general, and in small footprint systems such as embedded systems in particular. String 1452 is stored in memory as 12 bytes (no terminating character is required). String structure 1460 includes pointers (`Address(A)` and `Address(L)`) to the first and last characters of string 1452. Using this string structure, the string's length may be efficiently computed by subtracting the pointer to the first character from the pointer to the last character.

Operations such as string copy operations `strcpy()` and `strncpy()` may also be handled more efficiently. With string structures such as those illustrated in Figure 33C, a new string structure 1462 may be created, and the first and last character pointers may be initialized to point to the respective characters in string 1452. Thus, a portion or all the string 1452 does not have to be copied to new storage for the string. As strings can be hundreds or even thousands of characters long, the memory saved using the string structures and string methods implemented to take advantage of them may be considerable. This method of handling copies of portions or all of

a string may be called "substring management," as it deals with the efficient handling of portions (substrings) of strings.

Other string functions from the standard C string library may be replaced with string functions taking advantage of the string structure as illustrated in Figure 33C. Examples of other C string functions include, but are not limited to: strstr(), strcat(), and sprintf(). The string handling structures and methods as described in Figure 33C may be used, along with the hierarchical structure of XML documents, to provide more efficient handling of XML text (such as XML messages) in systems with small memory footprints such as embedded systems. The following is a simple example of an XML schema defining a purchase order:

```
<!DOCTYPE purchase.order SYSTEM "po.dtd">
<purchase.order>
  <date>22 May 2000</date>
  <billing.address>
    <name>John Smith</name>
    <street>123 Main</street>
    <city>Anywhere</city>
    <state>MA</state>
    <zip>12345-6789</zip>
  </billing.address>
  <items>
    <item>
      <quantity>3</quantity>
      <product.number>248</product.number>
      <description>Decorative Widget, Red, Large</description>
      <unitcost>19.95</unitcost>
    </item>
    <item>
      <quantity>1</quantity>
      <product.number>1632</product.number>
      <description>Battery, AA, 4-pack</description>
      <unitcost>4.95</unitcost>
    </item>
  </items>
</purchase.order>
```

The hierarchical structure of XML documents may allow them to be processed in a recursive fashion with successively smaller portions of the document processed at each level of recursion. References to various portions are recorded and processed recursively. String structures as described in regard to Figure 33C may be used to record the various portions. In this manner, the content of specific XML tags (one line in the above example), in one embodiment the smallest unit of the XML document processed recursively, may be determined efficiently. Documents with repeated tags in the same scope may also be handled efficiently, as tags within a given scope may be enumerated and processed efficiently.

A recursive method for processing an XML document using string structures similar to those described in Figure 33C may accept a string structure representing the entire XML document string and pointing to the first byte and the last byte in the document string. The method may then locate the next subsection of the document and pass a string structure representing the substring of the entire document string containing the subsection to a processing function for the subsection type. The subsection itself may be broken into another level of subsections represented by string structures passed to processing functions for the subsection type. The method may continue in the recursive processing of the XML document subsections until the entire document has been processed.

Using the string structures with the recursive processing allows the processing to be done without creating copies of the subsections for processing. Copying of subsections may be particularly costly in recursive processing, because as the recursion goes deeper, more and more copies of the same data are made. Using the string structures, only the string structure containing the pointers to the first and last bytes in the subsection needs to be created and passed down to the next level. Other operations, such as determining the length of a subsection, may be performed efficiently using the address information stored in the string structures. Also, by using the string structures, terminating characters such as those used to terminate C strings are not necessary, conserving memory in small footprint devices such as embedded devices.

#### XML representation of Objects

As previously mentioned, Jini RMI may not be practical for some clients, such as thin clients with minimal memory footprints and minimal bandwidth. The serialization associated with the Jini RMI is slow, big, requires the JVM reflection API, and is a Java specific object representation. Java deserialization is also slow, big and requires a serialized-object parser. Even Java based thin clients may not be able to accept huge Java objects (along with needed classes) being returned (necessarily) across the network to the client, as required in Jini.

A more scalable distributed computing mechanism may be provided by embodiments of a distributed computing environment. A distributed computing environment may include an API layer for facilitating distributed computing. The API layer provides send message and receive message capabilities between clients and services. This messaging API may provide an interface for simple messages in a representation data or meta-data format, such as in the eXtensible Mark-up Language (XML). Note that while embodiments are described herein employing XML, other meta-data type languages or formats may be used in alternate embodiments. In some embodiments, the API layer may also provide an interface for messages to communicate between objects or to pass objects, such as Java objects. Objects accessible through API layer 102 are represented by a representation data format, such as XML. Thus, an XML representation of an object may be manipulated, as opposed to the object itself.

The API layer may sit on top of a messaging layer. The messaging layer may be based on a representation data format, such as XML. In one embodiment, XML messages are generated by the messaging layer according to calls to the API layer. The messaging layer may provide defined static messages that may be sent between clients and services. Messaging layer may also provide for dynamically generated messages. In one embodiment, an object, such as a Java object, may be dynamically converted (compiled) into an XML representation. The object may include code and/or data portions. The object's code and/or data portions may be compiled into code and data segments identified by XML tags in the XML representation. The messaging layer may then send the XML object representation as a message. Conversely, the messaging layer may receive an XML representation of an object. The object may then be reconstituted (decompiled) from that message. The reconstitution may examine the XML representation for tags identifying code and/or data segments of the XML representation, and use information stored in the tags to identify and decompile the code and/or data portions of the object.

### Creating and sending an XML representation of an Object

Figure 34 illustrates a process of moving Java objects between a client 1500 and a service 1502 according to one embodiment. Service 1502 may be any service supported in the distributed computing environment, including space services. Client 1500 employs a gate 1504, which may have been created using an XML schema received from a service advertisement for service 1502, to communicate with a corresponding gate 1506 for service 1502. At some point, client 1500 may need to send Java object 1510 to service 1502. Java object 1510 may reference other objects, which may in turn reference other objects, and so on. Java object 1510 and its referenced objects, the objects they in turn reference, and so on, may be referred to as an object graph.

Java object 1510 may be passed to a Java object compilation process 1512 to be compiled to produce an XML representation of the object graph. The XML representation of the object graph may be passed as an XML data stream 1514 to gate 1504. The XML data stream 1514 may include an XML representation of all the objects in the object graph. In one embodiment, the objects in the object graph may be stored recursively in the XML data stream 1514.

Gate 1504 may then package the XML data stream 1514 in a message 1516 and send the message 1516 to gate 1506 of service 1502. Gate 1506 may extract the XML data stream 1514 from XML message 1516 and send the XML data stream 1514 to an XML data stream decompilation process 1518 to be decompiled to produce the object(s) comprising the object graph, including Java object 1510. In one embodiment, the objects in the object graph may be stored recursively in the XML data stream 1514, and thus a recursive decompilation process may be used.

When service 1502 needs to send a Java object to client 1500, a substantially similar process may be used. Java object 1520 may be passed to a Java object compilation process 1512 to be compiled to produce an XML representation of the object graph. The XML representation of the object graph may be passed as an XML data stream 1522 to gate 1506. Gate 1506 may then package the XML data stream 1522 in a message 1524 and send the message 1524 to gate 1504 of client 1500. Gate 1504 may extract the XML data stream 1522 from XML message 1524 and send the XML data stream 1522 to an XML data stream decompilation process 1518 to be decompiled to produce the object(s) comprising the object graph, including Java object 1520.

In another embodiment, the gates may be responsible for the compilation and decompilation of Java objects. In this embodiment, Java object 1510 may be passed to gate 1504. Gate 1504 may then pass object 1510 to a Java object compilation process 1512 to be compiled to produce an XML representation of the object graph in an XML data stream 1514. Gate 1504 may then package the XML data stream 1514 in a message 1516 and send the message 1516 to gate 1506 of service 1502. Gate 1506 may extract the XML data stream 1514 from XML message 1516 and send the XML data stream 1514 to an XML data stream decompilation process 1518 to be decompiled to produce the object(s) comprising the object graph, including Java object 1510. The process of sending a Java object from service 1502 to client 1500 may be substantially similar to the process of sending an object from the client to the service.

In one embodiment, object compilation process 1512 and object decompilation process 1518 may both exist on the client 1500 and the service 1502, and may be programmed to perform compilation and decompilation substantially similarly on the two devices, thus ensuring the object(s) output on one end are substantially identical to the object(s) input on the other end. In one embodiment, XML schemas including descriptions of Java objects



may be used on both the client and/or the service in the compilation and decompilation processes. In one embodiment, XML schema(s) to be used in the compilation and decompilation of Java objects may be passed by the service to the client in the service advertisement.

XML provides a language- and platform-independent object representation format. Thus, the process as illustrated in Figure 34 where an object is compiled into an XML representation of the object and decompiled to reproduce the object may not be limited to moving Java objects, but in some embodiments may be applied to moving objects of other types between entities in a network.

Figure 46 illustrates a mechanism for sending objects from services to clients using XML representations of the objects. In step 2200, a client may request an object from a service. In one embodiment, the object may be a Java object. In one embodiment, the client may send a message (e.g. an XML message) to the service requesting the object. In step 2202, the service, after receiving the request, may provide the object to a compilation process. In one embodiment, the compilation process may be integrated in the virtual machine within which the service is executing. In one embodiment, the virtual machine may be a Java Virtual Machine (JVM). In one embodiment, the compilation process may be provided as an extension to the JVM. In step 2204, the compilation process generates a data representation language representation of the object. In one embodiment, the data representation language is XML. The representation of the object may include a name or identifier for the object and one or more instance variables for the object. An instance variable, in object-oriented programming, is one of the variables of a class template that may have a different value for each object of that class. In step 2206, the service may send the data representation language representation of the object to the client. In one embodiment, the representation may be packaged in a message. In one embodiment, the message is in the data representation language. Message gates, as described elsewhere herein, may be used for message passing between the client and service.

In step 2208, the client receives the data representation language representation of the object and provides the representation to a decompilation process. In one embodiment, the decompilation process may be integrated in the virtual machine within which the client is executing. In one embodiment, the virtual machine may be a Java Virtual Machine (JVM). In one embodiment, the decompilation process may be provided as an extension to the JVM. In step 2210, the decompilation may generate a copy of the object from the data representation language representation of the object. The object may then be provided to the client.

### JVM compilation/decompilation API

Figures 35a and 35b are data flow diagrams illustrating embodiments where a virtual machine (e.g. JVM) includes extensions for compiling objects (e.g. Java Objects) into XML representations of the objects, and for decompiling XML representations of (Java) objects into (Java) objects. The JVM may supply an Applications Programming Interface (API) to the compilation/decompilation extensions. The client 1500 and service 1502 may be executing within JVMs. The JVMs may be on the same device or on different devices.

In both Figure 35a and Figure 35b, the JVM XML compiler/decompiler API 1530 may accept a Java object 1510 as input, and output an XML representation of the object 1510 and all its referenced objects (the object graph of object 1510) in an XML data stream 1514. In addition, the JVM XML compiler/decompiler API 1530 may accept an XML data stream 1522, which includes an XML representation of object 1520 and all its

referenced objects (the object graph of object 1520), and output Java object 1520 (and all the objects in its object graph).

Figure 35a illustrates one embodiment where, when sending Java object 1510, the client calls the JVM XML compiler/decompiler API 1530. The client 1510 passes Java object 1510 to the API 1530, which compiles the object to produce its XML representation, stores the XML representation in XML data stream 1514, and outputs XML data stream 1514. The client may then pass XML data stream 1514 to gate 1504. Gate 1504 may then package the XML data stream 1514 in an XML message 1516 and send message 1516 to service 1502.

Upon receiving XML message 1524 from service 1502, gate 1522 may extract XML data stream 1522 from message 1524 and pass data stream 1522 to client 1500. Client 1500 may then call the JVM XML compiler/decompiler API 1530, passing API 1530 the XML data stream 1522. The API 1530 may then decompile the XML data stream 1522 to produce Java object 1520 and other objects in its object graph, returning the objects to client 1500.

Figure 35b illustrates another embodiment where, when sending Java object 1510, the JVM XML compiler/decompiler API 1530 is called by the gate. The client 1510 passes Java object 1510 to gate 1504. Gate 1504 then passes object 1510 to API 1530, which compiles the object to produce its XML representation, stores the XML representation in XML data stream 1514, and outputs XML data stream 1514. Gate 1504 may then package the XML data stream 1514 in an XML message 1516 and send message 1516 to service 1502.

Upon receiving XML message 1524 from service 1502, gate 1522 may extract XML data stream 1522 from message 1524 and pass data stream 1522 to the JVM XML compiler/decompiler API 1530. The API 1530 may then decompile the XML data stream 1522 to produce Java object 1520 and other objects in its object graph. The gate may then send Java object 1520 and the other objects to client 1500.

In one embodiment, the JVM XML compiler and decompiler may be implemented as integrated functions of the JVM. In another embodiment, the XML compiler and decompiler may be embodied in API method invocations in standard extensions to the JVM; thus, the core JVM does not have to be modified. The JVM may supply the JVM XML compiler/decompiler API 1530 to processes (clients and/or services) executing within the JVM to allow the processes to access the Java object compilation/decompilation functionality provided by the JVM. In one embodiment, for a process to utilize the object compilation/decompilation, the JVM within which the process is executing must have the JVM XML compiler/decompiler functionality and API 1530.

Methods using reflection and serialization to transform and send objects are typically implemented in applications separate from the JVM. The application must repeatedly access the JVM to pick apart an object one field at a time as the transitive closure of the object is dynamically analyzed. This tends to be a slow and cumbersome process, while also requiring large amounts of application and JVM code.

Implementing the Java object compilation/decompilation functionality within the JVM is advantageous because the JVM already understands the concept of, and contents of, an object graph. Thus, the compilation/decompilation functions may leverage the knowledge (and reuse code) of the JVM in parsing the object graph to produce the XML representation, and in parsing the XML representation to produce the object graph. Thus, the compilation/decompilation functions may not have to duplicate functionality that is provided by the JVM, as do object sending methods using reflection and serialization. This may allow the code footprint of the compilation/decompilation functions to be smaller than that of object sending methods using reflection and

serialization. Also, an object may be compiled or decompiled by a single call to the JVM XML compiler/decompiler API.

In addition, integrating the compilation/decompilation of objects with the JVM may allow the compilation and decompilation of objects to be performed faster than methods using reflection and serialization because, in the object traversal model implemented with reflection and serialization, the code outside the JVM does not know the structure or graph of the Java object, and thus must traverse the object graph, pulling it apart, and ultimately must repeatedly call upon the JVM to do the compilation (and the reverse process for decompilation). This process may be slowed by the necessity of making repeated calls to the JVM, outside the code. Having the compilation and decompilation functionality integrated with the JVM, as described herein, avoids having to make repeated calls from code outside the JVM to the JVM. In one embodiment, an object may be compiled or decompiled by a single call to the JVM XML compiler/decompiler API.

In one embodiment, the compilation/decompilation functionality may be implemented as a service in the distributed computing environment. The service may publish a service advertisement in a space. A process in the distributed computing environment may use a search or discovery service to locate the compilation/decompilation service. The process (a client of the service) may then use the service by passing Java objects to be compiled into XML representations and/or XML representations to be decompiled into Java objects to the service.

Java objects may include code (the object's methods) and data. An object's code may be non-transient; the code does not change once the object is created. An object's data, however, may be transient. Two objects created from the same Java class may include identical code, but the data in the two objects may be different. In one embodiment, the compilation function may compile a Java object's data into an XML representation of the object, but may not include the object's actual code in the XML representation. In one embodiment, information about the object may be included in the compiled XML representation to indicate to the receiver how to recreate the code for the object. The XML representation may then be stored in an XML data stream and sent (e.g. in a message) to a receiving process (client or service). The receiving process may then pass the XML data stream to the decompilation function. The decompilation function may then decompile the XML data stream to produce the Java object including its data. In one embodiment, the code for the object may be reproduced by the decompilation function using information about the object included in the XML representation, as the code for an object may be statically defined and the JVM receiving the object may be able to reproduce the code (if necessary) using its knowledge of the object.

In one embodiment, the XML representation of an object produced by the compilation function may include the Java object's data and information about the Java object. The information may include class information for the Java object. An object signature may be included in the information and may be used to identify the object's class, etc. The decompilation function may recreate the code for the Java object using the information about the Java object and may decompile the data from the XML data stream into the Java object. Thus, a complete object including its code and data may be reproduced on the JVM executing the receiving client or service from the decompiled data and the information describing the object. In one embodiment, the information describing the object may be stored in one or more XML tags. In one embodiment, the client or service receiving the XML data stream may include an XML schema that describes the object, and the XML schema may be used to reconstruct the Java object from the decompiled data and from the information about the

Java object. The decompilation process may proceed recursively through the object graph, reconstructing the objects referenced by the object by decompiling the referenced objects' data from the XML data stream and recreating the referenced objects' code from information about the referenced objects in the XML data stream.

In one embodiment, the XML representation of the object produced by the compilation function may include the object's data and information that identifies the code of an object. In one embodiment, the information identifying the code of the object may be stored in one or more XML tags in the XML data stream. When received, the decompilation function may recreate the code for the Java object using the information about the code from the XML data stream and decompile the data for the object from the XML data stream. Thus, a complete object including its code and data may be reproduced on the JVM executing the receiving client or service from the decompiled data and the information describing the code of the object.

Several scenarios of using XML representations of objects to transfer objects between entities (typically clients and services) in a distributed computing environment are included for clarification. These scenarios are exemplary and are not intended to be limiting.

In a first scenario, a service may use the XML compiler/decompiler to compile a Java object into an XML representation of the object and send the XML representation to a client. The client may use the XML compiler/decompiler to decompile the XML representation and perform operations on the data within the object, and later may use the XML compiler/decompiler to compile the object into an XML representation of the object and return the XML representation of the object to the service.

In a second scenario, a service may use the XML compiler/decompiler to compile a Java object into an XML representation of the object and send the XML representation to a client. The client may then send the XML representation to another service, which may use the XML compiler/decompiler to decompile the XML representation to reproduce the object, perform operations on the object at the request of the client (possibly modifying the data), use the XML compiler/decompiler to recompile the modified object into its XML representation, and send the XML representation of the object to the client.

In a third scenario, a service may use the XML compiler/decompiler to compile a Java object into an XML representation of the object and send the XML representation to an object repository or store space. The service may then send a message to a client informing the client of the location of the XML representation. The message may include a Universal Resource Identifier (URI) for the XML representation. The client may then retrieve the XML representation of the object from the store space, and may use the XML compiler/decompiler to decompile the representation to reproduce the object. Alternatively, the client may send the location of the XML representation of the object to another service, along with a request for operations to be performed on the object. The other service may then retrieve the XML representation from the store space, use the XML compiler/decompiler to decompile the XML representation to reproduce the object, and perform the requested operations on the object.

In a fourth scenario, a process (could be a client or service) may locate an object repository or store space in the distributed computing environment by searching for and finding a service advertisement for the store space. The process may, during execution, create or obtain a plurality of Java objects. The process may use the XML compiler/decompiler to compile one or more of the objects into XML representations of the objects, and may

send, as a client of the store space service, the XML representations of the objects to the store space to be stored for possible later access, or for access by other processes.

#### Security issues in the Decompilation of XML Representations of Objects

5 Spaces, as described herein, may serve as a file system in the distributed computing environment. Security may be provided for files in the system in the form of access rights. Access rights may be checked each time a file is accessed (opened, read, or written to). Thus, a method for providing file access security in the distributed computing environment may be desirable. This method may also be applied to the XML representations of Java objects that may be stored in spaces and transmitted between clients and services in the distributed computing environment.

10 In one embodiment, a user of a client on a device in the distributed computing environment may be identified and authenticated when first accessing the client. In one embodiment, the user may supply a physical identification such as a smart card for identification and authorization. In another embodiment, a challenge-response mechanism (such as user ID and password) may be used for identification and authorization. Yet another embodiment may use electronic identification such as a digital signature for identification and authorization. Any other method of identification and authorization may be used.

15 Once identified and authorized, the user may then perform various operations on the client, including accessing one or more services in the distributed computing environment. During these operations, as described above, one or more objects may be created (locally) or acquired from elsewhere (e.g. from services or spaces). The objects may be modified and may be compiled into XML representations of the objects and stored locally by the client or sent to a space service for (transitive or persistent) store. Some of the objects may be received from services (store services or other services) in the form of XML representations of the objects, which may be decompiled by the XML compiler/decompiler to recreate the objects on the client.

20 In one embodiment, during the decompilation of the XML representation of objects, each XML message may be checked to verify that the user has access rights to the object. If the user does not have the proper access rights, the XML compiler/decompiler may not decompile the object for the user. In one embodiment, a security exception may be thrown by the XML compiler/decompiler. In one embodiment, the user may be informed of the access violation.

25 Access right information, such as the creator and access levels allowed (creator-only access, read only, read/write, delete, copy, etc.) for the object may be embedded in the XML message(s) containing the XML representation of the object. Access authorization may be determined during the identification and authorization of the user. For example, the object may allow "read only" access for most users, and "read/write" access for the creator of the object. If the user tries to access an object using read/write access rights, and the user did not create the object, the decompilation process may detect this as an access violation, and may disallow the access and notify the user.

30 In one embodiment, when the user is done using the client, the user may log off or otherwise signal the user is finished with the client (e.g. remove a smart card). Objects created on the client by decompilation may be automatically deleted when the client detects that the user is finished. This may prohibit future users from intentionally or accidentally accessing the user's objects. In one embodiment, all objects created by decompilation

may be deleted upon detecting that the user is finished. In another embodiment, a method may be provided to store at least some of the objects created on the client persistently (e.g. with access rights information), so that the client may later access the objects, or provide the objects to other users for access.

In one embodiment, the user may have a "smart card" or other physical device to gain access to the client.

5 The user may insert the smart card into the client device to begin the session. When the client is finished, the client may remove the smart card. The client may detect the removal of the smart card, and thus detect that the client is finished, and may then proceed to delete objects created by decompilation of XML representations.

Figure 47 illustrates a mechanism for secure object decompilation on a client device. In step 2240, a user may access a client device. In one embodiment, the user may provide identification to the client. In one  
10 embodiment, the user may log on to the client, for example, with a user name and password. In one embodiment, the user may provide a physical identification method, e.g. a smart card, to the client device to establish the user's identity with the device.

After the user has been authenticated, the client may request one or more objects from one or more services during access by the user. In one embodiment, the objects may be Java objects. In one embodiment, the  
15 client may send messages (e.g. an XML messages) to the services requesting the objects. The services, after receiving the requests, may send the data representation language representations of the objects to the client. In one embodiment, the representations may be packaged in messages. Message gates, as described elsewhere herein, may be used for message passing between the client and service.

In step 2242, the client receives the data representation language representations of the objects and  
20 provides the representations to a decompilation process. In one embodiment, the decompilation process may be integrated in the virtual machine within which the client is executing. In one embodiment, the virtual machine may be a Java Virtual Machine (JVM). The decompilation may generate copies of the objects from the data representation language representations of the objects. In one embodiment, the messages may be checked to make sure the client has access privileges to the requested objects. The objects may then be provided to the client to be  
25 available for use during access by the user.

In step 2244, the user may end access to the client device. For example, the user may log off or, if one was used, may remove an identification device such as a smart card to signal to the client device that the user is ending access of the client. Upon detecting that the client has ended the access, the client device may automatically delete any objects that have been decompiled for the user during the access by the user. Deleting the  
30 objects may insure that the objects are not left on the client device to be accidentally or intentionally accessed by subsequent users of the device.

Alternatively, one or more of the objects may not be deleted when the user terminates access. Instead, the objects may be stored (either locally or elsewhere in the distributed computing environment) for later access by the user. In one embodiment, access information of the client may be stored with the objects to prevent unauthorized  
35 users from accessing the objects.

#### XML-based object repositories

In the distributed computing environment, processes (services and/or clients) may desire transient and/or persistent storage of objects such as XML schemas, service advertisements, results generated by services, XML

representations of Java objects and/or objects implemented in other languages, etc. Existing object storage technologies tend to be language and/or operating system specific. These storage systems also tend to be too complicated to be used with small footprint systems such as embedded systems.

JavaSpaces in Jini is an existing object repository mechanism. A JavaSpace may be only capable of storing Java objects and may be too large to be implemented in small devices with limited amounts of memory. Each object in a JavaSpace may be serialized as previously described, and thus has the same limitations as previously described for the reflection and serialization techniques.

A store mechanism may be provided for the distributed computing environment that may be heterogeneous (not language or operating system dependent), that may scale from small to large devices, and that may provide transient or persistent storage of objects. In one embodiment, the store mechanism in the distributed computing environment may be implemented as an Internet Web page or set of pages defined in the XML markup language. XML provides a language- and platform-independent object representation format enabling Java and non-Java software to store and retrieve language-independent objects. Since the store mechanism is on the Web, devices of all types and sizes (small to large) may access the store mechanisms. Web browsers may be used to view the store mechanism implemented as Web pages. Web search engines may be used to search for contents in the store mechanism implemented as Web pages. Internet administration mechanisms (existing and future) and XML tools may be used to administer the XML-based store mechanisms.

In one embodiment, the store mechanisms may be used to store objects created, represented or encapsulated in XML. Examples of objects that may be stored in the store mechanisms may include, but are not limited to: XML schemas, XML representations of objects (for example, Java objects compiled into XML representations as described above), service advertisements, and service results (data) encapsulated in XML. In one embodiment, to prevent unauthorized access of an XML object, an authorization credential such as a digital signature or certificate may be included with the XML object, and a client wishing to access the XML object may be required to have the proper authorization credential to access the XML object. In one embodiment, the store mechanism may be a space as described in the Spaces section herein.

Store mechanisms may be services in the distributed computing environment. A store mechanism implemented as a service may be referred to as a "store service". A store service may publish an advertisement in a space. The space itself is an example of a store service. Some store services may be transient. For example, a space service that stores service advertisements may be a transient store. Other store services may be persistent. For example, a store service that stores results from services may be a persistent store.

Figure 36 illustrates a client 1604 and a service A 1606 accessing store mechanisms 1600 and 1602 in the distributed computing environment according to one embodiment. This illustration is intended to be exemplary and is not intended to be limiting to the scope of this invention. In one embodiment, store mechanisms 1600 and 1602 may each be an Internet Web page or set of Web pages defined in XML and accessible by a Web browser and other Internet tools. Store mechanism 1600 is a transient store capable of storing objects implemented using XML. Store mechanism 1602 is a persistent store also capable of storing objects implemented using XML. Service A 1606 may publish an XML service advertisement 1608 in transient store 1600. Persistent store may also publish an XML service advertisement in transient store 1600 (or on another transient store in the distributed computing environment). At some point, client 1604 may require functionality provided by Service A 1606.

Client 1604 may use a discovery and/or lookup service to locate service advertisement 1608. Client 1604 may then construct a message gate, as described herein, and begin communications with Service A 1606. Client 1604 may send one or more XML request messages to Service A 1606. Service A 1606 may perform one or more functions in response to the one or more request messages. One or more of the functions performed by Service A 1606 may produce results to be provided to client 1604.

For transient results 1610, Service A 1606 may encapsulate the results in an XML advertisement 1612 and publish the advertisement 1612 in transient store 1600 (or on another transient store in the distributed computing environment). Service A 1606 may then notify client 1604 that the results 1610 are stored in advertisement 1612 on transient store 1600, or client 1604 may be notified by other mechanisms as described herein. Client 1604 may then retrieve transient results 1610 from advertisement 1612. The advertisement 1612 may include an XML schema describing the formatting, contents, type, etc. of the transient results 1610. The results may be encapsulated in XML. For example, XML tags may be used to describe portions of the data:

<XML tag1> <data1>

<XML tag2> <data2>

....

For persistent results 1618, Service A 1606 may use a service or other mechanism as described herein to locate XML service advertisement 1616 for persistent store 1602, and thus locate persistent store 1602 for storing persistent results. Alternatively, client 1604 may have previously located persistent store 1602 by locating its service advertisement 1616, and then may send a Universal Resource Identifier (URI) for a storage location for persistent results 1618 to Service A in an XML message. In one embodiment, persistent results 1618 may be stored in an Internet Web page or set of Web pages defined in XML and accessible by a Web browser. Service A 1606 may then store persistent results 1618 in persistent store 1602. Service A 1606 may then publish an XML advertisement 1616 for the persistent results 1618 in transient store 1600 (or on another transient store in the distributed computing environment) and return the location of the advertisement 1616 to client 1604. The advertisement 1616 may include an XML schema describing the formatting, contents, type, etc. of the persistent results 1618. The results may be encapsulated in XML as previously described. The advertisement may also include the URI of the persistent results 1618. The client 1604 may then retrieve the advertisement 1616 and use it to locate and retrieve persistent results 1618. Alternatively, Service A 1606 may not publish an advertisement for persistent results 1618, but instead may return a URI for the persistent results 1618 to client 1604 so client 1604 may access the results without looking up an advertisement. Note in some embodiments, the various advertisements shown in transient store 1600 may each be stored in different transient stores or spaces.

Thus, store mechanisms may be implemented as XML-based Internet Web pages in the distributed computing environment. These store mechanisms may be implemented on a variety of devices in the environment, and may provide service advertisements to allow clients (which may be other services) to locate and use the store mechanisms. Existing and future Web and XML tools may be used to manage the store mechanisms. The store mechanisms may store objects of various types implemented or encapsulated in XML. Clients on devices of substantially any size, from small footprint devices to supercomputers, may access the store mechanisms to store and retrieve the various objects on the Internet. The clients may be Java or non-Java applications, as XML provides a language-independent storage format. The transient or persistent object repositories may provide for a



file system in the distributed computing environment and may include access checks and other security mechanism as described herein.

#### Dynamically Converting a Java Object into an XML Document

In one embodiment, the distributed computing environment may provide a mechanism to convert and represent an object class instance into an XML document. In order to send representation of a class instance to another service, the object may be converted and represented as an XML document. In one embodiment, when receiving an XML document, a program may instantiate a class instance corresponding to the object represented by the document. In one embodiment, the objects may be Java objects, and the program may be a Java program.

In one embodiment, an intermediary format may be used to represent an XML document and may be dynamically processed to generate a class instance that represents the XML document. The class may define a set of instance variables and "set and get" methods to access the instance variables. A corresponding XML document may be defined as a set of tags, with one tag for each instance variable. When the document is parsed, a hashable representation may be constructed where the hash key may include the instance variable name and the value may include the instance variable value. If there are multiple occurrences of a complex instance variable, an enumeration value may be stored in a hash table. In one embodiment, the process may be limited to only one level of complex types for the instance variables, and the elements may be homogeneous.

In one embodiment, a protected instance variable may be added to the class definition that may include the name of the corresponding class. The XML document representation may use the class name as the document type. Having the class name embedded in the document may allow dynamic instantiation of the right class instance when the object is reconstructed.

In one embodiment, upon receiving a document, a class instance generator method may be used to extract the class type and to parse the document to generate the intermediary hash table representation. The generator method may instantiate a new class instance and may use the set methods to initialize the instance object from the hash table values. In one embodiment, since the class type is defined and the hash table is generic, this process may be performed for any class that matches the above class definition.

In one embodiment, the reverse process may also be performed where a class instance may be processed into the intermediary hash table representation and a generator method may be used to produce an XML document from the hash table representation. This process may also be made generic so that it may be performed for any XML document that matches the above specification.

This method is not intended to be limited to Java Class objects, and may be applied to other computer-based objects, including class object instances of other programming languages. In addition, the method is not intended to be limited to XML representations of object instances; other representation formats including other data representation languages (such as HTML) may be substituted for XML.

#### XML-Based Process Migration

The distributed computing environment may enable the distribution and management of distributed applications. For example, the distributed computing environment may include mobile clients that are dockable with stations that provide monitors, printers, keyboards, and various other input/output devices that are typically not provided on mobile devices such as PDAs, cell phones, etc. These mobile clients may run one or more

applications, and may migrate from one station to another in the distributed computing environment. Thus, one embodiment of the distributed computing environment may provide a method for migrating an executing application (process) with its entire current state from a mobile client on one node to the same mobile client or another mobile client at another node within the distributed computing environment.

5 In one embodiment, an XML representation of the state of a process executing on a client or service may be created. In one embodiment, the XML representation of the state of the process may include a computation state of the device and/or virtual machine on which the process is executing, wherein the computation state of the device and/or virtual machine comprises information about the execution state of the process on the device and/or virtual machine. A process state may include, but is not limited to: threads, all objects referenced by the threads,  
10 transient variables created during the execution of the process, objects and their data, etc. In one embodiment, data describing one or more leases representing grants of access to external services, obtained from spaces by the process, wherein the one or more external services are external to the device and/or virtual machine on which the process is executing, may also be represented in XML and stored with the process state. Leases are described in more detail in the Leases section of this document.

15 Using XML and the messaging system as described herein, an XML representation of the state of a process may be moved from node to node within the distributed computing environment, e.g. from node to node on the Internet. The XML representation of the state of a process may also be stored as an XML object in an XML-based store mechanism as described above, and later retrieved from the store mechanism to resume the process execution on the same node or on a different node in the distributed computing environment. In one  
20 embodiment, the XML object compilation/decompilation process as described herein may be used in creating (compiling) an XML representation of the state of a process and in regenerating the state of the process by decompiling the XML representation of the state of the process.

Using this mechanism, an XML representation of the state of a process may be stored in an XML-based store mechanism, such as a space, from an initial node. Subsequently, another node may locate the stored state of  
25 the process, download the state of the process, and resume the process from the downloaded stored state at the point at which it was executing when the state was stored. Since the process state is stored in an XML format, the tools and search facilities described herein to store, locate and retrieve XML objects in XML-based store mechanisms may be used to enable the migration of the process. An advertisement of the stored XML representation of the state of the process may be published to allow a client resuming the process execution on the  
30 same node or another node to locate and access the stored state.

The XML representation of the state of a process may be stored to an XML-based persistent store mechanism, and thus may provide a persistent snapshot of the process. This may be used as a method to resume process execution on a node after the interruption of the process on the node, for example, due to the intentional or unintentional shutdown of the node. An advertisement of the stored state of the process may be published to allow  
35 clients to locate the stored state in the distributed computing environment. In one embodiment, to prevent unauthorized access of an XML representation of the stored state of a process, an authorization credential such as a digital signature or certificate may be included with the stored state, and a client wishing to resume a process from the stored state may be required to have the proper authorization credential to access the stored state.

Figure 37 illustrates process migration using an XML representation of the state of a process according to one embodiment. Process A 1636a may be executing on node 1630. Process A 1636a may be a client or service. At some point during the execution of Process A 1636a, the state of execution of Process A 1636a may be captured and stored in an XML-encapsulated state of Process A 1638. The execution of Process A 1636a on node  
5 1630 may then be stopped. Later, node 1632 may locate the XML-encapsulated state of Process A 1638 and use it to resume Process A 1636b on the node 1632. Resuming Process A may include using the stored state 1638 to resume thread execution, recalculate transient variables, re-establish leased resources, and perform any other functions necessary to resume execution as recorded in the stored XML state of the process 1638.

The following is an example of using XML-based process migration in the distributed computing  
10 environment, and is not intended to be limiting. A mobile client device may be connected to node 1630 and executing Process A 1636a. The user of the mobile client device may desire to stop execution of Process A 1636a on node 1630, and to resume execution at a later time at another (or the same) node. In one embodiment, the user may be prompted with a query to determine if the user wishes to store the state of Process A 1636a and resume execution later. If the user replies in the affirmative, the XML-encapsulated state of the process may be captured  
15 and stored in persistent store 1634. Later, the user may connect the mobile computing device at node 1632. In one embodiment, the user may then execute process 1636b and select a "Resume from Stored State" option. The node 1632 may then search for and locate the XML-encapsulated state of Process A 1638, download it, and use it to resume Process A 1636b. Alternatively, the process may itself know that it was "suspended" on another node, and may resume from the stored state without user input.

Figure 48 illustrates a mechanism for migrating processes using data representation language (such as XML) representations of the processes in a distributed computing environment. In step 2260, a process is executing within a first device. In step 2262, a current computation state of the process is converted into a data representation language representation of the current computation state, wherein the computation state of the process comprises information about the execution state of the process within the first device. This information  
25 may include, but is not limited to, information about one or more threads of the process, information about one or more leases to services held by the process, and information about one or more objects of the process (such as objects held by the threads), wherein an object is an instance of a class in a computer programming language (such as the Java programming language).

In step 2264, the data representation language representation of the current computation state of the  
30 process may be stored. In one embodiment, the representation may be stored locally. In one embodiment, the data representation language representation of the current computation state of the process may be stored to a space using a space service. In one embodiment, the data representation language representation of the current computation state of the process may be sent to the space service in one or more messages.

In step 2266, a second device may access the stored data representation language representation of the  
35 current computation state of the process. In one embodiment, an advertisement may be provided for the stored data representation language representation, and the second device may receive or access the advertisement and use information in the advertisement to locate and access the stored data representation language representation. In step 2268, the process may be reconstituted at the current computation state within the second device from the

accessed data representation language representation of the current computation state of the process. The process may then resume execution within the second device from the current computation state.

Alternatively, the process execution may be ended on the first device subsequent to step 2264. The first device may then subsequently access the stored data representation language representation of the current computation state of the process. The process may then be reconstituted at the current computation state within the first device from the data representation language representation of the current computation state of the process and execution of the process may be resumed within the first device from the current computation state.

In another alternative, the data representation language representation of the current computation state of the process generated at step 2262 may be sent directly to the second device (e.g. in one or more data representation language messages through message gates). The process may then be reconstituted at the current computation state within the second device from the received data representation language representation of the current computation state of the process. The process may then resume execution within the second device from the current computation state.

## Applications

Technologies exist that allow a user to access network data from remote locations, making the remote data appear as local data to the user, provided the user has access to a browser. However, such technologies do not provide an automatic infrastructure to query networks near a client device's location. A mechanism for discovering information about networks and services near a client device may be desirable. For example, such a mechanism may be used to locate information about restaurants, weather, maps, traffic, movie information, etc within a certain distance (radius) of the client device, and to display desired information on the client device. An example of using this mechanism may be a cell phone that can be used to automatically locate services in a local environment, for example, in a movie theater to display the titles and show times of current features in the movie theater or in a restaurant to view menu selections and prices. In the distributed computing environment as described herein, such a mechanism may be used to discover spaces including local information and/or services proximate to the client device. The mechanism may also be applied in other distributed computing environments, for example, the Jini system from Sun Microsystems, Inc.

In one embodiment, a mobile client device may include Global Positioning System (GPS) capability and wireless connection technology. Local distributed computing networks may be provided. For example, a city may provide a citywide distributed computing environment. Another example may be a shopping mall with a local distributed computing environment. A local distributed computing network may include a discovery mechanism to allow client devices to connect to the distributed computing environment and to discover services and data in the local environment. For example, one or more devices in the environment may include wireless connection technology to allow mobile client devices to connect to the network and to access the discovery mechanism via the XML messaging system as described previously. A local distributed computing environment may include one or more spaces with advertisements for services and/or data to be made available to mobile clients. For example, a citywide distributed computing environment may include spaces that represent entities such as malls, movie theaters, local news, local weather, traffic, etc. A space may include individual service and/or data advertisements for accessing services of and information about the entity the space represents. The discovery mechanism may

include a GPS location or locations of the local distributed computing environment, entities represented by space services within the environment, and/or the various services advertised in the spaces in the environment.

In one embodiment, wired connections may be provided to a local distributed computing network. In this environment, a user with a mobile client device may “plug in” directly to the network using a wired connection “docking station”. Examples of wired connections include, but are not limited to: Universal Serial Bus (USB), FireWire, and twisted-pair Internet. In one embodiment, a docking station may also provide input/output capabilities such as a keyboard, mouse, and display for the mobile client device. In this embodiment, the location of the mobile client device may be provided to the lookup or discovery mechanism by the docking station.

In one embodiment, a mobile client device may connect to a distributed computing network. As the user of the mobile client device navigates within wireless communications range of the distributed computing network, the mobile client device may constantly, or at various intervals, provide a location vector as input to the local lookup or discovery mechanism. The mobile client device may obtain the location vector from a GPS system built into or associated with the mobile client. In one embodiment, the client may send its location information (e.g. via XML messaging) to a local service discovery mechanism, such as one of the space location mechanisms described herein. For example, the client may run the space discovery protocol specifying discovery for spaces offering services within a certain range of the client’s location, or the client may instantiate a space search service to search for spaces advertising services provided for the client’s vicinity.

As the mobile client device moves into a specified range of a space within the distributed computing environment, the services and/or data stored in the space may be made available to the mobile client device. In embodiments where the client device regularly provides its location to a discovery mechanism, local services and/or data may automatically be made available to the client’s user. In one embodiment, the user of the mobile client device may determine the specified range of a space. For example, the user may choose to display all restaurants within one mile of a current location. Alternatively, the range may be specified in the configuration of the local distributed computing network. For example, a citywide distributed computing network may be configured to provide its services to all users within three miles of the city limits. In one embodiment, visual indicators, for example icons, representing the various services and/or data offered by the space may be displayed on the mobile client device. The client may then access one or more of the displayed services and/or data. In one embodiment, information from two or more spaces may be displayed simultaneously on the mobile client device. In one embodiment, the user may select what services and/or data are to be detected. For example, in a shopping mall, a user with a mobile client device may choose to display all shoe stores in the mall.

In one embodiment, executable code and/or data used in the execution of the code may be downloaded to the mobile client device to allow the user to execute an application provided by a service in the space. For example, moviegoers with mobile client devices may download interactive movie reviews from services in a space for the movie theater, and may thus perform real-time feedback about the movie they are watching. In one embodiment, an XML object compilation/decompilation mechanism as described elsewhere herein may be used to compile the code and/or data to produce XML representations of the code and/or data, and to decompile the XML representations to reproduce the code and/or data on the mobile client device. In one embodiment, an executable version of a process may previously exist on the mobile client device, and a stored state of the process may be downloaded to the mobile client device to allow the user to execute the process using the stored state. In one

embodiment, an executable version of a process may previously exist on the mobile client device, and data for the process may be downloaded to the mobile client device. For example, data may be downloaded for viewing with a viewer program on the mobile client device. In one embodiment, an executable version of a process, including the code and data for executing the process, may be downloaded for execution on the mobile client device. In one  
5 embodiment, the service may execute the application remotely on behalf of the mobile client device, and the service and client may pass to each other XML messages including data and optionally XML schemas describing the data. In one embodiment, some code may be executed on the service and some on the client. For example, the service may execute code to perform operations on a set of data such as numerical calculations. The mobile client device may execute code that may display portions of the data passed to the client from the service in XML  
10 messages and allow the user of the mobile client device to enter and/or select data and send the data to the service for performing one or more operations on the data.

In one embodiment, a mobile client device may be connected to two or more services in the distributed computing network simultaneously. The services may be used independently or in conjunction for performing a series of tasks. For example, one service may be used by a remote client device to locate and/or perform  
15 operations on a set of data, and a second service may be used to print the set of data.

Figure 38 illustrates a mobile client device accessing spaces in a local distributed computing network, according to one embodiment. A user of GPS-enabled mobile computing device 1700 may move into proximity of a local distributed computing environment. The mobile client device 1700 may provide its location provided by GPS 1702 to one or more discovery mechanisms 1706 in the local distributed computing network. The discovery  
20 mechanism 1706 may use the provided GPS location of the mobile client device and predetermined locations of spaces within the environment to determine when the user moves within a specified range of one or more spaces or a vicinity served by one or more spaces within the environment. For example, discovery mechanism 1706 may determine that mobile client device 1700 has moved within range of space 1704. Discovery mechanism 1706 may then provide one or more advertisements 1710 from space 1704 to the mobile client device 1700. Alternatively,  
25 discovery mechanism 1706 may provide a Universal Resource Identifier (URI) for space 1704, or for one or more advertisements in space 1704, to mobile client device 1700. Icons representing the various services advertised by service advertisements 1708 and/or data represented by content advertisements 1710 may then be displayed on mobile client device 1700. The user may then select one or more of the advertised services and/or data for execution and/or display on the mobile client device. The mobile computing device 1700 may establish a wireless  
30 connection with the device offering the service and communicate with the device to execute the service using the XML-based messaging system as previously described herein. Alternatively, the user of the mobile computing device 1700 may connect the device at a docking station. The location of the docking station may have been discovered by the user using the lookup or discovery mechanism 1706, and spaces containing advertisements for the docking stations to discover the location and availability of docking stations within a specified range of the  
35 user.

Discovery mechanism 1706 may also detect when mobile client device 1700 moves into a selected range of space 1714. The various service advertisements 1718 and content advertisements 1720 may then be made available to the user of the mobile client device 1700. When the mobile client device moves out of the specified

range of one of the spaces, the advertisements offered by that space may be removed from the mobile client device 1700's display.

In one embodiment, advertisements on a space may include location information for the services or data that they provide. Thus, discovery mechanism 1706 may determine when mobile client device 1700 moves within a specified range of a particular service advertised on space 1718, and may provide (or remove) the service advertisement based upon the location of the mobile client device 1700.

Computing devices are shrinking while at the same time gaining power and functionality. Storage devices, CPUs, RAM, I/O ASICS, power supplies, etc. have been reduced in size to where small, mobile client devices may include much of the functionality of a full-sized personal computer. However, some components of a computer system are not easily shrinkable because of the human factor and other factors. These components include, but are not limited to: keyboards, monitors, scanners, and printers. The limits on reducing the size of some components may prevent mobile client devices from truly assuming the role of personal computers.

In one embodiment, docking stations may be provided that allow users with mobile client devices to connect to and use components that are not available on the mobile client device because of human or other factors. For example, docking stations may be provided in public places such as airports or libraries. The docking stations may provide monitors, keyboards, printers or other devices for users with mobile client devices. In one embodiment, the docking stations may not fully function without help from a real computing device such as a mobile client device connected by a user. The docking station may provide services such as various input/output functions to the client using the computing power of the mobile client device.

A docking station may provide one or more connection options to a mobile client device. The connection options may include wireless connections and wired connections. Examples of wireless connections include, but are not limited to: infrared such as IrDA and wireless network connections similar to those provided by a network interface card (NIC) in a notebook computer. Examples of wired connections include, but are not limited to: USB, FireWire, and twisted-pair Ethernet.

A mobile client device may discover the location of docking stations using a method substantially similar to that described above for mobile client devices. The location of one or more docking stations in a local distributed computing network may be discovered using a discovery mechanism to discover spaces with advertisements for docking stations. The mobile client device may provide a location to the discovery mechanism. In one embodiment, the discovery mechanism or a lookup mechanism may return the location of one or more docking stations closest to the location of the mobile client device. Alternatively, the discovery mechanism or lookup mechanism may return a URI of the space containing the advertisements for the docking stations, and the mobile client device may then connect with the space to provide the location of the one or more docking stations near the device. In one embodiment, the mobile client device may supply information to the lookup or discovery mechanism to specify requirements such as monitor resolution, screen size, graphics capabilities, available devices such as printers and scanners, etc. In one embodiment, information about the one or more docking stations may be supplied to the user on the mobile client device including availability (is another user using the docking station), components and capabilities of the various docking stations.

When a user approaches a docking station, a claiming protocol may be initiated. When the docking station accepts the claim, secure input and output connections may be established between the mobile client device

and the docking station. Alternatively, the user may select the docking station from one or more docking stations discovered using the lookup or discovery mechanism displayed on the mobile client device. When the user selects the docking station, the claiming protocol may be initiated to give the user secure, exclusive connection to the docking station for the duration of the claim. A docking station release method may also be provided to allow the user to terminate the session on the docking station and release the docking station for use by other users. In one embodiment, the claiming protocol may be a lease on the docking station service as described previously herein.

Figure 39a illustrates a user of a mobile device discovering the location of docking stations according to one embodiment. Mobile client device 1750 may connect with discovery mechanism 1756. Mobile client device 1750 may provide a location obtained using GPS 1752 to discovery mechanism 1756. Mobile client device 1750 may also provide docking station requirements to discovery mechanism 1756. Discovery mechanism 1756 may search one or more spaces 1754 for advertisements for docking stations 1758 that meet the requirements of mobile client device 1750. In one embodiment, a lookup or discovery mechanism may locate one or more docking stations within a specified range of mobile device 1750 by comparing location information stored in advertisements 1758 with the supplied location of mobile device 1750. Discovery mechanism 1756 may then provide the location of one or more docking stations within a specified range of mobile client device 1750. Alternatively, discovery mechanism 1756 may locate a nearest docking station to mobile client device 1750 and provide the location to mobile client device 1750.

Figure 39b illustrates a mobile client device 1750 connecting to a docking station 1760, according to one embodiment. In one embodiment, the user may move mobile client device 1750 into wireless range of docking station 1760 and make a wireless connection to the docking station 1760. In another embodiment, the user may establish a wired connection to docking station 1760 by connecting one or more cables between docking station 1760 and mobile client device 1750. In one embodiment, the user of the mobile client device 1750 may establish a claim to the docking station 1760. The claim may establish secure, exclusive rights to the docking station for the duration of the connection. In one embodiment, the claim mechanism may be a lease mechanism for a resource (the docking station) as described previously herein. In one embodiment, a user may be billed for use of the docking station. For example, the user may supply a credit card number as part of the process of claiming a docking station. Refer to the description of bill gates in the Message Gates section herein. Once connected, the user may use the various facilities provided by the docking station 1760 such as keyboard, monitor, printer, etc. Docking station 1760 may also include a connection to a local distributed computing network and thus may provide the user of the mobile client device 1750 connected to the docking station 1760 with discovery services for locating service and content advertisements on other devices within the network, allowing the user to locate and use various services and content in the distributed computing environment as described previously herein.

When finished, the user may disconnect the mobile client device 1750 from the docking station 1760. In one embodiment, a docking station release mechanism may automatically be initiated when the mobile client device 1750 is disconnected from the docking station 1750. The release mechanism may clear any claim on the docking station 1760 established by the user of the mobile client device 1750. In one embodiment, the release mechanism may notify the discovery mechanism 1756 and/or docking station advertisement 1758 that the docking station is available.



In one embodiment, a user may connect a mobile client device to a docking station without using the discovery mechanism. For example, a user in an airport may visually detect a docking station and connect a mobile client device to it. Another example may be a library providing a docking station room with a plurality of docking stations for use, where users may access any of the docking stations that are available.

## WHAT IS CLAIMED IS

1. A method for remotely invoking functions in a distributed computing environment, comprising:  
a client generating a message, wherein the message includes information representing a computer  
programming language method call;  
the client sending the message to a service, wherein the service is configured to perform functions on  
behalf of the client; and  
the service performing a function on behalf of the client in accordance with the information representing  
the computer programming language method call included in the message.
2. The method as recited in claim 1, wherein the service performs the function on behalf of the client  
asynchronously to processing on the client.
3. The method as recited in claim 1, wherein the client comprises a client method gate, wherein said  
generating a message comprises:  
the client method gate receiving the computer programming language method call from a process  
executing within the client; and  
the client method gate generating the message for the client.
4. The method as recited in claim 3, wherein said sending the message comprises the client method gate  
sending the message to the service.
5. The method as recited in claim 4, wherein the process is executing within a virtual machine, wherein the  
virtual machine is executing within a client device in the distributed computing environment.
6. The method as recited in claim 5, wherein the virtual machine is a Java Virtual Machine (JVM).
7. The method as recited in claim 1, wherein the service comprises one or more computer programming  
language methods executable within the service, wherein said performing a function comprises executing a  
computer programming language method in accordance with the information representing the computer  
programming language method call included in the message.
8. The method as recited in claim 1, wherein the service comprises one or more computer programming  
language methods executable within the service, wherein the information representing the computer programming  
language method call includes an identifier of the method call, and wherein said performing a function comprises:  
regenerating the method call in accordance with the identifier of the method call included in the  
information representing the method call; and  
executing a computer programming language method in accordance with the regenerated method call.

9. The method as recited in claim 8, wherein the information representing the computer programming language method call further includes one or more parameter values of the method call, and wherein said executing a computer programming language method in accordance with the regenerated method call comprises providing the one or more parameter values from the information representing the method call as parameter values of the method call.

10. The method as recited in claim 8, wherein the service comprises a service method gate configured to provide an interface to computer programming language methods of the service by receiving messages and invoking methods specified by the messages, and wherein said regenerating the method call is performed by the service method gate.

11. The method as recited in claim 1, wherein said performing a function generates results data, the method further comprising the service providing the generated results data to the client.

12. The method as recited in claim 1, wherein said performing a function generates results data, the method further comprising:

storing the generated results data to a space service in the distributed computing environment;

providing an advertisement for the stored results data to the client, wherein the advertisement comprises information to enable access by the client to the stored results data; and

the client accessing the stored results data from the space service in accordance with the information in the provided advertisement.

13. The method as recited in claim 12, wherein the client accessing the stored results data comprises:

generating a client results message endpoint in accordance with the information in the provided advertisement, wherein the client results message endpoint is configured to send messages to the space service for the client;

generating a results request message, wherein the results request message requests a portion of the results data to be provided to the client;

the client results message endpoint sending the results request message to the space service; and

the space service sending the requested portion of the results data to the client results message endpoint in response to receiving the results request message.

14. The method as recited in claim 13, wherein the results request message is received on the space service by a space service results message endpoint, and wherein the space service sending the requested portion of the results to the client results message endpoint comprises:

generating a results response message, wherein the results response message includes the requested portion of the results; and

the space service results message endpoint sending the results response message to the client results message endpoint.

15. The method as recited in claim 12, wherein the information to enable access by the client to the stored results comprises one or more Uniform Resource Identifiers (URIs) for accessing the stored results.

16. The method as recited in claim 1, wherein said computer programming language is the Java programming language, and wherein the information representing the method call in the message represents a Java method call to a Java method implemented on the service, and wherein the service performing a function comprises invoking the Java method on the service in accordance with the information representing the Java method call included in the message.

17. A distributed computing system comprising:

a service device configured to execute functions on behalf of clients of the service device;

a client device configured to:

generate a message, wherein the message includes information representing a computer programming language method call; and

send the message to the service device;

wherein the service device is configured to:

receive the message sent by the client device; and

perform a function on behalf of the client device in accordance with the information representing the computer programming language method call included in the message.

18. The system as recited in claim 17, wherein the service device performs the function on behalf of the client device asynchronously to processing on the client device.

19. The system as recited in claim 17, wherein the client device comprises a client method gate executable within the client device, and wherein the client method gate is configured to:

receive the computer programming language method call from a process executing within the client device; and

wherein said generating the message is performed on the client device by the client method gate, and

wherein the information in the message represents the method call received from the process.

20. The system as recited in claim 19, wherein the client method gate is further configured to send the message to the service for the client device.

21. The system as recited in claim 19, wherein the client device further comprises a virtual machine executable within the client device, wherein the process is executing within the virtual machine.

22. The system as recited in claim 21, wherein the virtual machine is a Java Virtual Machine (JVM).

23. The system as recited in claim 17, wherein, in said performing a function, the service device is further configured to execute a computer programming language method in accordance with the information representing the computer programming language method call included in the message.

5 24. The system as recited in claim 17, wherein, in said performing a function, the service device is further configured to:

regenerate the computer programming language method call in accordance with an identifier of the  
method call included in the message; and

execute a computer programming language method in accordance with the regenerated method call.

10 25. The system as recited in claim 24, wherein, in said executing a computer programming language method, the service device is further configured to provide one or more parameter values included in the message as parameter values of the method call.

15 26. The system as recited in claim 17, wherein said performing the function generates results data, and wherein the service device is further configured to provide the generated results data to the client device.

27. The system as recited in claim 17, further comprising:

20 a space service device configured to receive and store results data from service devices in the distributed computing system;

wherein said performing the function generates results data, and wherein the service device is further configured to:

store the results data to the space service device; and

25 provide an advertisement for the stored results data to the client device, wherein the advertisement comprises information to enable access by the client device to the stored results data.

28. The system as recited in claim 27, wherein the client device is further configured to access the stored results data from the space service device in accordance with the information in the provided advertisement for the  
30 stored results data.

29. The system as recited in claim 28, wherein, in said accessing the stored results data, the client device is further configured to:

35 generate a client results message endpoint in accordance with the information in the provided advertisement, wherein the client results message endpoint is executable within the client device, wherein the client results message endpoint is configured to:

generate a results request message, wherein the results request message requests a portion of the results data be provided to the client device; and

send the results request message to the space service device.

30. The system as recited in claim 29, wherein the space service device comprises a space service results message endpoint executable within the space service device and configured to:

receive the results request message; and

5 send a results response message to the client results message endpoint, wherein the results response message includes the requested portion of the results data.

31. The system as recited in claim 27, wherein the information to enable access comprises one or more Uniform Resource Identifiers (URIs) for accessing the stored results.

10 32. The system as recited in claim 17, wherein said computer programming language is the Java programming language, and wherein the information representing the method call in the message represents a Java method call to a Java method implemented on the service, and wherein, in said performing a function, the service device is further configured to invoke the Java method on the service device in accordance with the information  
15 representing the Java method call included in the message.

33. A device comprising:

a client component; and

a method gate;

20 wherein the client component is configured to:

generate a computer programming language method call;

wherein the method gate is configured to:

access the computer programming language method call generated by the client component;

25 generate a message, wherein the message includes information representing the computer programming language method call; and

send the message to a service in a distributed computing environment;

wherein the service is operable to perform a function on behalf of the client component in accordance with the information representing the computer programming language method call included in the message.

30 34. The device as recited in claim 33, wherein the service is further operable to perform the function on behalf of the client component asynchronously to processing of the client component.

35 35. The device as recited in claim 33, wherein the device further comprises a virtual machine executable within the device, wherein the client component and the method gate are executable within the virtual machine.

36. The device as recited in claim 35, wherein the virtual machine is a Java Virtual Machine (JVM).

37. The device as recited in claim 33, wherein the service is further operable to store results data generated by the function to a space service in the distributed computing environment, and wherein the client component is further configured to:

access an advertisement for the results data, wherein the advertisement comprises information to enable  
access by the client component to the results data; and  
access the results data from the space service in accordance with the information in the provided  
advertisement for the stored results data.

38. The device as recited in claim 33, wherein said computer programming language is the Java programming language, and wherein the information representing a method call in the message represents a Java method call to a Java method implemented on the service.

39. A device comprising:

a client component configured to generate a message, wherein the message includes information  
representing a computer programming language method call; and  
a message endpoint configured to send the message to a service in a distributed computing environment;  
wherein the service is operable to perform a function on behalf of the client component in accordance  
with the information representing the computer programming language method call included in  
the message.

40. The device as recited in claim 39, wherein the service is further operable to perform the function on behalf of the client component asynchronously to processing of the client component.

41. The device as recited in claim 39, wherein the client component is further configured to generate the computer programming language method call, and wherein said generating a message is performed in response to said generating the computer programming language method call.

42. The device as recited in claim 39, wherein the device further comprises a virtual machine executable within the device, wherein the client component and the message endpoint are executable within the virtual machine.

43. The device as recited in claim 42, wherein the virtual machine is a Java Virtual Machine (JVM).

44. The device as recited in claim 39, wherein the service is further operable to store results data generated by the function to a space service in the distributed computing environment, and wherein the client component is further configured to:

access an advertisement for the results data, wherein the advertisement comprises information to enable  
access by the client component to the results data; and

access the results data from the space service in accordance with the information in the provided advertisement for the stored results data.

45. The device as recited in claim 39, wherein said computer programming language is the Java programming language, and wherein the information representing a method call in the message represents a Java method call to a Java method implemented on the service.

46. A device comprising:

a message endpoint configured to receive a message sent by a client of the device in a distributed computing environment, wherein the message includes information representing a computer programming language method call; and

a service component configured to:

perform a function on behalf of the client in accordance with the information representing the computer programming language method call included in the message;

store results data generated by said performing a function to a space service in the distributed computing environment; and

provide an advertisement for the stored results data to the client, wherein the advertisement comprises information to enable access by the client to the stored results data.

47. The device as recited in claim 46, wherein the service component performs the function on behalf of the client asynchronously to processing on the client.

48. The device as recited in claim 46, wherein the service component comprises a computer programming language method,

wherein the message endpoint is further configured to:

regenerate the computer programming language method call in accordance with an identifier of the method call included in the message; and

invoke the computer programming language method of the service component with the regenerated method call;

wherein, in said performing a function, the service component is further configured to execute the computer programming language method in accordance with the regenerated method call in response to said invocation.

49. The device as recited in claim 48, wherein, in said invoking the computer programming language method, the message endpoint is further configured to provide one or more parameter values included in the message as parameter values of the method call.

50. The device as recited in claim 46, wherein said computer programming language is the Java programming language.



51. A carrier medium comprising program instructions, wherein the program instructions are computer-executable to implement:

a client generating a message, wherein the message includes information representing a computer programming language method call;

the client sending the message to a service, wherein the service is configured to perform functions on behalf of the client; and

the service performing a function on behalf of the client in accordance with the information representing the computer programming language method call included in the message.

52. The carrier medium as recited in claim 51, wherein the service device performs the function on behalf of the client device asynchronously to processing on the client device.

53. The carrier medium as recited in claim 51, wherein the client comprises a client method gate, wherein, in said generating a message, the program instructions are further computer-executable to implement:

the client method gate receiving the computer programming language method call from a process executing within the client; and

the client method gate generating the message for the client.

54. The carrier medium as recited in claim 53, wherein the process is executing within a virtual machine, wherein the virtual machine is executing within a client device in the distributed computing environment.

55. The carrier medium as recited in claim 54, wherein the virtual machine is a Java Virtual Machine (JVM).

56. The carrier medium as recited in claim 51, wherein the information representing the computer programming language method call includes an identifier of the method call, and wherein, in said performing a function, the program instructions are further computer-executable to implement:

regenerating the method call in accordance with the identifier of the method call included in the information representing the method call; and

executing a computer programming language method in accordance with the regenerated method call.

57. The carrier medium as recited in claim 56, wherein the information representing the computer programming language method call further includes one or more parameter values of the method call, and wherein, in said executing a computer programming language method in accordance with the regenerated method call, the program instructions are further computer-executable to implement providing the one or more parameter values from the information representing the method call as parameter values of the method call.

58. The carrier medium as recited in claim 51, wherein the program instructions are further computer-executable to implement:

storing results data from said performing a function to a space service;  
providing an advertisement for the stored results data to the client, wherein the advertisement comprises  
information to enable access by the client to the stored results data; and  
the client accessing the stored results data from the space service in accordance with the information in  
5 the provided advertisement.

59. The carrier medium as recited in claim 58, wherein, in the client accessing the stored results data, the program instructions are further computer-executable to implement:

generating a client results message endpoint in accordance with the information in the provided  
10 advertisement, wherein the client results message endpoint is configured to send messages to  
the space service for the client;

generating a results request message, wherein the results request message requests a portion of the results  
data to be provided to the client;

the client results message endpoint sending the results request message to the space service; and

15 the space service sending the requested portion of the results data to the client results message endpoint in  
response to receiving the results request message.

60. The carrier medium as recited in claim 51, wherein said computer programming language is the Java  
programming language, and wherein the information representing the method call in the message represents a Java  
20 method call to a Java method implemented on the service, and wherein, in said performing a function, the program  
instructions are further computer-executable to implement invoking the Java method on the service in accordance  
with the information representing the Java method call included in the message




Fig. 1  
(Prior Art)




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10a




Fig. 10b






Fig. 11a




Fig. 11b




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23






Fig. 24




Fig. 25




FIG. 26a




FIG. 26b




Fig. 27




Fig. 28




Fig. 30





Fig. 29

Fig. 31






Fig. 32A








Fig. 32B







**Fig. 34**




Fig. 35a




Fig. 35b




Fig. 36




Fig. 37




Fig. 38




Fig. 39a




Fig. 39b




Fig. 40a




Fig. 40b






FIG. 41





FIG. 42a

FIG. 42b






FIG. 42c




FIG. 43




FIG. 44




Figure 45a




Figure 45b




Figure 45c




Figure 45d




Figure 45e






Figure 46




Figure 47




Figure 48